QRC series
C7-T2x
8-pin, miniature relay, 2-poles, twin contact, faston

Type	**C7-T2x/ ... V** Standard relays for low level 2 change-over bifurcated contacts
Maximum contact load	**6 A/250 V AC1 6 A/30 V DC1**
Recommended minimum contact load	**1 mA/5 V** (with 10 µ Au) **5 mA/5 V** (standard contact)

Contacts

Material	Standard	Code 1	AgNi + 0,2 µ Au
	Optional	Code 2	AgNi + 10 µ Au
Rated current			6 A
Switch-on current max. (20 ms)			15 A
Switching voltage max.			250 V
AC load			1,2 kVA
DC load			see fg. 2

Coil

Coil resistance	see table; tolerance ± 10 %
Pick-up voltage	≥ 0,8 x U_N
Release voltage	≥ 0,1 x U_N
Nominal power	1,2 VA (AC)/1 W (DC)

Coil table

VAC	Ω	mA	VDC	Ω	mA
24	174	50	12	148	85
48	686	25	24	594	43
115	4K3	10,4	48	2K3	21
230	18K6	5,2	110	11K4	11

Insulation

	Volt rms, 1 min
Contact open	1000 V
Contact/contact	2,5 kV
Contact/coil	2,5 kV
Insulation resistance at 500 V	≥1 GΩ
Insulation, IEC 61810-5	2,5 kV/3

Specifications

Ambient temperature operation/storage	-40 (no ice)….60 °C /-40 ... 80 °C
Pick-up time/bounce time	16 ms/≤ 3 ms
Release time/bounce time	8 ms/≤ 1 ms
Mechanical life	AC: 10 Mill./DC: 20 Mill. switching cycles
AC voltage endurance at rated load	≥100000 switching cycles
Switching frequency at rated load	≤ 1200/h
Protection class	IP40
Weight	43 g


Standard types

AC 50 Hz/60 Hz: 24, 48, 115, (120), 230, (240)	**C7-T21/AC ... V**	**C7-T22/AC ... V**
LED	**C7-T21X/AC ... V**	**C7-T22X/AC ... V**
DC 24, 48, 110	**C7-T21/DC ... V**	**C7-T22/DC ... V**
LED	**C7-T21X/DC ... V**	**C7-T22X/DC ... V**
Free wheeling diode	**C7-T21DX/DC ... V**	**C7-T22DX/DC ...V**
Polarity and free wheeling diode	**C7-T21FX/DC ... V**	**C7-T22FX/DC ... V**
AC/DC bridge rectifier 24 V, 48 V, 60 V	**C7-T21BX/UC ... V**	**C7-T22BX/UC ... V**

"..." Enter the voltage for full type designation

Accessories

Socket: **S7-M, S7-I/O, S7-L, S7-P, S7-P0**



Connection diagram




Fig. 1 AC voltage endurance






Fig. 2 DC load limit curve



Dimensions [mm]



Technical approvals, conformities

IEC 61810; EN 60947