# *Product datasheet*
*Characteristics*

# zcy39
limit switch lever ZCY - thermoplastic roller lever Ø50 mm



## Main

| | |
|---|---|
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCY |
| Product compatibility | XCKD<br>XCKP<br>XCKT |
| Associated head | ZCE01<br>ZCE05 |
| Movement of operating head | Rotary |
| Type of operator | Roller lever spring return thermoplastic (roller diameter 50 mm) |
| Tracks | No track |
| Type of approach | Lateral approach |

## Complementary

| | |
|---|---|
| Switch actuation | By 30° cam |
| Positive opening | With |

## Environment

| | |
|---|---|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS | Compliant - since 0851 - Schneider Electric declaration of conformity |
| Product environmental profile | Available |
| Product end of life instructions | Available |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.