KERN **KFU 600V20M**

U-Weighing bridge, Load range: painted steel



Category

Brand	KERN
Product categoriy	Component
Product group	Weighing bridge
Product family	KFU-V20-IP67

Measuring System

Weighing capacity [Max]	600 kg
Readability [d]	200 g
Minimum weight [Min]	4 kg
Loadcell type	ZEMIC H8C 0.5 ton

Construction

Dimensions weighing surface (W×D)	1190×840 mm
Dimensions weighing surface	1190×840 mm
Dimensions weighing platform (W×D×H)	1361×840×80 mm
Material weighing plate	steel, powder-coated
Material platform	steel, powder-coated
Material load cell(s)	alloyed steel
Levelling feet adjustable	✓
Transport wheels	✓
Cable length	5 m
Allowed cable length display device [Max]	5 m
Platform Construction	Welded load plate; smooth surface
Load cells - number	4

Functions

IP protection - complete device	IP67 (load cell)
IP protection - load cell	IP67

Approval

Conformity assessment possible ex works	✓
Verification scale interval [e]	200 g

Services (optional)

Article number for conformity assessment	965-230
Article number for DAkkS calibration	963-130

Packing & Shipping

Delivery time	2 d
Dimensions packaging (W×D×H)	1410×890×310 mm
Shipping method	Freight
Net weight approx.	55 kg
Gross weight approx.	90 kg
Shipping weight	87 kg

Product information

GTIN/EAN number	4045761119086
REACH classification	no prohibited substances

Pictograms

STANDARD



FACTORY

