



TEGERA® 465

Learn more

Cut resistant glove, PU, palm-dipped, smooth finish, cut resistance level D, 18 gg, CRF® Technology, polyester, spandex, stainless steel fibre yarn, Cat. II, breathable back, water and oil repellent palm, for fine assembly work

CHARACTERISTICS

- High level of protection
- Extra comfortable
- Good grip
- Extremely good fingertip sensitivity
- Extra flexible

FUNCTIONS

- Thin
- Reinforcement between index finger and thumb

CRF®

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Cut injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Assembly, sheet-metal work, engineering, transport work, warehouse work, metalwork

PRIMARY INDUSTRIES OF USE

Rubber and plastic, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, logistics

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Cut resistant gloves
CATEGORY Cat. II
LINING MATERIAL 18 gg, CRF® Technology, HPPE, Nylon, Spandex, Stainless steel fibre yarn
LENGTH 210-275 mm
DEXTERITY 5
GRIP DESIGN Smooth finish
COLOUR Grey
PAIRS PER: BUNDLE/CARTON 6/60
DISPLAY TYPE Bulk pack
DIPPING Palm-dipped
DIPPING MATERIAL PU
CUFF STYLE Knitwrist cuff
CUFF MATERIAL Textile
CUT RESISTANCE (EN ISO 13997) Cut resistance level D
CUT RESISTANCE (EN ISO 13997) TDM: 17.1 N
INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Stainless steel fibre yarn, Elastane
OUTER MATERIAL SPECIFICATION Polyurethane

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

EN 388:2016
4X31D

EN 420:2003
+A1:2009

ANSI A4 CUT

FEATURES

Cut protection

SIZE		ARTICLE NUMBER	EAN
5	XXS	465-5	7340118339894
6	XS	465-6	7340118324906
7	S	465-7	7340118324913
10	XL	465-10	7340118324883
11	XXL	465-11	7340118324890

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.