SKYTEC®

NINJA X4™

ALSO KNOWN AS SAPPHIRE X4™

CUT RESISTANCE WITH A BI-POLYMER PALM

A supple and lightweight glove providing a good level of cut resistance, dexterity and comfort. The bi-polymer coating delivers excellent grip in both wet and dry handling conditions.

FEATURES

- Cut resistant: Level B (EN 388:2016)
- High resistance to abrasion
- Breathable liner
- Silicone free
- Elasticated wrist provides a secure fit
- Mottled grey and black colouring helps to extend wearable life
- Sanitized® antimicrobial finish provides extra freshness



CUT LEVEL B

Sanitized Actifresh

VENDING MACHINE COMPATIBLE

SUITABLE FOR

Typical Industries

- Engineering
- Glass
- Packaging

Suitable Applications

- Assembly
- Bottling or Canning
- General handling

CERTIFICATION

UKCA

CE

CAT II

EN 388:2016

4X31B

ASTM / ANSI 105-2016

A2

CUT

See overleaf for explanation

Globus GROUP

SKYTEC® NINJA X4™

ALSO KNOWN AS SAPPHIRE X4™

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge nylon, glass fibre
	COATING:	Bi-Polymer
COLOUR	Grey/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

			VEND COMPATIBLE OPTION	
SIZE	**CODE**	**PACKAGING**	**CODE**	**PACKAGING**
7/S 8/M 9/L 10/XL 11/XXL	SKY031 SKY032 SKY033 SKY034 SKY035	10 pairs per bag 120 pairs per case	SKYV031 SKYV032 SKYV033 SKYV034 SKYV035	120 individually bagged pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE	
Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus GROUP

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

©2022 Globus (Shetland) Ltd | SKY-DATA-NINJA-X4-0722_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777).
UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.