Date: 12/04/2023

TCS2CC - 10 ... 70 °C 1/2 NPT male Adaptor M20x1,5-F

compact temperature switch

Item number: 48796522

Quantity: 1 pcs.

Order code: TCS2CC-CACB-EISZZZZC1ZZ ZCK
F5-C1- - - - -

Overview:
TCS2CC - 10 ... 70 °C 1/2 NPT male Adaptor M20x1,5-F
compact temperature switch TCS
switch enclosure: aluminium,copper-free
sensor version: remote mounting with capillary, length 2 m
contact version: 1xSPDT, gold-plated contact, hermetically sealed with argon gas
setting range: 10 ... 70 °C, working range -40 ... +70°C, proof temperature +90°C
Set point definition: Set Point not defined
Process connection: 1/2 NPT male
Electrical connection: Adaptor M20x1,5-F
Mounting: standard direct or wall mounting, fixing bore on the case
Sensor Dimensions: active length X = 71 mm, insertion length Ymin = 100 mm, Ymax = 350 mm, bulb diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
Approvals / Certificates
IECEx-ATEX Ex ia

Details:
compact temperature switch
model TCS
Specifications according to data sheet: TV 31.64
Repeatability of set point: ≤ 1% of span
switch enclosure: aluminium,copper-free
sensor version: remote mounting with capillary, length 2 m
1xSPDT, gold-plated contact, hermetically sealed with argon gas
10 ... 70 °C, working range -40 ... +70°C, proof temperature +90°C
Set Point not defined
Process connection: 1/2 NPT male
Electrical connection: Adaptor M20x1,5-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Sensor Dimensions: active length X = 71 mm, insertion length Ymin = 100 mm, Ymax = 350 mm, bulb diameter D=9,5 mm
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Unit: °C
TCS2CC

© 2023 - WIKA Instruments s.a.r.l.

Date: 12/04/2023

Approvals / Certificates
IECEx-ATEX Ex ia

© 2023 - WIKA Instruments s.a.r.l.