DERBY NOIR S3 SRC

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



memoryfoam
By LEMAITRE

- **78% high density recycled foam**



Sizes 35 to 50 Ref. **DERNS30NR**

Product Highlights

- **Upper in water-repellent suede microfiber** : lightness, breathability, tearing and abrasion resistant
- **Breathable perforated microfiber lining:** anti-allergic and anti-microbial, thermoregulatory effect. Prevents odor formation.
- **Memory Foam by Lemaitre anti-bacterial insole with memory foam**, energy absorption and dissipation, MSD prevention
- **Derby shoe characterized by open lacing:** easy to put on, adapts to the morphology of the foot. Good hold, comfort. Suitable for strong instep
- **Casual chic style:** elegance and relaxation, a great classic of the city shoe revisited as a safety shoe.
- **Protective toe cap:** HDFC composite fiber.
- **Puncture resistant midsole:** high tenacity composite textile «0» penetration.



Anti-static sole CARBON PU2D

- **Developed outsole for industrial and urban floors:** good adhesion
- **Large bearing surface:** optimal stability
- **Shock absorption:** preservation of the back and joints
- **Sculpted studs:** reinforced grip
- **Conformal to bent positions:** knee notches and crouching

USE

- Service company, crafts, management.
- Logistics, services, handling, distribution, transportation.

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

Lemaitre vous protège.

DERBY NOIR S3 SRC

Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material :** water-repellent microfiber velvet effect
- **Tongue :** water-repellent microfiber
- **Lining :** smooth perforated microfiber

Characteristics of the sole

- **Designation:** CARBON PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,34 (standard ≥ 0,32)
  forward heel slip: 0,31 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,22 (standard ≥ 0,18)
  forward heel slip: 0,20 (standard ≥ 0,13)

VARIANT



Derby marine S3 SRC
DERMS30BM

Practical information

Weight of one shoe size 42 : 478 g

AET N° 0075/007/161/09/19/2718 EXT 17/01/22

Packaging

Sizes 35 to 43	Sizes 44 to 50
shoebox 316 x 204 x 121 mm	**shoebox** 345 x 230 x 122 mm
carton 635 x 445 x 325 mm	**carton** 635 x 485 x 355 mm
10 shoeboxes per carton	10 shoeboxes per carton

Gencods

35	3237154464359	**43**	3237154464434
36	3237154464366	**44**	3237154464441
37	3237154464373	**45**	3237154464458
38	3237154464380	**46**	3237154464465
39	3237154464397	**47**	3237154464472
40	3237154464403	**48**	3237154464489
41	3237154464410	**49**	3237154464496
42	3237154464427	**50**	3237154464502

Memo for basic and additional requirements of the standard EN ISO 20345 : 2011

Safety footwear			
SBP			
S1			A E Fo
S1P			A E Fo
S2			A E Fo Wru
S3			A E Fo Wru

200 J toe cap: Protection of the forefoot against shocks and crushing

Anti-perforation insert 1100 N: foot protection against perforation.

- **A** Anti-static footwear
- **E** Shock absorption at the heel
- **Fo** Fuel oil-resistant outsole
- **Wru** Water penetration and water absorption resistant upper
- **ESD** Electrostatic discharge
- **Ci** Insulation against cold
- **Hi** Insulation against heat
- **Hro** Outsole resistance to hot contact
- **Wr** Water resistant
- **An** Ankle protection

- **SRA** Slip-resistance on ceramic floors with detergent
- **SRB** Slip-resistance on steel floors with glycerol
- **SRC** = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

Member of SYNAMAP

DON_LS 04 TDS 0177
update: 15/04/24