Cut protection

KRYTECH 622

Very high risk - ISO E

Very high cut protection without any compromise on comfort and dexterity.



CUT PROTECTION
LEVEL E

EN388

4X43E

CATEGORY 2

CE

ISO 13997:

29.5 N

DEXTERITY

EN420:
5/5

OEKO TEX®
STANDARD 100
CQ 979/2
IFTH

SPECIFIC ADVANTAGES

Cut protection

- Very high cut protection without any compromise on comfort, dexterity and breathability

Comfort

- A seamless plaited glove for very good fit, dexterity and flexibility.

Durability

- Optimal durability that offers better productivity and optimizes your costs

Suitable for touchscreen

- Can be used with touch devices & touch screen

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

- Washable up to 5 times at 60°C , allowing to extend glove lifespan, reducing costs and waste.

Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

INDUSTRIES

- Automotive/mechanical industry
- Mechanical industry
- Construction Industry (Metalworkers/Locksmiths)
- Glass industry

APPLICATIONS

- Handling and installing metal structures
- Handling sheet metal
- Handling glass sheets
- Assembly of small, oil and grease free parts
- Cutting and stamping metal
- Handling aluminium strips
- Handling of thick, untrimmed sheet metal (not sharp-edged)
- Handling sharp sheet metal
- Metal shearing or cutting
- Assembly of thin metal sheets

Edit 29/11/2024

Cut protection

KRYTECH 622

Very high risk - ISO E

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	3	E	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Black Grey
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2,8E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1,1E+10 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/carton 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/19/1551
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 29/11/2024