SOFTANE™ BTP

JALFIR SAS
JJE41

S3 CI AN SRC
EN ISO 20345:2011
35 to 47



Spécial BTP

- **Water-repellent full-grain leather**
- **Dual density Softane™ sole**
- **Polymère toe cap / Antiperforation rustproof steel**
- **Antistatic**

- High-laced boot style outdoor, **adapted to the building sector**. Brown and black color.
- Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- Ankle protector system on each side of the shoe. Inside result 5,9 kN, outside result 5,9 kN.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Fastened by six pairs of lace stays and 2 pairs of open hooks. Laces 130 cm.
- Padded, "3D' lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
- Tabs at the back for easy pull-on.
- Upper lined in breathable 3D mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- **POLYJA**L footbed single-block structure made of soft polyurethane and textile, anatomical, perforated in the font part and with heel schock absorbers.
- Heel stiffener to reinforce the heel seat.
- Ergonomic shoe, with broad synthetic polymer toe cap **SPRINGTANE** , for saving on weight (50% lighter than steel). Impact resistance to 200 Joules.
- **Stainless rustproof steel midsole**.

- Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole.

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,30** (>0,18) – On the heel: **0,28** (>0,13)

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorbtion > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.



Weight	Gross weight (42) : 1628 g / Net weight (42) : 1420 g		
Size	35 to 39	40 to 45	46 to 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions carton (mm)	685 x 255 x 345	685 x 505 x 345	685 x 255 x 345
Dimensions box shoe (mm)	340 x 245 x 133		

Non contractual document
Copyright JALLATTE
Limited distribution

23/11/2015

Jallatte®
www.jallatte.com