Date: 11/04/2023

F73.100/4, 0...120°C, L1=300 mmx8mm,

Gas actuated thermometer, stainless steel series

Item number:	48788515
Quantity:	1 pcs.
Order code:	F73.100-C1F-4GD-C0300-N04-2-Z-HZZ-ZZZZZZ G7 FZZZEVZZIWP-AZ1ZZZZZ2ZZZZ
Overview:	F73.100/4, 0...120°C, L1=300 mmx8mm, G 1/2 B axial Panel mounting flange, stainless steel standard capillary stainless steel 1.4571 Capillary length: 4 m laminated safety glass class 1 per EN 13190 *WIKA* with Serial number
Details:	Gas actuated thermometer, stainless steel series Specifications according to data sheet: TM 73.01 Case: stainless steel Stem material: stainless steel Model: F73.100, nominal size 100, with capillary Unit: °C Scale range: 0 °C ... 120 °C Connection design: 4, compression fitting, sliding on stem Process connection: G 1/2 B Stem diameter: 8 mm Insertion length L1: 300 mm Capillary: standard capillary stainless steel 1.4571 Capillary length: 4 m Design of case mounting: Panel mounting flange, stainless steel Ignition protection type: without Zone: without Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 Window: laminated safety glass Case: Stainless steel Connector location: axial Manufacturer logo: *WIKA* Permissible ambient temperature: -40 … +60 °C with Serial number

© 2023 - WIKA Instruments s.a.r.l.