Specifications

Eaton 278426

Catalog Number: 278426

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/OE, 1 NCL, Side mounted, Screw terminals, DILM40 - DILM225A



General specifications

Product Name
Eaton Moeller® series DILM auxiliary contact module

Catalog Number
278426

EAN
4015082784263

Product Length/Depth
77 mm

Product Height
77 mm

Product Width
15 mm

Product Weight
0.04 kg

Certifications
VDE 0660
CSA
CSA-C22.2 No. 14-05
IEC/EN 60947
IEC/EN 60947-4-1
UL File No.: E29184
UL 508
UL Category Control No.: NKCR
CSA File No.: 012528
UL
CSA Class No.: 3211-04
CE

Catalog Notes
Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.

Powering Business Worldwide

Features Functions

Functions
For standard applications

Number of poles
Two-pole

Electric connection type
Screw connection

General

Degree of protection
IP20

Lifespan, electrical
1,300,000 Operations (at 230 V, AC-15, 3 A)

Model
Top mounting

Mounting method
Side mounting

Connection
Screw terminals

Overvoltage category
III

Pollution degree
3

Protection
Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)
6000 V AC
6000 V

Type
Side-mounting auxiliary contacts

Climatic environmental conditions

Ambient operating temperature - min
-25 °C

Ambient operating temperature - max
60 °C

Ambient operating temperature (enclosed) - min
-25 °C

Ambient operating temperature (enclosed) - max
40 °C

Ambient storage temperature - min
-40 °C

Ambient storage temperature - max

Terminal capacities

Terminal capacity (flexible with ferrule)
1 x (0.75 - 2.5) mm²
2 x (0.75 - 2.5) mm²

Terminal capacity (solid)
1 x (0.75 - 2.5) mm²
2 x (0.75 - 2.5) mm²

Terminal capacity (solid/stranded AWG)
18 - 14

Screw size
M3.5, Terminal screw

Screwdriver size
0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

80 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

2, Terminal screw, Pozidriv screwdriver

Tightening torque

1.2 Nm, Screw terminals

Electrical rating

Rated operational current (Ie)

6 A at 60 V, DC L/R ≤ 15 ms (with 1 contact in series)

3 A at 110 V, DC L/R ≤ 15 ms (with 1 contact in series)

10 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in series)

1 A at 220 V, DC L/R ≤ 15 ms (with 1 contact in series)

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V

4 A

Rated operational current (Ie) at AC-15, 500 V

1.5 A

Rated operational current (Ie) at DC-13, 24 V

2 A

Rated operational current (Ie) at DC-13, 60 V

1.5 A

Rated operational current (Ie) at DC-13, 110 V

0.8 A

Rated operational current (Ie) at DC-13, 220 V, 230 V

0.3 A

Rated insulation voltage (Ui)

690 V

Rated operational voltage (Ue) at AC - max

500 V

Short-circuit rating

Rated conditional short-circuit current (Iq)

1 kA at 500 V

Short-circuit protection rating

Conventional thermal current Ith

Conventional thermal current ith at 60°C (3-pole, open)

10 A

Max. 16 A gG/gL, Fuse, Without welding, Auxiliary contacts

Short-circuit protection rating without welding

16 A gG/gL, 500 V, Max. Fuse, Contacts

Switching capacity

Switching capacity (auxiliary contacts, general use)

1 A, 250 V DC, (UL/CSA)

15 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

P300, DC operated (UL/CSA)

Contacts

Control circuit reliability

$\lambda < 5 \times 1/10^7$ (1 failure at 2,000,000 operations for U_e = 24 V DC, Umin = 17 V, Imin = 5.4 mA)

Number of contacts

1 (normally open, early make)

1 (normally closed, late break)

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

1

Safety

Safe isolation

440 V AC, Between auxiliary contacts and main contacts, According to EN 61140

440 V AC, Between auxiliary contacts, According to EN 61140

440 V AC, Between coil and auxiliary contacts, According to EN 61140

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0.11 W

Rated operational current for specified heat dissipation (In)

4 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Resources

Catalogs

SmartWire-DT Catalog

Product Range Catalog Switching and protecting motors

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004799.pdf

DA-DC-00004818.pdf

DA-DC-00004817.pdf

DA-DC-00004070.pdf

DA-DC-00004229.pdf

DA-DC-00004781.pdf

DA-DC-00005043.pdf

DA-DC-00004782.pdf

DA-DC-00004802.pdf

DA-DC-00005052.pdf

Drawings

eaton-contactors-contact-dilm-accessory-3d-drawing-006.eps

eCAD model

ETN.278426.edz

Installation instructions

IL03407034Z

Installation videos

WIN-WIN with push-in technology

mCAD model

dil_m32_xhi11_s

dil_m32_xhi11_s.stp

Wiring diagrams

eaton-contactors-mounting-dilm-accessory-wiring-diagram-002.eps

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia