Datasheet: H65Z-C

Connectors / Weatherproof Connectors

Watertight Cable Joint IP67 3 pole



Technical Specification

Product Code	H65Z-C
Feature 1	Can be temporarily submersed in water
Feature 2	For repairing or extending outdoor cables yp to 3 core 2.5mm2
Feature 3	Max current 15A
Feature 4	Cable diameter Max 12.5mm Min 6mm
Barcode	5012739065309
CE	Y
Colour	Black
Company DUNS Number	216156018
Country of Origin	China
Current (I)	15

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 19/02/26

Datasheet: H65Z-C

Finish body	Gloss
Frequency (Hz) max	60
Frequency (Hz) min	50
Greenbrook Guarantee (Years)	1
HS Code	8536901000
Ingress Protection (IP)	IP67
Installation method	Inline
Knock-out Dimensions	Cable Dia: Max 12.5mm/Min 6mm
Knock-out Qty	2
Materials Main Body	Nylon
Min Order Qty	1
Operating Temperature Range max C	50
Operating Temperature Range min C	-20
Package Product Max. Length (mm)	240
Package Product Max. Height (mm)	35
Package Product Max. Width (mm)	75
Product (only) Max. Depth (mm)	120
Product (only) Max. Height (mm)	32
Product (only) Max. Width (mm)	32
Product Weight net (g)	68.5
Sales Pack Qty	1
StatusCode	Active
UKCA	Y
Voltage (VAC) MAX (V)	240
Voltage (VAC) Min (V)	220
Voltage (VAC) Rated (V)	230
Feature 5	32 x 120mm

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 19/02/26