PRODUCT-DETAILS

SPL25/25M

25MM GS-PVC COAT CONDUIT 25M - BL



General Information

Extended Product Type:	SPL25/25M
Product ID:	7TCA296030R0193
EAN:	5020963000263
Catalog Description:	25MM GS-PVC COAT CONDUIT 25M - BL
Long Description:	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black
Display Name:	SPL25/25M

Additional Information

Product Main Type:	Adaptaflex Flexible Cable Protection
Application:	Liquid Tight - Indoors / Outdoors, Marine, Buildings

Ordering

EAN:	5020963000263

© 2026 ABB. All rights reserved.

UPC:	786210247052

Dimensions

Outside Diameter:	26.4 mm

Technical

Number of Batteries:	0
Color:	Black
Material:	Galvanized Steel Core with PVC Covering

Environmental

WEEE Category:	Product Not in WEEE Scope
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5020963000263
Package Level 1 Height:	10 in 254 mm
Package Level 1 Depth / Length:	16 in 406 mm
Package Level 1 Width:	16 in 406 mm

Certificates and Declarations

Declaration of Conformity - CE:	9AKK107492A9618
RoHS Declaration:	9AKK107992A8994
REACH Declaration:	9AKK107992A8994

External Classifications and Standards

ETIM 8:	EC001179 - Protective metallic hose
ETIM 9:	EC001179 - Protective metallic hose
UNSPSC:	39131706

Categories

© 2026 ABB. All rights reserved.

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems



© 2026 ABB. All rights reserved.