



jalas® GRAN PREMIO 1668W

EN ISO 20349-2:2017 S3, SRC, WG, HRO, CI, HI EN ISO 20345:2011 S3, SRC, WG, HRO, CI, HI ASTM F2413-18 M/I/C PR ASTM F3445-21 SR

Learn more

WELDING BOOT WITH MANY FEATURES

Durable and comfortable mid-cut welding boot certified in compliance with EN 20349-2, with Thinsulate™ lining for extra heat insulation. Specially treated leather with heat resistance para-aramid thread in the seams provides a max operating heat limit of 400°C/752°F for 30 minutes. The removable insole has advanced shock absorbing with two protective zones PORON® XRD® and the oil and heat-resistant nitrile outer sole means excellent grip. JALAS® aluminium toe cap and steel nail penetration insert help prevent injuries.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Pull loops
- ESD
- Water repellent
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Easy clean upper
- Ventilating insole
- Thinsulate™ heat insulation
- Wide fit
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Double shock absorption zones

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, all-year use, warm surfaces, environments with risk for outsole penetration, dirty environments, harsh environments

PRIMARY AREAS OF USE

Hot work, metalwork, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE

Metal fabrication

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Steel
FITTING Wide
COLLECTION Gran Premio
UPPER MATERIAL PU-coated leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, Thinsulate™
INSOLE FX2 Pro-X
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING Hook-and-loop
COLOUR Black
NET WEIGHT, (SIZE 42) 1.34 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

Information/UIS

EN ISO 20349-2:2017
S3, SRC, WG, HRO, CI, HI

EN ISO 20345:2011
S3, SRC, WG, HRO, CI, HI

ASTM F2413-18
M/I/C
PR

ASTM F3445-21
SR

FEATURES

- Oil-resistant outsole
- ProNose toe reinforcement
- Wide fit
- Water repellent
- Aluminium toecap
- Nail protection in steel
- Heat-resistant outsole
- Ergothan Shock Absorption System
- Heat-resistant upper
- Anti-static properties
- ESD

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1668W-36	6408487542022
37	4	5	6	1668W-37	6408487541537
38	5	5½	6½	1668W-38	6408487541575
39	6	6½	7½	1668W-39	6408487541612
40	6½	7½	8½	1668W-40	6408487541650
41	7	8	9	1668W-41	6408487541698
42	8	9	10	1668W-42	6408487541735
43	9	9½	11	1668W-43	6408487541773
44	10	10½	11½	1668W-44	6408487541810
45	10½	11	12½	1668W-45	6408487541858
46	11	12	13	1668W-46	6408487541896
47	12	13	14	1668W-47	6408487541933
48	13	13½	14½	1668W-48	6408487541971

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.