Specifications

Eaton 106429



Catalog Number: 106429

Eaton xEnergy Basic LV systems Low voltage switchgear. Glass door, for HxW=2060x600mm, left, white

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	106429
EAN	**Product Length/Depth**
4015081061990	45 mm
Product Height	**Product Width**
2010 mm	615 mm
Product Weight	**Compliances**
19.8 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory

Accessory consideration

Floor-standing enclosure

Service distribution board IVS

Special features

can be used as right door for two-leaf versions

order together with standard door for 600 mm

Protective cover mounted on left

Transparent doors

Two doors

Mounting from front, fast mounting, hinges on left or right possible

Door opening angle 167°

3-point turn lock with roller lever lock

Transparent panels from 4 mm safety glass (EN 12150-1, DIN 1249)

Type

Additional equipment for floor-standing service distribution board IVS

Features

EMC-version

Version as glazed door

Accessory/spare part type

Doors

Surface finishing

Powder coating

With powder coating

Color

Traffic white (RAL 9016)

White

Degree of protection

IP30

NEMA Other

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Unit type

Modular system

Suitable for height

2060 mm

Suitable for width

1200 mm

Cover/door color

Transparent

Cover/door type

Three-point turn-lock

Material

Sheet steel/glass

Steel

Housing material

Sheet steel/glass

Model

Stop door

Mounting method

Floor standing distribution board

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia