Chemical protection

ULTRANEO 420

Frequent contact | intermittent wear

Extremely supple with freedom of movement for standard chemical protection



CHEMICAL PROTECTION
TYPE A

EN388
2121X

EN ISO 374-1
TYPE A
ALMNST

EN ISO 374-5

CATEGORY 3

DEXTERITY
EN420:
5/5

0334

SPECIFIC ADVANTAGES

Comfort

- Freedom of movement, due to the supple quality of the neoprene and the comfort of the cotton flock-lining

Productivity

- Good grip due to the embossed texture

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Handling, loading and unloading of chemicals
- Industrial cleaning, maintenance
- Preparation of industrial glues
- Spreading fertilizer
- Electric accumulator and battery manufacturing

Edit 01/12/2024

Chemical protection

ULTRANEO 420

Frequent contact | intermittent wear

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

2	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN ISO 374-1



TYPE A

CHEMICAL RISKS

A: Methanol
L: Sulphuric acid 96%
M: Nitric acid 65%
N: Acetic acid 99%
S: Hydrofluoric acid 40%
T: Formaldehyde 37%

EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Polychloroprene and natural latex
Cuff characteristic	Straight cuff
Colour.s	Black
Length (cm)	32
Thickness (mm)	.75
European sizes	6 7 8 9 10 11

LOGISTIC DETAILS

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/05/18/0802
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 01/12/2024