DATASHEET

BU-P2249-C-XX

(Test Lead, BNC with Strain Relief on Each End, RG-58C/U)



- **Materials:**
  - Cable: Cable is RG 58C/U, complies to Mil-M17/155-00001
    Jacket is non-contaminating PVC
    Center conductor is 20 AWG (19x33) tinned copper
    Shield is tinned copper braid (95% coverage)
  - Male BNC: Body is tarnish resistant nickel plated brass
    Center Contact is Gold plated brass
    Insulator is PTFE
  - Strain Relief is Molded PVC that is bonded to the BNC.

- **Ratings:** Impedance: 50 Ohms
  Capacitance per foot: 30.8 pf
  Power Loss/100 Ft. @ 1 MHz: .40 dB
  Hands free testing to 500 VRMS
  Operating Temperature: -40°C to 85°C

- Ordering: The "XX" in the part number represents the length in Inches.
  Standard lengths: 6", 12", 24", 36", 48", 60", 72", 120", 144" 180", 240", 300", and 600"
- RoHS Compliant, CE Compliant

Mueller Electric Company
1208 Massillon Rd. Ste. N-1500
Akron, OH 44306-4524

www.muellerelectric.com

Toll Free: 800.955.2629
Phone: 330.780.2525
Fax: 330.780.2524