



CONNECT AND PROTECT

Varistar Electronics

nVent
SCHROFF

OVERVIEW

MAIN KATALOG

Cabinets 1

Wall mounted cases 2

Accessories for cabinets and wall mounted cases . . 3

Climate control . . 4

Electronics cases 5

Subracks/ 19" chassis 6

Front panels, plug-in units 7

Systems 8

Power supply units 9

Backplanes 10

Connectors, front panel component system 11

Appendix 12





01008004



01009002

19" panel mounts integrated in decorative frame




01005014

All-round gasketing to IP 55



01009002

Side panels with quick-release fastener, optionally lockable



01005014

3-point locking with contradirectional bolts

Cabinets – Varistar Electronics

OVERVIEW

THE UNIVERSAL CABINET FOR ELECTRONICS

- **Selectable stability, static load-carrying capacity up to 800 kg**
- **Professional solutions for cable ducting**
- **Variable ventilation concepts, active and passive**
- **Various versions in ServicePLUS configuration**

VARISTAR DECO



01004001

- Open at front, with deco frame and integrated 19" panel mounts

VARISTAR IP 20



01004002

- With glass door and single point locking

VARISTAR IP 55



01004003

- With glass or steel door and 3-point locking

SERVICEPLUS

e.g. individual configuration and assembly
e.g. modifications (cut-outs, special colours)
e.g. variants of uprights (Slim-Line, Heavy-Duty)
e.g. custom solutions (special sizes)

Overview **1.10**

VARISTAR Platform 1.4
Dimensions 1.8

VARISTAR Deco .. **1.12**
VARISTAR IP 20 .. **1.13**
VARISTAR IP 55 .. **1.14**

Accessories
Lever handle **1.15**
Base plate **1.15**
Base/plinth **1.16**
Mounting plate ... **1.17**
19" swing frame 1.18
19 panel/slide mount **1.19**
19" fixing materials kit, M6 ..... **1.19**
Slide rails **1.20**
19" shelves **1.21**
Depth members .. **1.24**
C horizontal rail .. **1.24**
Cable tie, Velcro **1.26**


ServicePLUS IP 20 ..... **1.27**
ServicePLUS IP 55 ..... **1.39**
ServicePLUS Interior configuration **1.44**

VARISTAR EMC ... 1.54
VARISTAR Seismic 1.84
VARISTAR datacom and Networking Technology 1.124
VARISTAR air/water heat exchanger 1.224

VARISTAR DECO



01004001



01004151

- Open at front (no door)
- 19" panel mounts integrated into decoration frame
- Rear door with single point locking, side panels with quick release fastener
- Static load-carrying capacity 400 kg (Slim-Line)

DELIVERY COMPRISES (assembled)

Item	Qty	Description
1	1	Welded basic frame, Slim-Line, St profile, zinc-plated, powder-coated, RAL 7021
2	4	Adjustable foot, assembled
3	1	Raised top cover, St, RAL 7021, with 10 mm air gap all around
4	1	Decorative frame, Al, integrated 19" panel mounts at the front, RAL 7035
5	2	Adapter bracket, St, 2 mm, RAL 7035, front, for assembling shelves and slide rails
6	1	Rear door, St, 180° hinge, single point locking and key with safety lock, RAL 7035
7	2	Side panel, St, with quick-release fastener, RAL 7035
8	1	GND/earthing kit, supplied loose

ORDER INFORMATION

Height U	Height H mm	Width W mm	Depth D mm	Part no.
38	1800	600	600	**10130-001**
38	1800	600	800	**10130-002**
42	2000	600	600	**10130-003**
42	2000	600	800	**10130-004**
Castors load-carrying capacity 400 kg, PS/St, PU 4 pieces, 2 locking, 2 non locking				**23130-077**
Castors with integrated adjustable feet load-carrying capacity 400 kg, PU 4 pieces				**23130-078**
Lever handle for single point locking with push button, 1 piece				**23130-067**
DIN profile half cylinder, common locking for lever handle (1 key fits all locks) incl. 2 keys				**25127-995**
Lifting eye for raised top cover PU 4 pieces				**23130-085**


NOTE

- Lever handle can be added to rear door
- For more dimensions and versions see ServicePLUS IP 20, starting on page 1.27
- Please order base plate separately, see page 1.15
- Please order base/plinth separately, see page 1.16
- For assembly of shelves and slide rails another pair of panel/slide mounts is necessary, see page 1.19

VARISTAR IP 20



01004002



01004152

- With glazed front door
- Doors with single point locking, side panels with quick release fastener
- Type of protection IP 20
- Static load-carrying capacity 400 kg (Slim-Line)

DELIVERY COMPRISES (assembled)

Item	Qty	Description
1	1	Welded basic frame, Slim-Line, St profile, zinc-plated, powder-coated, RAL 7021
2	4	Adjustable foot, assembled
3	1	Raised top cover, St, RAL 7021, with 10 mm air gap all around
4	1	Front door, glazed, safety glass, 6 mm, 180° hinge, RAL 7035, single point locking, key lock cover
5	1	Rear door, St, 180° hinge, RAL 7035, single point locking, key with safety lock
6	2	Side panel, St, quick-release fastener with safety lock, RAL 7035
7	2	19" panel/slide mount with EIA cut-outs, St, RAL 7035, assembled at front, depth-adjustable in 25 mm increments
8	1	GND/earthing kit, enclosed loose

ORDER INFORMATION

Height U	Height H mm	Width W mm	Depth D mm	Part no.
38	1800	600	600	**10130-005**
38	1800	600	800	**10130-006**
42	2000	600	600	**10130-007**
42	2000	600	800	**10130-008**
Castors load-carrying capacity 400 kg, PS/St, PU 4 pieces, 2 locking, 2 non locking				**23130-077**
Castors with integrated adjustable feet load-carrying capacity 400 kg, PU 4 pieces				**23130-078**
Lever handle for single point locking with push button, 1 piece				**23130-067**
DIN profile half cylinder, common locking for lever handle (1 key fits all locks) incl. 2 keys				**25127-995**
Lifting eye for raised top cover PU 4 pieces				**23130-085**

NOTE

- Lever handle can be added to the doors
- For other dimensions and versions see ServicePLUS configuration IP 20, from page 1.27
- Please order base plate separately, see page 1.15
- Please order base/plinth separately, see page 1.16
- For assembly of shelves and slide rails another pair of panel/slide mounts is necessary, see page 1.19

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

VARISTAR IP 55



01005006



01005014

- With glazed or steel front door
- Doors with 3-point locking and screw-fixed side panels
- Type of protection IP 55
- Static load-carrying capacity 400 kg (Slim-Line)

DELIVERY COMPRISES (assembled)

Item	Qty	Description
1	1	Welded basic frame, Slim-Line, St profile, zinc-plated, powder-coated, RAL 7021, with all around rubber seals
2	4	Adjustable foot, assembled
3	1	Flat top cover, St, RAL 7021
4	1	Front door, St or glazed, RAL 7035, 180° hinge, 3-point locking, lever handle
5	1	Rear panel, screw fixed, St, RAL 7035
6	2	Side panel, screw fixed, St, RAL 7035
7	1	Base plate, multi-piece, with cover plate, St, RAL 7021, with gasket
8	2	19" panel/slide mount with EIA cut-outs, AlZn, assembled at front, depth-adjustable in 25 mm increments
9	1	GND/earthing kit, enclosed loose

ORDER INFORMATION

Height U	Height H mm	Width W mm	Depth D mm	Description	Part no.
42	2000	600	600	With glazed door	**10130-021**
42	2000	600	600	With steel door	10130-022
Castors load-carrying capacity 400 kg, PS/St, PU 4 pieces, 2 locking, 2 non locking					**23130-077**
Castors with integrated adjustable feet load-carrying capacity 400 kg, PU 4 pieces					**23130-078**
DIN profile half cylinder, common locking for lever handle (1 key fits all locks) incl. 2 keys					**25127-995**
Lifting eye for top cover PU 4 pieces					**23130-072**

NOTE

- For other dimensions and versions see ServicePLUS configuration IP 55, from page 1.39
- Please order base/plinth separately, see page 1.16
- For assembly of shelves and slide rails another pair of panel/slide mounts is necessary, see page 1.19

LEVER HANDLE FOR SINGLE POINT LOCKING



01005016

- For installation instead of key lock insert
- To open press push-button
- DIN profile half cylinder retrofittable

DELIVERY COMPRISES

Item	Qty	Description
1	1	Lever handle for single point locking
2	1	Assembly kit


ORDER INFORMATION

Description	Part No.
Lever handle for single point locking	**23130-067**
Accessories	
DIN profile half cylinder, common locking for lever handle (1 key type 333 fits all locks) incl. 2 keys	**25127-995**
DIN profile half cylinder, common locking for lever handle (1 key type 2233 fits all locks) incl. 2 keys	**60130-402**

NOTE

- Other locks such as ASSA, KABA or RONIS available on request

BASE PLATE, MULTI-PIECE



01004050

1: Base plate, multi-piece; 2: Cover plate; 3: Brush strip; 4: Filter kit

- The multi-piece base plate is open at the rear
- The opening may be completed
  - with a filter mat
  - with a brush strip for the cable entry
  - with a cover plate

DELIVERY COMPRISES (kit)

Item	Qty	Description
1	1	Multi-piece base plate, St, 1.5 mm, RAL 7021
5	1	Assembly kit


ORDER INFORMATION

Width mm	Depth mm	Part no.
600	600	**23130-001**
600	800	**23130-002**
Item 2 Cover plate for base plate, multi-piece for 600 mm wide base plate, 200 mm deep, incl. assembly kit, 1 piece		**23130-076**
Item 3 Brush strip for base plate for 600 mm width base plate, 200 mm deep, incl. assembly kit, 1 piece		**23130-074**
Item 4 Filter mat white, class M1 in accordance with EN 799-G3, for 600 mm wide base plate, 200 mm deep, incl. assembly kit, 1 piece		**23130-075**

NOTE

- Is assembled from inside
- Please order cover plate, brush strip or filter mat separately

STATIONARY BASE



D = cabinet depth

- Static load-carrying capacity 1000 kg
- Removable covers allow cable entry from all sides
- Cannot be used in conjunction with castors
- Plinth height 100 mm, with feet adjustable from 112 to 132 mm
- Versions
  - Front/rear trim perforated
  - Front/rear trim solid

DELIVERY COMPRISES (kit)

Item	Qty	Description
1	2	Support with feet, St, 3 mm
2a	2	Solid trim, St, 1.5 mm, RAL 7021
2b	2	Perforated trim, St, 1.5 mm, RAL 7021
3	1	Assembly kit


ORDER INFORMATION

For cabinet width W mm	Front/rear trim	Part no.
600	perforated	**23130-187**
600	plain	23130-387
Item 4 Side trim height 100 mm, depth 600 mm, PU 2 pieces		**23130-169**
Item 4 Side trim height 100 mm, depth 800 mm, PU 2 pieces		**23130-170**

NOTE

- Please order side trims (item 4) separately

BASE/PLINTH, MOBILE



- Load-carrying capacity on castors 400 kg, on adjustable feet 1000 kg
- Plinth height H = 100 mm, with feet adjustable from 126 to 134 mm


DELIVERY COMPRISES

Item	Qty	Description
1	1	Frame, St, 3 mm, RAL 7021, with adjustable feet
2	4	Trim, St, 1.5 mm, RAL 7021
3	4	Castor
4	1	Assembly kit


ORDER INFORMATION

For cabinet width mm	For cabinet depth mm	Part no.
600	600	23130-208
600	800	**23130-209**

MOUNTING PLATE



Full height



010080520 1008053

For partial-height mounting

- For mounting electrical components and sub-assemblies incl. cabling
- Mounting pitch 25 mm in depth and 50 mm in height for partial-height mounting
- Depth members are required for partial-height mounting
- Static load
  - 450 kg at full height, mounted to rear
  - 600 kg at full height, mounted to rear, with additional strengthening brackets

DELIVERY COMPRISES


Item	Qty	Description
1	1	Mounting plate, St, 3 mm, zinc-plated
2	1	Assembly kit


ORDER INFORMATION

For cabinet height mm	Width mm	Part no.
1200 for partial-height mounting	600	23130-413
1800	600	23130-405
2000	600	23130-407
Strengthening bracket for mounting plate PU 2 pieces		**23130-418**
Depth member St, 2 mm, for cabinet depth 600 mm, 2 pieces		**23130-081**
Depth member St, 2 mm, for cabinet depth 800 mm, 2 pieces		**23130-082**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

19" SWING FRAME





01005055 01005059

- Can accommodate 19" chassis and 19" subracks
- For full height or partial-height mounting
- Pivot point can be selected right or left
- Load-carrying capacity 150 kg

DELIVERY INCLUDES (kit)


Item	Qty	Description
1	1	Swing frame, St, 2 mm, RAL 7021
2	2	Support bar, St, 3 mm, RAL 7021
3	2	Square lock, 8 mm, incl. 2 keys
4	2	120° hinge
5	1	Assembly kit


ORDER INFORMATION

For cabinet height mm	Height h1 U	Height h2 U	Part no.
900 for partial-height mounting	16	12	21130-740
1200 for partial-height mounting	24	21	21130-741
1400 for partial-height mounting	29	25	21130-742
1600 for partial-height mounting	33	30	21130-743
1800	38	34	21130-744
2000	42	39	21130-745
2200	47	43	21130-746
Accessories			
Swing frame stop max. swing angle 120°, St, zinc-plated, 1 piece			23130-158
Security lock to replace the square lock, PU 1 lock incl. 2 keys			**60113-267**
Spare key for security lock, 1 piece			**60220-003**
Slide rails for swing frames PU 2 pieces			23130-183

Swing frame stop

Security lock





01005061 41001517

Slide rail

Sliding rails mounted on the swing frame







01018051 01018052

NOTE

- 19" swing frames can be assembled:
  - Directly on the cabinet frame
  - In 50 mm increments by aid of depth members (depth-adjustable)
- For partial-height mounting, depth members are necessary, see page 1.24

19" PANEL/SLIDE MOUNT WITH UNIVERSAL PITCH (EIA)





Standard assembly dimension $x_r = x_f = 50$ mm

- Assembly in 600 mm wide cabinets directly on the frame
- Depth-adjustable in 25 mm increments
- In accordance with IEC 60297-1 (DIN 41 494, part 1)

DELIVERY COMPRISES

Item	Qty	Description
1	2	19" panel/slide mount, St, 1.75 mm, finish AlZn, RAL 7035 or RAL 7021
2	1	Assembly kit, incl. GND/earthing


ORDER INFORMATION

For cabinet height	Usable height	Length	AlZn	RAL 7035	RAL 7021
mm	U	mm	Part no.	Part no.	Part no.
Partial-height mounting	8	395	**23130-037**	**23130-027**	**23130-017**
Partial-height mounting	12	545	**23130-038**	**23130-028**	**23130-018**
Partial-height mounting	16	745	**23130-039**	**23130-029**	23130-019
Partial-height mounting	20	895	**23130-040**	**23130-030**	**23130-020**
Partial-height mounting	24	1095	**23130-031**	**23130-021**	**23130-011**
Partial-height mounting	29	1295	**23130-032**	**23130-022**	**23130-012**
Partial-height mounting	33	1495	**23130-033**	**23130-023**	**23130-013**
1800	38	1695	**23130-034**	**23130-024**	**23130-014**
2000	42	1895	**23130-035**	**23130-025**	**23130-015**
Dimensioning strip for 19" panel mounts, paper, white, serial numbered from 1 ... 47 U, PU 4 pieces					**25127-997**

NOTE

- For 19" partial-height mounting depth members are necessary
- Metric panel/slide mounts available on request

19" ASSEMBLY KIT, M6



- For front panels, distribution fields and other components

DELIVERY COMPRISES


Item	Description
1	Panhead screw, M6 x 16, St, zinc-plated
2	Plastic washer, black
3	Cage nut, M6, St, zinc-plated

ORDER INFORMATION


Description	Qty/PU	Part no.
19" assembly kit (screw, washer, nut)	50	**21101-809**
19" assembly kit (screw, washer, nut)	100	**21101-810**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

SLIDE RAILS




01004056




01005086

Static load-carrying capacity 25 kg



01004058

Static load-carrying capacity 100 kg



01004130

c = pitch of the 19" panel/slide mounts
x_f = standard dimension
D = cabinet depth

- For assembly on 19" panel/slide mounts
- Assembly in 1 U increments (snap-in, bolt-on)
- Wide support surface (48 mm)
- 2 versions
  - Static load-carrying capacity 25 kg per pair
  - Static load-carrying capacity 100 kg per pair

DELIVERY COMPRISES

Item	Qty	Description
1	see Order information	Slide rail, AlZn, 1.5 mm (static load-carrying capacity 25 kg), or 2.5 mm (static load-carrying capacity 100 kg), zinc-plated
2	1	Assembly kit incl. GND/earthing

ORDER INFORMATION

Static load carrying capacity 25 kg


For cabinet depth D mm	x_f mm	c mm	Length L mm	Qty/PU	Part no.
600	50	500	456	2	**23130-096**
600	50	500	456	10	**23130-101**
800	50	700	656	2	**23130-097**
800	50	700	656	10	**23130-102**

ORDER INFORMATION


Static load carrying capacity 100 kg

For cabinet depth D mm	x_f mm	c mm	Length L mm	Qty/PU	Part no.
600	50	500	458	2	**23130-118**
600	50	500	458	10	**23130-123**
800	50	700	658	2	**23130-119**
800	50	700	658	10	**23130-124**

19" FIXED SHELF, 75 KG



01004066



01004067

c = max. pitch of the 19" slide mounts
x_f, x_r = standard assembly dimension

- Static load-carrying capacity 75 kg (150 kg with strengthening rail)
- Mounting height 1 U, for mounting on four panel/slide mounts
- With hammer head perforation to fix cable ties

DELIVERY COMPRISES

Item	Qty	Description
1	1	Perforated shelf, St, 1.5 mm (colour see Order Information)
2	1	Assembly kit incl. GND/earthing

ORDER INFORMATION


For cabinet depth mm	Usable surface w x d mm	x_f mm	c mm	RAL 7035 Part no.	RAL 7021 Part no.
600	495 x 442	50	500	**22130-303**	**21130-303**
800	495 x 642	50	700	**22130-305**	**21130-305**
Strengthening rail for stationary 19" shelf PU 1 piece					**23130-310**

NOTE

- Cable ducting with cable ties, see page 1.26
- Other sizes, see ServicePLUS, page 1.49

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

19" TELESCOPIC SHELF, 30 KG




01004068

- Static load-carrying capacity at full extension 30 kg
- Mounting height 1 U, for mounting on four 19" panel/slide mounts
- Incl. telescopic slides
- Hammer head perforation to fix cable ties
- 2 versions
  - Full depth
  - Depth shortened by 100 mm for rear cable ducting

DELIVERY COMPRISES

Item	Qty	Description
1	1	Perforated shelf, St, 1.5 mm (colour see Order Information)
2	2	Telescopic slide
3	1	Assembly kit

Full depth



01004069

ORDER INFORMATION


Full depth

For cabinet depth	Usable surface w x d	x_f	c	RAL 7035	RAL 7021
mm	mm	mm	mm	Part no.	Part no.
600	417 x 482	50	500	**22130-343**	**21130-343**
800	417 x 682	50	700	**22130-345**	**21130-345**
GND/earthing for telescopic 19" shelf PU 1 kit, for VARISTAR				**23130-140**	

NOTE

- Cable ducting with cable ties, see page 1.26

Shortened depth



01004070

ORDER INFORMATION

Shortened by 100 mm


For cabinet depth	Usable surface w x d	x_f	c	RAL 7035	RAL 7021
mm	mm	mm	mm	Part no.	Part no.
600	417 x 382	50	500	**22130-342**	**21130-342**
800	417 x 582	50	700	**22130-344**	**21130-344**
GND/earthing for telescopic 19" shelf PU 1 kit, for VARISTAR				**23130-140**	

NOTE

- Cable ducting with cable ties, see page 1.26

c = max. pitch of the 19" panel/slide mounts
x_f, x_r = standard assembly dimension


19" TELESCOPIC SHELF, 70 KG



01004071

- Static load-carrying capacity at full extension 70 kg
- Mounting height 2 U, for mounting on four 19" panel/slide mounts
- Incl. telescopic slides
- Locking with T-bar lock possible
- Hammer head perforation to fix cable ties
- 2 versions
  - Full depth
  - Depth shortened by 100 mm for rear cable ducting


Full depth



01004069

c = max. pitch for 19" panel/slidemounts

Shortened depth



01004070

c = max. pitch of the 19" slide mounts
x_f, x_r = standard assembly dimension

DELIVERY COMPRISES

Item	Qty	Description
1	1	Perforated shelf, St, 1.5 mm (colour see Order Information)
2	2	Telescopic slide
3	1	Assembly kit

ORDER INFORMATION

Full depth

For cabinet depth	Usable surface w x d	x_f	c	RAL 7035	RAL 7021
mm	mm	mm	mm	Part no.	Part no.
600	405 x 482	50	500	**22130-353**	**21130-353**
800	405 x 682	50	700	**22130-355**	**21130-355**
Item 4 T-bar lock for 1 telescopic shelf (can be mounted right or left), 1 piece					**23130-092**
GND/earthing for telescopic 19" shelf PU 1 kit, for VARISTAR					**23130-140**

NOTE

- Please order T-bar lock (item 4) separately
- Cable ducting with cable ties, see page 1.26

ORDER INFORMATION

Shortened by 100 mm


For cabinet depth	Usable surface w x d	x_f	c	RAL 7035	RAL 7021
mm	mm	mm	mm	Part no.	Part no.
600	405 x 382	50	500	22130-352	**21130-352**
800	405 x 582	50	700	22130-354	**21130-354**
Item 4 T-bar lock for 1 telescopic shelf (can be mounted right or left), 1 piece					**23130-092**
GND/earthing for telescopic 19" shelf PU 1 kit, for VARISTAR					**23130-140**

NOTE

- Please order T-bar lock (item 4) separately
- Cable ducting with cable ties, see page 1.26

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

DEPTH MEMBER



Cable eye

- For fitting shortened 19" panel/slide mounts and mounting plates
- Cable ducting by means of cable ties and cable eye

DELIVERY COMPRISES


Item	Qty	Description
1	2	Depth member, St, 1.5 mm, finish AlZn
2	1	Assembly kit incl. GND/earthing

ORDER INFORMATION

Description	For cabinet depth mm	Part no.
Depth member	600	**23130-081**
Depth member	800	**23130-082**
Cable eye A = 38 mm, B = 25 mm, PU 25 pieces		**21101-151**
Cable eye A = 47 mm, B = 50 mm, PU 25 pieces		**21101-150**


- Cable ducting with cable ties, see page 1.26

C-PROFILE FOR THE CABINET DEPTH



Cable retention rail and cable shell mounted on C-profile

Slide nut



C-profile Cable retention rail

- For cable ducting in lateral area of cabinet
- For cable shells and cable retention rails

DELIVERY COMPRISES

Item	Qty	Description
1	2	C-profile, St, 1.5 mm, AlZn
2	1	Assembly kit incl. GND/earthing


ORDER INFORMATION

For cabinet depth mm	Length L mm	Part no.
600	460	**23130-086**
800	660	**23130-087**
Accessories		
Cable retention rail for C-rail Width 75 mm, length 39.5 mm, PU 5 piece		**60118-472**
Cable shell for cable bundle 18 ... 22 mm, PU 10 pieces		**20118-775**
Cable shell for cable bundle 22 ... 26 mm, PU 10 pieces		**20118-776**
Cable shell for cable bundle 26 ... 30 mm, PU 10 pieces		**20118-777**
Cable shell for cable bundle 30 ... 34 mm, PU 10 pieces		**20114-728**
Cable shell for cable bundle 34 ... 38 mm, PU 10 pieces		**20114-729**
Cable shell for cable bundle 38 ... 42 mm, PU 10 pieces		**20114-730**
Cable shell for cable bundle 42 ... 46 mm, PU 10 pieces		**20114-731**
Cable shell for cable bundle 46 ... 50 mm, PU 10 pieces		20118-778
Slide nut for C-profile, PU 10 piece		**21120-140**

NOTE


- Cable ties and Velcro for cable retention rail see page 1.26

C-PROFILE FOR CABINET WIDTH



C-profile

Slide nut



Cable retention rail

- For cable ducting in rear or front area of cabinet
- For cable shells and cable retention rails

DELIVERY COMPRISES

Item	Qty	Description
1	2	C-profile, St, 1.5 mm, finish AlZn
2	1	Assembly kit incl. GND/earthing


ORDER INFORMATION

For cabinet width mm	Length mm	Part no.
600	550	**23130-333**
800	750	**23130-334**
Accessories		
Cable retention rail for C-rail Width 75 mm, length 39.5 mm, PU 5 pieces		**60118-472**
Cable shell for cable bundle 18 ... 22 mm, PU 10 pieces		**20118-775**
Cable shell for cable bundle 22 ... 26 mm, PU 10 pieces		**20118-776**
Cable shell for cable bundle 26 ... 30 mm, PU 10 pieces		**20118-777**
Cable shell for cable bundle 30 ... 34 mm, PU 10 pieces		**20114-728**
Cable shell for cable bundle 34 ... 38 mm, PU 10 pieces		**20114-729**
Cable shell for cable bundle 38 ... 42 mm, PU 10 pieces		**20114-730**
Cable shell for cable bundle 42 ... 46 mm, PU 10 pieces		**20114-731**
Cable shell for cable bundle 46 ... 50 mm, PU 10 pieces		20118-778
Slide nut for C-profile, PU 10 pieces		**21120-140**

NOTE

- Cable ties and Velcro for cable retention rail see page 1.26

CABLE TIES, VELCRO



Cable tie Velcro


- Fixing materials kit for cable ducting

ORDER INFORMATION

Description	Part no.
Cable tie, Plastic, 92 mm x 2.5 mm, PU 25 pieces	**20118-351**
Cable tie, Plastic, 186 mm x 5 mm, PU 25 pieces	**20118-352**
Cable tie, Plastic, 360 mm x 5 mm, PU 25 pieces	**20118-353**
Velcro strip, PE/PA, black, length 300 mm, PU 10 pieces	**20118-624**

VARISTAR IP 20 SERVICEPLUS: CONFIGURATION AND ASSEMBLY

- Dimensions:
  - Height: 29 ... 47 U (1400 ... 2200 mm)
  - Width: 600 and 800 mm
  - Depth: 300, 600 and 800 mm
- 2 colour combinations:
  - Frame and covers in black grey (RAL 7021)
  - Frame, top cover and base in black grey (RAL 7021); Side panel, door and rear panel in light grey (RAL 7035)
- Build your cabinet out of individual components (please suffix each part number with /05)
- Once you have selected the desired cabinet dimensions, the row number (first column of the configuration tables) will guide you through all subsequent configuration pages that apply to these dimensions (see example below)
- The cabinet is assembled by us and ready for despatch within 10 working days



01004077

Example configuration (here: row 10)

Qty	Description	Order no.
1	Frame Slim-Line, height 2000 mm, width 600 mm, depth 800 mm, 1 piece	20130-019/05
1	Side panel with quick-release fastener, RAL 7021, PU 2 pieces	21130-051/05
2	Safety lock for side panel, PU 4 pieces	23130-132/05
1	Rear panel, screw-fixed, RAL 7021, 1 piece	21130-069/05
1	Glazed door with single point locking, RAL 7021, IP 20, 1 piece	21130-129/05
1	Adjustable feet, PU 4 pieces	23130-079/05
..	.....	.....








Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

	Page
Frames, side-by-side mounting kits, adjustable feet, castors	1.28
Side panels, rear panels	1.29
Decorative frames, glazed doors	1.30
Steel doors	1.31
Double doors	1.32
Flat top covers, lifting eyes	1.33
Flat top cover assemblies with cut-out zones	1.34
Fan top covers	1.35
Bases/plinths	1.36
Connecting plates for short doors/rear panels	1.37
Interior configuration for IP 20 and IP 55	
19" panel/slide mounts	1.44
ETSI panel/slide mounts	1.45
Swing frames	1.46
Mounting plate, stationary shelves, 75 kg	1.47
Telescopic shelves, 70 kg	1.48
19" shelves 1 U, fixed 75 kg, telescopic 30 kg	1.49
19" telescopic shelf, 2 U, 70 kg	1.50
Slide rails, depth members	1.51
Cable ductings	1.52
Cable ties, Velcro	1.53

Cabinets – Varistar Electronics

VARISTAR IP 20 FRAMES, SIDE-BY-SIDE MOUNTING KITS, ADJUSTABLE FEET, CASTORS

ORDER INFORMATION

		Frame		Side-by-side mounting kit IP 20	Side-by-side mounting kit IP 55 (with gasketing)	Adjustable feet	Castors	
		Slim-Line 400 kg	Heavy-Duty 800 kg				With 2 jacking feet	With adjustable feet
	Completely in RAL 7021 (black grey)	 01004078		 01004117		 01004081	 01004082	 01004156
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	static load-carrying capacity: 400 kg, St, 1.5 mm, zinc-plated, with central GND/earthing point; please order adjustable feet or castors separately	static load-carrying capacity: 800 kg, St, 1.5 mm, zinc-plated, with central GND/earthing point; please order adjustable feet or castors separately	side-by-side mounting bracket (4 pieces), St; RAL 7021, not in combination with decorative frame	side-by-side mounting bracket (4 pieces), St, RAL 7021, incl. gasketing to cover the gap between two racks; not in combination with decorative frame	for the frame, static load-carrying capacity:1000 kg, cannot be used with base/plinth	for the frame, static load-carrying capacity: 400 kg, cannot be used with base/plinth	for the frame, static load-carrying capacity:400 kg, cannot be used with base/plinth









No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	PU 1 kit supplied loose	PU 1 kit supplied loose	PU 4 pieces assembled	PU 4 pieces	PU 4 pieces
Completely in RAL 7021					**RAL 7021**	**RAL 7021**	**RAL 7021**				
1	29	1400	600	600	20130-005	20130-055	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
2	29	1400	600	800	20130-006	20130-056					
3	33	1600	600	600	20130-009	20130-059	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
4	33	1600	600	800	20130-010	20130-060					
5	38	1800	600	600	20130-013	20130-063	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
6	38	1800	600	800	20130-014	20130-064					
7	38	1800	800	600	20130-015	20130-065	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
8	42	2000	600	300	20130-017	–	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
9	42	2000	600	600	20130-018	20130-068	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
10	42	2000	600	800	20130-019	20130-069					
11	42	2000	800	600	20130-022	20130-072	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
12	42	2000	800	800	20130-023	20130-073					
13	47	2200	600	300	20130-026	–	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
14	47	2200	600	600	20130-027	20130-077	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
15	47	2200	600	800	20130-028	20130-078					
16	47	2200	800	800	20130-032	20130-082	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
Colour combinations					**RAL 7021**	**RAL 7021**	**RAL 7021**				
17	29	1400	600	600	20130-005	20130-055	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
18	29	1400	600	800	20130-006	20130-056					
19	33	1600	600	600	20130-009	20130-059	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
20	33	1600	600	800	20130-010	20130-060					
21	38	1800	600	600	20130-013	20130-063	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
22	38	1800	600	800	20130-014	20130-064					
23	38	1800	800	600	20130-015	20130-065	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
24	42	2000	600	300	20130-017	–	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
25	42	2000	600	600	20130-018	20130-068	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
26	42	2000	600	800	20130-019	20130-069					
27	42	2000	800	600	20130-022	20130-072	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
28	42	2000	800	800	20130-023	20130-073					
29	47	2200	600	300	20130-026	–	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
30	47	2200	600	600	20130-027	20130-077	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
31	47	2200	600	800	20130-028	20130-078					
32	47	2200	800	800	20130-032	20130-082	**23130-061**	**23130-062**	**23130-079**	**23130-077**	**23130-078**

Other dimensions and configurations online (with basket) at www.schroff.biz/conf

Cabinets – Varistar Electronics

VARISTAR IP 20 SIDE PANELS, REAR PANELS










ORDER INFORMATION

					Side panel		Screw-fixed side panel	Rear panel		Screw-fixed rear panel
					With quick release fastener	Lock		With quick release fastener	Lock	
 Completely in RAL 7021 (black grey)					 01004084	 01004072	 01004083	 01004087	 01004072	 01004085
 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)					St, 1 mm, incl. GND/ earthing, please order lock separately	for quick-release fasteners of one side panel; 4 locks sufficient for 2 side panels	St, 1 mm, incl. GND/ earthing	St, 1 mm, incl. GND/ earthing, please order lock separately	for quick-release fasteners of rear panel	St, 1 mm, incl. GND/ earthing
	Cabinet dimensions									
	Height		Width	Depth						
No.	U	mm	mm	mm	PU 2 pieces assembled	PU 4 pieces assembled	PU 2 pieces assembled	1 piece assembled	PU 2 pieces assembled	1 piece assembled
Completely in RAL 7021					**RAL 7021**		**RAL 7021**	**RAL 7021**		**RAL 7021**
1	29	1400	600	600	21130-043	23130-132	21130-003	21130-093	23130-133	21130-063
2	29	1400	600	800	21130-044		21130-004			
3	33	1600	600	600	21130-045	23130-132	21130-005	21130-095	23130-133	21130-065
4	33	1600	600	800	21130-046		21130-006			
5	38	1800	600	600	21130-047	23130-132	21130-007	21130-097	23130-133	21130-067
6	38	1800	600	800	21130-048		21130-008			
7	38	1800	800	600	21130-047	23130-132	21130-007	21130-098	23130-133	21130-068
8	42	2000	600	300	21130-049	23130-132	21130-009	21130-099	23130-133	21130-069
9	42	2000	600	600	21130-050	23130-132	21130-010	21130-099	23130-133	21130-069
10	42	2000	600	800	21130-051		21130-011			
11	42	2000	800	600	21130-050	23130-132	21130-010	21130-100	23130-133	21130-070
12	42	2000	800	800	21130-051		21130-011			
13	47	2200	600	300	21130-054	23130-132	21130-014	21130-101	23130-133	21130-071
14	47	2200	600	600	21130-055	23130-132	21130-015	21130-101	23130-133	21130-071
15	47	2200	600	800	21130-056		21130-016			
16	47	2200	800	800	21130-056	23130-132	21130-016	21130-102	23130-133	21130-072
Colour combinations					**RAL 7035**		**RAL 7035**	**RAL 7035**		**RAL 7035**
17	29	1400	600	600	22130-043	23130-132	22130-003	22130-093	23130-133	22130-063
18	29	1400	600	800	22130-044		22130-004			
19	33	1600	600	600	22130-045	23130-132	22130-005	22130-095	23130-133	22130-065
20	33	1600	600	800	22130-046		22130-006			
21	38	1800	600	600	22130-047	23130-132	22130-007	22130-097	23130-133	22130-067
22	38	1800	600	800	22130-048		22130-008			
23	38	1800	800	600	22130-047	23130-132	22130-007	22130-098	23130-133	22130-068
24	42	2000	600	300	22130-049	23130-132	22130-009	22130-099	23130-133	22130-069
25	42	2000	600	600	22130-050	23130-132	22130-010	22130-099	23130-133	22130-069
26	42	2000	600	800	22130-051		22130-011			
27	42	2000	800	600	22130-050	23130-132	22130-010	22130-100	23130-133	22130-070
28	42	2000	800	800	22130-051		22130-011			
29	47	2200	600	300	22130-054	23130-132	22130-014	22130-101	23130-133	22130-071
30	47	2200	600	600	22130-055	23130-132	22130-015	22130-101	23130-133	22130-071
31	47	2200	600	800	22130-056		22130-016			
32	47	2200	800	800	22130-056	23130-132	22130-016	22130-102	23130-133	22130-072

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

VARISTAR IP 20 DECORATIVE FRAMES, GLAZED DOORS










ORDER INFORMATION

					Deco frame		Glazed door		Glazed door	DIN profile half cylinder	DIN profile half cylinder
					Deco frame	Adapter bracket	Single point locking	Lever handle	3-point locking		
	 Completely in RAL 7021 (black grey)				 01004086	 01004160	 01004088	 01004147	 01004091	 01004148	 01004148
	 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)				Al, 19" plane integrated, front open, incl. GND/earthing, no door can be fitted	St, 2 mm, for deco frame, for assembly of slide rails and shelves	St, 1.5 mm, Sekurit glass 6 mm, opening angle 180°, lock cover, incl. GND/earthing	with push button for doors with single point locking	St, 1.5 mm, Sekurit glass, 6 mm, opening angle 180°, lever handle with push button, incl. GND/earthing	for lever handle, common locking, key type 333	for lever handle, common locking, key type 2233
	Cabinet dimensions										
No.	Height U	mm	Width mm	Depth mm	1 piece assembled	PU 1 pair assembled	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled
	Completely in RAL 7021				**RAL 7021**	**RAL 7021**	**RAL 7021**		**RAL 7021**		
1	29	1400	600	600	21130-232	23130-221	21130-123	**23130-067**	21130-183	**25127-995**	**60130-402**
2	29	1400	600	800							
3	33	1600	600	600	21130-233	23130-222	21130-125	**23130-067**	21130-185	**25127-995**	**60130-402**
4	33	1600	600	800							
5	38	1800	600	600	21130-234	23130-223	21130-127	**23130-067**	21130-187	**25127-995**	**60130-402**
6	38	1800	600	800							
7	38	1800	800	600	–	–	21130-128	**23130-067**	21130-188	**25127-995**	**60130-402**
8	42	2000	600	300	21130-235	**23130-224**	21130-129	**23130-067**	21130-189	**25127-995**	**60130-402**
9	42	2000	600	600	21130-235	**23130-224**	21130-129	**23130-067**	21130-189	**25127-995**	**60130-402**
10	42	2000	600	800							
11	42	2000	800	600	–	–	21130-130	**23130-067**	21130-190	**25127-995**	**60130-402**
12	42	2000	800	800							
13	47	2200	600	300	21130-236	23130-225	21130-131	**23130-067**	21130-191	**25127-995**	**60130-402**
14	47	2200	600	600	21130-236	23130-225	21130-131	**23130-067**	21130-191	**25127-995**	**60130-402**
15	47	2200	600	800							
16	47	2200	800	800	–	–	21130-132	**23130-067**	21130-192	**25127-995**	**60130-402**
	Colour combinations				**RAL 7035**	**RAL 7035**	**RAL 7035**		**RAL 7035**		
17	29	1400	600	600	22130-232	23130-231	22130-123	**23130-067**	22130-183	**25127-995**	**60130-402**
18	29	1400	600	800							
19	33	1600	600	600	22130-233	23130-232	22130-125	**23130-067**	22130-185	**25127-995**	**60130-402**
20	33	1600	600	800							
21	38	1800	600	600	22130-234	23130-233	22130-127	**23130-067**	22130-187	**25127-995**	**60130-402**
22	38	1800	600	800							
23	38	1800	800	600	–	–	22130-128	**23130-067**	22130-188	**25127-995**	**60130-402**
24	42	2000	600	300	22130-235	23130-234	22130-129	**23130-067**	22130-189	**25127-995**	**60130-402**
25	42	2000	600	600	22130-235	23130-234	22130-129	**23130-067**	22130-189	**25127-995**	**60130-402**
26	42	2000	600	800							
27	42	2000	800	600	–	–	22130-130	**23130-067**	22130-190	**25127-995**	**60130-402**
28	42	2000	800	800							
29	47	2200	600	300	22130-236	23130-235	22130-131	**23130-067**	22130-191	**25127-995**	**60130-402**
30	47	2200	600	600	22130-236	23130-235	22130-131	**23130-067**	22130-191	**25127-995**	**60130-402**
31	47	2200	600	800							
32	47	2200	800	800	–	–	22130-132	**23130-067**	22130-192	**25127-995**	**60130-402**

Cabinets – Varistar Electronics

VARISTAR IP 20 STEEL DOORS







ORDER INFORMATION

					Steel door, single point locking				Steel door 3-point locking	DIN profile half cylinder	DIN profile half cylinder
					Plain	Solid, inner surface with mounting frame	Perforated	Lever handle			
 Completely in RAL 7021 (black grey)					 01004089	 01008067	 01004090	 01004147	 01008085	 01004148	 01004148
 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)					St, 1 mm, opening angle 180°, key, incl. GND/ earthing	St, 1.5 mm, opening angle 180°, lock cover incl. GND/ earthing, designed to carry extensive cut-outs and assemblies	St, 1.5 mm, opening angle 180°, key, incl. GND/ earthing	with push button for doors with single point locking	St, 1.5 mm, opening angle 180°, inner side with mounting frame, lever handle with built-in push button, incl. GND/earthing	for lever handle, common locking, key type 333	for lever handle, common locking, key type 2233
	Cabinet dimensions										
	Height		Width	Depth	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece	1 piece
No.	U	mm	mm	mm	assembled	assembled	assembled	assembled	assembled	assembled	assembled
	Completely in RAL 7021				**RAL 7021**	**RAL 7021**	**RAL 7021**		**RAL 7021**		
1	29	1400	600	600	21130-108	21130-568	21130-138	**23130-067**	21130-153	**25127-995**	**60130-402**
2	29	1400	600	800							
3	33	1600	600	600	21130-110	21130-570	21130-140	**23130-067**	21130-155	**25127-995**	**60130-402**
4	33	1600	600	800							
5	38	1800	600	600	21130-112	21130-572	21130-142	**23130-067**	21130-157	**25127-995**	**60130-402**
6	38	1800	600	800							
7	38	1800	800	600	21130-113	21130-573	21130-143	**23130-067**	21130-158	**25127-995**	**60130-402**
8	42	2000	600	300	21130-114	21130-574	21130-144	**23130-067**	21130-159	**25127-995**	**60130-402**
9	42	2000	600	600	21130-114	21130-574	21130-144	**23130-067**	21130-159	**25127-995**	**60130-402**
10	42	2000	600	800							
11	42	2000	800	600	21130-115	21130-575	21130-145	**23130-067**	21130-160	**25127-995**	**60130-402**
12	42	2000	800	800							
13	47	2200	600	300	21130-116	21130-576	21130-146	**23130-067**	21130-161	**25127-995**	**60130-402**
14	47	2200	600	600	21130-116	21130-576	21130-146	**23130-067**	21130-161	**25127-995**	**60130-402**
15	47	2200	600	800							
16	47	2200	800	800	21130-117	21130-577	21130-147	**23130-067**	21130-162	**25127-995**	**60130-402**
	Colour combinations				**RAL 7035**	**RAL 7035**	**RAL 7035**		**RAL 7035**		
17	29	1400	600	600	22130-108	22130-568	22130-138	**23130-067**	22130-153	**25127-995**	**60130-402**
18	29	1400	600	800							
19	33	1600	600	600	22130-110	22130-570	22130-140	**23130-067**	22130-155	**25127-995**	**60130-402**
20	33	1600	600	800							
21	38	1800	600	600	22130-112	22130-572	22130-142	**23130-067**	22130-157	**25127-995**	**60130-402**
22	38	1800	600	800							
23	38	1800	800	600	22130-113	22130-573	22130-143	**23130-067**	22130-158	**25127-995**	**60130-402**
24	42	2000	600	300	22130-114	22130-574	22130-144	**23130-067**	22130-159	**25127-995**	**60130-402**
25	42	2000	600	600	22130-114	22130-574	22130-144	**23130-067**	22130-159	**25127-995**	**60130-402**
26	42	2000	600	800							
27	42	2000	800	600	22130-115	22130-575	22130-145	**23130-067**	22130-160	**25127-995**	**60130-402**
28	42	2000	800	800							
29	47	2200	600	300	22130-116	22130-576	22130-146	**23130-067**	22130-161	**25127-995**	**60130-402**
30	47	2200	600	600	22130-116	22130-576	22130-146	**23130-067**	22130-161	**25127-995**	**60130-402**
31	47	2200	600	800							
32	47	2200	800	800	22130-117	22130-577	22130-147	**23130-067**	22130-162	**25127-995**	**60130-402**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days








VARISTAR IP 20 DOUBLE DOORS

ORDER INFORMATION

		Double door, 3-point locking			DIN profile half cylinder
		Glazed	Perforated	Plain	
	Completely in RAL 7021 (black grey)	 01005065	 01005066	 01005064	 01004148
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	frame, St, 1.5 mm, Securit glass, 6 mm, opening angle 180°, lever handle with push button, incl. GND/earthing	St, 1.5 mm, opening angle 180°, lever handle with push button, incl. GND/earthing	St, 1.5 mm, opening angle 180°, lever handle with push button, incl. GND/earthing	for lever handle, common locking
	Cabinet dimensions				
No.	Height U mm / Width mm / Depth mm	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled
Completely in RAL 7021		**RAL 7021**	**RAL 7021**	**RAL 7021**	
1	29 / 1400 / 600 / 600	**21130-454**	**21130-213**	**21130-486**	**25127-995**
2	29 / 1400 / 600 / 800				
3	33 / 1600 / 600 / 600	**21130-456**	**21130-215**	**21130-488**	**25127-995**
4	33 / 1600 / 600 / 800				
5	38 / 1800 / 600 / 600	**21130-458**	**21130-217**	**21130-490**	**25127-995**
6	38 / 1800 / 600 / 800				
7	38 / 1800 / 800 / 600	**21130-459**	**21130-218**	**21130-491**	**25127-995**
8	42 / 2000 / 600 / 300	**21130-460**	**21130-219**	**21130-492**	**25127-995**
9	42 / 2000 / 600 / 600	**21130-460**	**21130-219**	**21130-492**	**25127-995**
10	42 / 2000 / 600 / 800				
11	42 / 2000 / 800 / 600	**21130-461**	**21130-220**	**21130-493**	**25127-995**
12	42 / 2000 / 800 / 800				
13	47 / 2200 / 600 / 300	**21130-462**	**21130-221**	21130-494	**25127-995**
14	47 / 2200 / 600 / 600	**21130-462**	**21130-221**	21130-494	**25127-995**
15	47 / 2200 / 600 / 800				
16	47 / 2200 / 800 / 800	**21130-463**	**21130-222**	**21130-495**	**25127-995**
Colour combinations		**RAL 7035**	**RAL 7035**	**RAL 7035**	
17	29 / 1400 / 600 / 600	22130-454	**22130-213**	**22130-486**	**25127-995**
18	29 / 1400 / 600 / 800				
19	33 / 1600 / 600 / 600	22130-456	**22130-215**	**22130-488**	**25127-995**
20	33 / 1600 / 600 / 800				
21	38 / 1800 / 600 / 600	22130-458	**22130-217**	**22130-490**	**25127-995**
22	38 / 1800 / 600 / 800				
23	38 / 1800 / 800 / 600	**22130-459**	**22130-218**	**22130-491**	**25127-995**
24	42 / 2000 / 600 / 300	**22130-460**	**22130-219**	**22130-492**	**25127-995**
25	42 / 2000 / 600 / 600	**22130-460**	**22130-219**	**22130-492**	**25127-995**
26	42 / 2000 / 600 / 800				
27	42 / 2000 / 800 / 600	**22130-461**	**22130-220**	**22130-493**	**25127-995**
28	42 / 2000 / 800 / 800				
29	47 / 2200 / 600 / 300	**22130-462**	**22130-221**	**22130-494**	**25127-995**
30	47 / 2200 / 600 / 600	**22130-462**	**22130-221**	**22130-494**	**25127-995**
31	47 / 2200 / 600 / 800				
32	47 / 2200 / 800 / 800	**22130-463**	**22130-222**	**22130-495**	**25127-995**

VARISTAR IP 20 FLAT TOP COVERS, LIFTING EYES

ORDER INFORMATION










		Flat top cover			Spacer	
		Plain flush top cover	Perforated	Lifting eye	Spacer	Lifting eye
 Completely in RAL 7021 (black grey)		 01004096	 01004097	 M12 01004100	 10 01004099	 M12 01004100
 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)		St, 1.5 mm, incl. GND/earthing	St, 1.5 mm, fully perforated, incl. GND/earthing	for top cover, applications and load in accordance with DIN 582	St, zinc-plated, for raising a top cover by 10 mm	for raised flat top cover, application and static load-carrying capacity in accordance with DIN 582

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	PU 4 pieces assembled	PU 4 pieces assembled	PU 4 pieces assembled
Completely in RAL 7021					**RAL 7021**	**RAL 7021**			
1	29	1400	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
2	29	1400	600	800	21130-243	21130-263			
3	33	1600	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
4	33	1600	600	800	21130-243	21130-263			
5	38	1800	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
6	38	1800	600	800	21130-243	21130-263			
7	38	1800	800	600	21130-246	21130-266	**23130-072**	**23130-068**	**23130-085**
8	42	2000	600	300	21130-241	21130-261	**23130-072**	**23130-068**	**23130-085**
9	42	2000	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
10	42	2000	600	800	21130-243	21130-263			
11	42	2000	800	600	21130-246	21130-266	**23130-072**	**23130-068**	**23130-085**
12	42	2000	800	800	21130-247	21130-267			
13	47	2200	600	300	21130-241	21130-261	**23130-072**	**23130-068**	**23130-085**
14	47	2200	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
15	47	2200	600	800	21130-243	21130-263			
16	47	2200	800	800	21130-247	21130-267	**23130-072**	**23130-068**	**23130-085**
Colour combinations					**RAL 7021**	**RAL 7021**			
17	29	1400	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
18	29	1400	600	800	21130-243	21130-263			
19	33	1600	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
20	33	1600	600	800	21130-243	21130-263			
21	38	1800	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
22	38	1800	600	800	21130-243	21130-263			
23	38	1800	800	600	21130-246	21130-266	**23130-072**	**23130-068**	**23130-085**
24	42	2000	600	300	21130-241	21130-261	**23130-072**	**23130-068**	**23130-085**
25	42	2000	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
26	42	2000	600	800	21130-243	21130-263			
27	42	2000	800	600	21130-246	21130-266	**23130-072**	**23130-068**	**23130-085**
28	42	2000	800	800	21130-247	21130-267			
29	47	2200	600	300	21130-241	21130-261	**23130-072**	**23130-068**	**23130-085**
30	47	2200	600	600	21130-242	21130-262	**23130-072**	**23130-068**	**23130-085**
31	47	2200	600	800	21130-243	21130-263			
32	47	2200	800	800	21130-247	21130-267	**23130-072**	**23130-068**	**23130-085**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

VARISTAR IP 20 FLAT TOP COVER ASSEMBLIES WITH CUT-OUT ZONES








ORDER INFORMATION

					Flat top cover with cut-out zones	Top cover assemblies					
						Brush strip	Fan insert	Thermostat	Top cover plate, perforated	Edge protection	Lifting eye
	Completely in RAL 7021 (black grey)				 01004098	 01006092	 01004102	 01108052	 01009056	 41003065	 01004100
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)				St, 1.5 mm, incl. GND/earthing, number of cut-outs and dimension drawings see page 1.9	nylon, black, one brush strip covers a lateral cut-out, two brush strips cover a center cut-out	230 V_{AC}, with three fans, 410 m^3/h, completely wired, connecting cable IEC 320	with mains cable 230 V_{AC} (SCHUKO/ UTE plug/ IEC 60320 C13 socket), adjustment range 0 ... 60°C	St, 1.5 mm, 6 mm hole diameter, incl. GND/earthing	PVC, 3 m, black, for open cut-out zones	for top cover, applications and load in accordance with DIN 582
	Cabinet dimensions										
	Height		Width	Depth	1 piece	PU 2 pieces	1 piece	1 piece	1 piece	1 piece	PU 4 pieces
No.	U	mm	mm	mm	assembled	assembled	assembled	assembled	assembled	enclosed loose	assembled
Completely in RAL 7021					**RAL 7021**	**RAL 7021**			**RAL 7021**		
1	29	1400	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
2	29	1400	600	800	21130-253						
3	33	1600	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
4	33	1600	600	800	21130-253						
5	38	1800	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
6	38	1800	600	800	21130-253						
7	38	1800	800	600	21130-256	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
8	42	2000	600	300	–	–	–	–	–	–	–
9	42	2000	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
10	42	2000	600	800	21130-253						
11	42	2000	800	600	21130-256	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
12	42	2000	800	800	21130-257						
13	47	2200	600	300	–	–	–	–	–	–	–
14	47	2200	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
15	47	2200	600	800	21130-253						
16	47	2200	800	800	21130-257	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
Colour combinations					**RAL 7021**	**RAL 7021**			**RAL 7021**		
17	29	1400	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
18	29	1400	600	800	21130-253						
19	33	1600	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
20	33	1600	600	800	21130-253						
21	38	1800	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
22	38	1800	600	800	21130-253						
23	38	1800	800	600	21130-256	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
24	42	2000	600	300	–	–	–	–	–	–	–
25	42	2000	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
26	42	2000	600	800	21130-253						
27	42	2000	800	600	21130-256	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
28	42	2000	800	800	21130-257						
29	47	2200	600	300	–	–	–	–	–	–	–
30	47	2200	600	600	21130-252	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**
31	47	2200	600	800	21130-253						
32	47	2200	800	800	21130-257	**23130-069**	**23130-070**	**20118-750**	**23130-071**	**28127-281**	**23130-072**

Cabinets – Varistar Electronics

VARISTAR IP 20 FAN TOP COVERS

ORDER INFORMATION

		Fan top cover				
		Top cover for 6 fans	Replacement fan for fan top	Thermostat	Speed control	Lifting eye
	Completely in RAL 7021 (black grey)	 01005060	 kta44844	 01108052	 01105055	 01005085
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	St, 1.5 mm, raised cover, 3 axial fans, 230 V_{AC}, incl. cabling andGN D/earthing, connecting cable2.5 m, SCHUKO/ IEC60320 C12 plug	fan with grille for top assembly, 230 V_{AC}, 38x119x119 mm, for 50 Hz, 162 m^3/h	with mains cable 230 V_{AC} (SCHUKO/ UTE plug/ IEC 60320 C13 socket), adjustment range 0 ... 60°C	fully wired, 90 ... 264 V_{AC}, input SCHUKO/UTE plug, outlet IEC 60320 C13 socket; external NTC sensor 1.5 m	for fan top cover, applications and static load-carrying capacity in accordance with DIN 582










No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	PU 4 pieces assembled
Completely in RAL 7021					**RAL 7021**				
1	29	1400	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
2	29	1400	600	800	21130-401				
3	33	1600	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
4	33	1600	600	800	21130-401				
5	38	1800	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
6	38	1800	600	800	21130-401				
7	38	1800	800	600	21130-402	**23130-165**	**20118-750**	**60715-005**	23130-090
8	42	2000	600	300	–	–	–	–	–
9	42	2000	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
10	42	2000	600	800	21130-401				
11	42	2000	800	600	21130-402	**23130-165**	**20118-750**	**60715-005**	23130-090
12	42	2000	800	800	21130-403				
13	47	2200	600	300	–	–	–	–	–
14	47	2200	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
15	47	2200	600	800	21130-401				
16	47	2200	800	800	21130-403	**23130-165**	**20118-750**	**60715-005**	23130-090
Colour combinations					**RAL 7021**				
17	29	1400	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
18	29	1400	600	800	21130-401				
19	33	1600	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
20	33	1600	600	800	21130-401				
21	38	1800	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
22	38	1800	600	800	21130-401				
23	38	1800	800	600	21130-402	**23130-165**	**20118-750**	**60715-005**	23130-090
24	42	2000	600	300	–	–	–	–	–
25	42	2000	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
26	42	2000	600	800	21130-401				
27	42	2000	800	600	21130-402	**23130-165**	**20118-750**	**60715-005**	23130-090
28	42	2000	800	800	21130-403				
29	47	2200	600	300	–	–	–	–	–
30	47	2200	600	600	21130-400	**23130-165**	**20118-750**	**60715-005**	23130-090
31	47	2200	600	800	21130-401				
32	47	2200	800	800	21130-403	**23130-165**	**20118-750**	**60715-005**	23130-090

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

Cabinets – Varistar Electronics






VARISTAR IP 20 BASES/PLINTHS

ORDER INFORMATION

		Base plate				Base/plinth		Base/plinth, mobile
		Base plate, multi-piece	Brush strip	Dust filter set	Cover plate	Base/plinth, ventilated	Side covers	
	Completely in RAL 7021 (black grey)	 01004104	 01004105	 01004059	 01004106	 01004110	 01004053	 01004111
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	St, 1.5 mm, multi-piece, opening to rear 200 mm deep (no rear opening with 300 mm cabinet depth), incl. GND/earthing; dimension drawings see page 1.9	nylon, black	filter mat, white, class M1, in accordance with EN 799-G3	St, 1.5 mm, please order gasket IP55 separately	support with adjustable feet and 2 trims, perforated, static load-carrying capacity 1000 kg; please order side trims separately	St, 1.5 mm	support, St, 3 mm, trim, St, 1.5 mm, static load-carrying capacity on castors 400 kg, on adjustable feet 1000 kg
	Cabinet dimensions							
	Height	Width	Depth	1 piece	1 piece	1 piece	1 piece	PU 1 kit	PU 1 pair	1 piece
No.	U mm	mm	mm	assembled	assembled	assembled	assembled	assembled	assembled	assembled
Completely in RAL 7021				**RAL 7021**	**RAL 7021**		**RAL 7021**	**RAL 7021**	**RAL 7021**	**RAL 7021**
1	29 1400	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
2	29 1400	600	800	**23130-002**					**23130-170**	**23130-209**
3	33 1600	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
4	33 1600	600	800	**23130-002**					**23130-170**	**23130-209**
5	38 1800	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
6	38 1800	600	800	**23130-002**					**23130-170**	**23130-209**
7	38 1800	800	600	23130-005	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-169**	23130-212
8	42 2000	600	300	23130-009	**23130-074**	**23130-075**	–	**23130-187**	23130-166	–
9	42 2000	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
10	42 2000	600	800	**23130-002**					**23130-170**	**23130-209**
11	42 2000	800	600	23130-005	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-169**	23130-212
12	42 2000	800	800	23130-006					**23130-170**	23130-213
13	47 2200	600	300	23130-009	**23130-074**	**23130-075**	–	**23130-187**	23130-166	–
14	47 2200	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
15	47 2200	600	800	**23130-002**					**23130-170**	**23130-209**
16	47 2200	800	800	23130-006	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-170**	23130-213
Colour combinations				**RAL 7021**	**RAL 7021**		**RAL 7021**	**RAL 7021**	**RAL 7021**	**RAL 7021**
17	29 1400	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
18	29 1400	600	800	**23130-002**					**23130-170**	**23130-209**
19	33 1600	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
20	33 1600	600	800	**23130-002**					**23130-170**	**23130-209**
21	38 1800	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
22	38 1800	600	800	**23130-002**					**23130-170**	**23130-209**
23	38 1800	800	600	23130-005	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-169**	23130-212
24	42 2000	600	300	23130-009	**23130-074**	**23130-075**	–	**23130-187**	23130-166	–
25	42 2000	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
26	42 2000	600	800	**23130-002**					**23130-170**	**23130-209**
27	42 2000	800	600	23130-005	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-169**	23130-212
28	42 2000	800	800	23130-006					**23130-170**	23130-213
29	47 2200	600	300	23130-009	**23130-074**	**23130-075**	–	**23130-187**	23130-166	–
30	47 2200	600	600	**23130-001**	**23130-074**	**23130-075**	**23130-076**	**23130-187**	**23130-169**	23130-208
31	47 2200	600	800	**23130-002**					**23130-170**	**23130-209**
32	47 2200	800	800	23130-006	**23130-134**	**23130-135**	**23130-136**	**23130-194**	**23130-170**	23130-213

VARISTAR IP 20 CONNECTING PLATES FOR SHORT DOORS/REAR PANELS

ORDER INFORMATION


	Dimensioning connecting plate door/rear panel	Connecting plate for door and rear panel			Other VARISTAR interior mounting parts
		Plain	With brush strip	Assembly kit	
 Completely in RAL 7021 (black grey)	 01005071	 01005063	 01005069		  01004066 01004056
 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	door and rear panel must be selected 400 mm shorter than the cabinet height; cannot be used with double door	St, 1 mm, assembly also possible at top, height 400 mm, please order assembly kit separately in conjunction with rear panel	St, 1 mm, assembly also possible at top, height 400 mm, please order assembly kit separately in conjunction with rear panel	only required if rear panel with quick-release fastener is assembled above the connecting plate	rack shelves, 19" shelves, slide rails, cable ducting
Height mm / Width mm		1 piece assembled	1 piece assembled	PU 1 kit assembled	
Completely in RAL 7021		**RAL 7021**	**RAL 7021**		
400 600		21130-472	21130-478	23130-164	from page 1.44
400 800		21130-473	21130-479	23130-164	
Colour combinations		**RAL 7035**	**RAL 7035**		
400 600		22130-472	22130-478	23130-164	from page 1.44
400 800		22130-473	22130-479	23130-164	

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

Cabinets – Varistar Electronics

VARISTAR IP 55 SERVICEPLUS: CONFIGURATION AND ASSEMBLY

- Dimensions:
  - Height: 29 ... 47 U (1400 ... 2200 mm)
  - Width: 600 and 800 mm
  - Depth: 300, 600 and 800 mm
- 2 colour combinations:
  - Frame and covers in black grey (RAL 7021)
  - Frame, top cover and base in black grey (RAL 7021); Side panel, door and rear panel in light grey (RAL 7035)
- Build your cabinet out of individual components (please suffix each part number with /05)
- Once you have selected the desired cabinet dimensions, the row number (first column of the configuration tables) will guide you through all subsequent configuration pages that apply to these dimensions (see example below)
- The cabinet is assembled by us and ready for despatch within 10 working days



01004077

Example configuration (here: row 10)









Qty	Description	Part no.
1	Frame Slim-Line, height 2000 mm, width 600 mm, depth 800 mm, 1 piece	20130-019/05
1	IP 55 gasketing kit, 1 piece	23130-064/05
1	Side panel, screw-fixed, RAL 7021, PU 2 pieces	21130-011/05
1	Rear panel, screw-fixed, RAL 7021, 1 piece	21130-069/05
1	Glazed door with 3-point locking, RAL 7021, IP 55, 1 piece	21130-189/05
1	Adjustable feet, PU 4 pieces	23130-079/05
..	.....	.....

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

	Page
Frames, side-by-side mounting kits, adjustable feet, castors	1.40
Side panels, rear panels, doors, top covers	1.41
Flat top covers, lifting eyes	1.42
Connecting plates for short doors/rear panels	1.43
Interior configuration for IP 20 and IP 55	
19" panel/slide mounts	1.44
ETSI panel/slide mounts	1.45
Swing frames	1.46
Mounting plates, stationary shelves, 75 kg	1.47
Telescopic shelves, 70 kg	1.48
19" shelves 1 U, fixed 75 kg, telescopic 30 kg	1.49
19" telescopic shelves, 2 U, 70 kg	1.50
Slide rails, depth members	1.51
Cable ductings	1.52
Cable ties, Velcro	1.53

VARISTAR IP 55 FRAMES, SIDE-BY-SIDE MOUNTING KITS, ADJUSTABLE FEET, CASTORS

ORDER INFORMATION

		Frame		Gasket kit IP 55	Side-by-side mounting kit IP 55 (with gasketing)	Adjustable feet	Castors	
		Slim-Line 400 kg	Heavy-Duty 800 kg				with 2 jacking feet	with adjustable feet
	Completely in RAL 7021 (black grey)	 01004078		 01004157	 01004120	 01004081	 01004082	 01004158
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	static load-carrying capacity: 400 kg, St, 1.5 mm, zinc-plated, with central GND/ earthing point; please order adjustable feet or castors separately	static load-carrying capacity: 800 kg, St, 1.5 mm, zinc-plated, with central GND/ earthing point; please order adjustable feet or castors separately	seals are glued to the frame, so that all cladding parts conform to protection type IP 55	side-to-side mounting bracket (4 pieces), St, RAL 7021, incl. gasketing to cover the gap between two racks; cannot be used with decorative frame	for the frame, static load-carrying capacity:1000 kg, cannot be used with base/ plinth	for the frame, static load-carrying capacity:400 kg,cannot be used with base/plinth	for the frame, static load-carrying capacity:400 kg,cannot be used with base/plinth









No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	PU 1 kit assembled	PU 1 kit supplied loose	PU 4 pieces assembled	PU 4 pieces	PU 4 pieces
Completely in RAL 7021					**RAL 7021**	**RAL 7021**					
1	29	1400	600	600	20130-005	20130-055	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
2	29	1400	600	800	20130-006	20130-056					
3	33	1600	600	600	20130-009	20130-059	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
4	33	1600	600	800	20130-010	20130-060					
5	38	1800	600	600	20130-013	20130-063	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
6	38	1800	600	800	20130-014	20130-064					
7	38	1800	800	600	20130-015	20130-065	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
8	42	2000	600	300	20130-017	–	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
9	42	2000	600	600	20130-018	20130-068	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
10	42	2000	600	800	20130-019	20130-069					
11	42	2000	800	600	20130-022	20130-072	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
12	42	2000	800	800	20130-023	20130-073					
13	47	2200	600	300	20130-026	–	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
14	47	2200	600	600	20130-027	20130-077	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
15	47	2200	600	800	20130-028	20130-078					
16	47	2200	800	800	20130-032	20130-082	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
Colour combinations					**RAL 7021**	**RAL 7021**					
17	29	1400	600	600	20130-005	20130-055	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
18	29	1400	600	800	20130-006	20130-056					
19	33	1600	600	600	20130-009	20130-059	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
20	33	1600	600	800	20130-010	20130-060					
21	38	1800	600	600	20130-013	20130-063	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
22	38	1800	600	800	20130-014	20130-064					
23	38	1800	800	600	20130-015	20130-065	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
24	42	2000	600	300	20130-017	–	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
25	42	2000	600	600	20130-018	20130-068	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
26	42	2000	600	800	20130-019	20130-069					
27	42	2000	800	600	20130-022	20130-072	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
28	42	2000	800	800	20130-023	20130-073					
29	47	2200	600	300	20130-026	–	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
30	47	2200	600	600	20130-027	20130-077	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**
31	47	2200	600	800	20130-028	20130-078					
32	47	2200	800	800	20130-032	20130-082	**23130-064**	**23130-062**	**23130-079**	**23130-077**	**23130-078**

Other dimensions and configurations online (with basket) at www.schroff.biz/conf

Cabinets – Varistar Electronics

VARISTAR IP 55 SIDE PANELS, REAR PANELS, DOORS, TOP COVERS

ORDER INFORMATION










					Screw-fixed side panel	Screw-fixed rear panel	Glazed door 3-point locking	Steel door 3-point locking	DIN profile half cylinder	Plain flush top cover	
										Flat top cover	Lifting eye
	Completely in RAL 7021 (black grey)				 01004083	 01004085	 01004091	 01008085	 01004148	 01004096	 01004100
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)				St, 1 mm, incl. GND/ earthing	St, 1 mm, incl. GND/ earthing	St, 1.5 mm, Sekurit glass, 6 mm, opening angle 180°, lever handle with push button, incl. GND/earthing	St, 1.5 mm, opening angle 180°, inner side with mounting frame, lever handle with built-in push button, incl. GND/earthing	for lever handle, common locking	St, 1.5 mm, incl. GND/earthing	for top cover, applications and load in compliance with DIN 582
	Cabinet dimensions										
	Height		Width	Depth							
No.	U	mm	mm	mm	PU 2 pieces assembled	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	PU 4 pieces assembled
Completely in RAL 7021					**RAL 7021**	**RAL 7021**	**RAL 7021**	**RAL 7021**		**RAL 7021**	
1	29	1400	600	600	21130-003	21130-063	21130-183	21130-153	**25127-995**	21130-242	**23130-072**
2	29	1400	600	800	21130-004					21130-243	
3	33	1600	600	600	21130-005	21130-065	21130-185	21130-155	**25127-995**	21130-242	**23130-072**
4	33	1600	600	800	21130-006					21130-243	
5	38	1800	600	600	21130-007	21130-067	21130-187	21130-157	**25127-995**	21130-242	**23130-072**
6	38	1800	600	800	21130-008					21130-243	
7	38	1800	800	600	21130-007	21130-068	21130-188	21130-158	**25127-995**	21130-246	**23130-072**
8	42	2000	600	300	21130-009	21130-069	21130-189	21130-159	**25127-995**	21130-241	**23130-072**
9	42	2000	600	600	21130-010	21130-069	21130-189	21130-159	**25127-995**	21130-242	**23130-072**
10	42	2000	600	800	21130-011					21130-243	
11	42	2000	800	600	21130-010	21130-070	21130-190	21130-160	**25127-995**	21130-246	**23130-072**
12	42	2000	800	800	21130-011					21130-247	
13	47	2200	600	300	21130-014	21130-071	21130-191	21130-161	**25127-995**	21130-241	**23130-072**
14	47	2200	600	600	21130-015	21130-071	21130-191	21130-161	**25127-995**	21130-242	**23130-072**
15	47	2200	600	800	21130-016					21130-243	
16	47	2200	800	800	21130-016	21130-072	21130-192	21130-162	**25127-995**	21130-247	**23130-072**
Colour combinations					**RAL 7035**	**RAL 7035**	**RAL 7035**	**RAL 7035**		**RAL 7021**	
17	29	1400	600	600	22130-003	22130-063	22130-183	22130-153	**25127-995**	21130-242	**23130-072**
18	29	1400	600	800	22130-004					21130-243	
19	33	1600	600	600	22130-005	22130-065	22130-185	22130-155	**25127-995**	21130-242	**23130-072**
20	33	1600	600	800	22130-006					21130-243	
21	38	1800	600	600	22130-007	22130-067	22130-187	22130-157	**25127-995**	21130-242	**23130-072**
22	38	1800	600	800	22130-008					21130-243	
23	38	1800	800	600	22130-007	22130-068	22130-188	22130-158	**25127-995**	21130-246	**23130-072**
24	42	2000	600	300	22130-009	22130-069	22130-189	22130-159	**25127-995**	21130-241	**23130-072**
25	42	2000	600	600	22130-010	22130-069	22130-189	22130-159	**25127-995**	21130-242	**23130-072**
26	42	2000	600	800	22130-011					21130-243	
27	42	2000	800	600	22130-010	22130-070	22130-190	22130-160	**25127-995**	21130-246	**23130-072**
28	42	2000	800	800	22130-011					21130-247	
29	47	2200	600	300	22130-014	22130-071	22130-191	22130-161	**25127-995**	21130-241	**23130-072**
30	47	2200	600	600	22130-015	22130-071	22130-191	22130-161	**25127-995**	21130-242	**23130-072**
31	47	2200	600	800	22130-016					21130-243	
32	47	2200	800	800	22130-016	22130-072	22130-192	22130-162	**25127-995**	21130-247	**23130-072**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

Cabinets – Varistar Electronics

VARISTAR IP 55 FLAT TOP COVERS, LIFTING EYES





ORDER INFORMATION

		Base plate			Base plate, one-piece, EMC, IP 55	Base/plinth		Base/plinth, mobile
		Base plate, multi-piece	Cover plate	Seal IP 55		Base/plinth, ventilated	Side cover	
	Completely in RAL 7021 (black grey)	 01004104	 01004106	 01004073	 01004051	 01004110	 01004053	 01004111
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	St, 1.5 mm, multi-piece, opening to rear 200 mm deep (no rear opening with 300 mm cabinet depth), incl. GND/earthing, dimension drawings see page 1.9	St, 1.5 mm, please order gasket IP55 separately	for base plate with cover	AlZn, 1.5 mm, incl. GND/earthing, assembly from outside	support with adjustable feet and 2 trims, perforated, static load-carrying capacity 1000 kg; please order side trims separately	St, 1.5 mm	support, St, 3 mm, trim, St, 1.5 mm, static load-carrying capacity on castors 400 kg, on adjustable feet 1000 kg

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	PU 1 kit assembled	PU 1 pair assembled	1 piece assembled
Completely in RAL 7021					**RAL 7021**	**RAL 7021**		**AlZn**	**RAL 7021**	**RAL 7021**	**RAL 7021**
1	29	1400	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
2	29	1400	600	800	**23130-002**			21130-282		**23130-170**	23130-209
3	33	1600	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
4	33	1600	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
5	38	1800	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
6	38	1800	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
7	38	1800	800	600	23130-005	**23130-036**	**23130-073**	21130-283	**23130-194**	**23130-169**	23130-212
8	42	2000	600	300	23130-009	–	**23130-073**	21130-285	**23130-187**	23130-166	–
9	42	2000	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
10	42	2000	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
11	42	2000	800	600	23130-005	**23130-036**	**23130-073**	21130-283	**23130-194**	**23130-169**	23130-212
12	42	2000	800	800	23130-006			21130-284		**23130-170**	23130-213
13	47	2200	600	300	23130-009	–	**23130-073**	21130-285	**23130-187**	23130-166	–
14	47	2200	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
15	47	2200	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
16	47	2200	800	800	23130-006	**23130-076**	**23130-073**	21130-284	**23130-194**	**23130-170**	23130-213
Colour combinations					**RAL 7021**	**RAL 7021**		**AlZn**	**RAL 7021**	**RAL 7021**	**RAL 7021**
17	29	1400	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
18	29	1400	600	800	**23130-002**			21130-282		**23130-170**	23130-209
19	33	1600	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
20	33	1600	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
21	38	1800	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
22	38	1800	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
23	38	1800	800	600	23130-005	**23130-036**	**23130-073**	21130-283	**23130-194**	**23130-169**	23130-212
24	42	2000	600	300	23130-009	–	**23130-073**	21130-285	**23130-187**	23130-166	–
25	42	2000	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
26	42	2000	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
27	42	2000	800	600	23130-005	**23130-036**	**23130-073**	21130-283	**23130-194**	**23130-169**	23130-212
28	42	2000	800	800	23130-006			21130-284		**23130-170**	23130-213
29	47	2200	600	300	23130-009	–	**23130-073**	21130-285	**23130-187**	23130-166	–
30	47	2200	600	600	**23130-001**	**23130-076**	**23130-073**	21130-281	**23130-187**	**23130-169**	23130-208
31	47	2200	600	800	**23130-002**			21130-282		**23130-170**	**23130-209**
32	47	2200	800	800	23130-006	**23130-076**	**23130-073**	21130-284	**23130-194**	**23130-170**	23130-213

VARISTAR IP 55 CONNECTING PLATES FOR SHORT DOORS/REAR PANELS








ORDER INFORMATION

		Dimensioning connecting plate door/rear panel	Connecting plate
	Completely in RAL 7021 (black grey)	 01005071	 01005072
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	door and rear panel must be selected 400 mm shorter than the cabinet height; cannot be used with double door	St, 1 mm, can also be fitted in upper part, height 400 mm, with assembly kit

Height mm	Width mm		1 piece assembled
Completely in RAL 7021			**RAL 7021**
400	600		21130-504
400	800		21130-505
Colour combinations			**RAL 7035**
400	600		22130-504
400	800		22130-505





Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

ORDER INFORMATION

		Dimension Standard fitting	19" panel/slide mounts EIA		U height identification for 19" panel/slide mount	19" assembly kit M6	Adapter bracket for reduced width
			Painted RAL 7021	AlZn			
	Completely in RAL 7021 (black grey)	 01004146	 01004112		 00505050	 sc128	 01004128
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	x_f = distance from front c = pitch of 19" panel/slide mounts D = cabinet depth W = cabinet width	St, 1.75 mm; reduced-width adapter bracket required for 800 mm width; depth members are required for partial-height mounting		paper strip, white, serial numbered from 1 ... 47 H	assembly kit: item 1: screws, item 2: cage nuts, item 3: washers	St, 2 mm, finish AlZn, for fixing the 19" panel/slide mounts in 800 mm wide cabinets

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	x_f mm	c mm	PU 1 pair assembled	PU 1 pair assembled	PU 4 pieces assembled	PU 50 pieces supplied loose	PU 4 pieces assembled
Completely in RAL 7021							**RAL 7021**	**AlZn**			**AlZn**
1	29	1400	600	600	50	500	**23130-012**	**23130-032**	**25127-997**	**21101-809**	–
2	29	1400	600	800	50	700					
3	33	1600	600	600	50	500	**23130-013**	**23130-033**	**25127-997**	**21101-809**	–
4	33	1600	600	800	50	700					
5	38	1800	600	600	50	500	**23130-014**	**23130-034**	**25127-997**	**21101-809**	–
6	38	1800	600	800	50	700					
7	38	1800	800	600	50	500	**23130-014**	**23130-034**	**25127-997**	**21101-809**	**23130-091**
8	42	2000	600	300	50	200	**23130-015**	**23130-035**	**25127-997**	**21101-809**	–
9	42	2000	600	600	50	500	**23130-015**	**23130-035**	**25127-997**	**21101-809**	–
10	42	2000	600	800	50	700					
11	42	2000	800	600	50	500	**23130-015**	**23130-035**	**25127-997**	**21101-809**	**23130-091**
12	42	2000	800	800	150	500					
13	47	2200	600	300	50	200	**23130-016**	**23130-036**	**25127-997**	**21101-809**	–
14	47	2200	600	600	50	500	**23130-016**	**23130-036**	**25127-997**	**21101-809**	–
15	47	2200	600	800	50	700					
16	47	2200	800	800	150	500	**23130-016**	**23130-036**	**25127-997**	**21101-809**	**23130-091**
Colour combinations							**RAL 7035**	**AlZn**			**AlZn**
17	29	1400	600	600	50	500	**23130-022**	**23130-032**	**25127-997**	**21101-809**	–
18	29	1400	600	800	50	700					
19	33	1600	600	600	50	500	**23130-023**	**23130-033**	**25127-997**	**21101-809**	–
20	33	1600	600	800	50	700					
21	38	1800	600	600	50	500	**23130-024**	**23130-034**	**25127-997**	**21101-809**	–
22	38	1800	600	800	50	700					
23	38	1800	800	600	50	500	**23130-024**	**23130-034**	**25127-997**	**21101-809**	**23130-091**
24	42	2000	600	300	50	200	**23130-025**	**23130-035**	**25127-997**	**21101-809**	–
25	42	2000	600	600	50	500	**23130-025**	**23130-035**	**25127-997**	**21101-809**	–
26	42	2000	600	800	50	700					
27	42	2000	800	600	50	500	**23130-025**	**23130-035**	**25127-997**	**21101-809**	**23130-091**
28	42	2000	800	800	150	500					
29	47	2200	600	300	50	200	**23130-026**	**23130-036**	**25127-997**	**21101-809**	–
30	47	2200	600	600	50	500	**23130-026**	**23130-036**	**25127-997**	**21101-809**	–
31	47	2200	600	800	50	700					
32	47	2200	800	800	150	500	**23130-026**	**23130-036**	**25127-997**	**21101-809**	**23130-091**

ORDER INFORMATION





		ETSI panel/slide mount	
		Dimensions	Panel/slide mount
	**Completely in RAL 7021 (black grey)**		
	**Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)**	in accordance with ETS 300119-3 and IEC 60917-211; SU = 25 mm	St, 2 mm, Al-Zn finish, suitable only for Slim-Line frame; shelves available on request

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	Height SU	PU 1 pair assembled
Completely in RAL 7021						**AlZn**
1	29	1400	600	600	50	23130-052
2	29	1400	600	800	50	
3	33	1600	600	600	60	23130-053
4	33	1600	600	800	60	
5	38	1800	600	600	68	23130-054
6	38	1800	600	800	68	
7	38	1800	800	600	68	23130-054
8	42	2000	600	300	76	23130-055
9	42	2000	600	600	76	23130-055
10	42	2000	600	800	76	
11	42	2000	800	600	76	23130-055
12	42	2000	800	800	76	
13	47	2200	600	300	84	23130-056
14	47	2200	600	600	84	23130-056
15	47	2200	600	800	84	
16	47	2200	800	800	84	23130-056
Colour combinations						**AlZn**
17	29	1400	600	600	50	23130-052
18	29	1400	600	800	50	
19	33	1600	600	600	60	23130-053
20	33	1600	600	800	60	
21	38	1800	600	600	68	23130-054
22	38	1800	600	800	68	
23	38	1800	800	600	68	23130-054
24	42	2000	600	300	76	23130-055
25	42	2000	600	600	76	23130-055
26	42	2000	600	800	76	
27	42	2000	800	600	76	23130-055
28	42	2000	800	800	76	
29	47	2200	600	300	84	23130-056
30	47	2200	600	600	84	23130-056
31	47	2200	600	800	84	
32	47	2200	800	800	84	23130-056

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days









INTERIOR MOUNTING SWING FRAMES FOR CABINET WIDTH 600 MM

ORDER INFORMATION

			Swing frame	Slide rail for swing frame	Stop 120°	Safety lock	Spare key
			 01005070 St, 2 mm, RAL 7021, load-carrying capacity: 150 kg, 120° hinge, square locks incl. 2 keys	 01018051	 01005061 St; for safety reasons a swing frame stop is recommended	 01015060 for swing frame, instead of square lock, incl. 2 keys	 01015059
Height U	Usable height U	Width mm	1 piece assembled	PU 2 pieces assembled	PU 1 kit assembled	1 piece assembled	PU 2 pieces supplied loose
Partial height	12	600	21130-740	23130-183	23130-158	**60113-267**	**60220-003**
	21	600	21130-741	23130-183	23130-158	**60113-267**	**60220-003**
29	25	600	21130-742	23130-183	23130-158	**60113-267**	**60220-003**
33	30	600	21130-743	23130-183	23130-158	**60113-267**	**60220-003**
38	34	600	21130-744	23130-183	23130-158	**60113-267**	**60220-003**
42	39	600	21130-745	23130-183	23130-158	**60113-267**	**60220-003**
47	43	600	21130-746	23130-183	23130-158	**60113-267**	**60220-003**

INTERIOR MOUNTING SWING FRAMES FOR CABINET WIDTH 800 MM









ORDER INFORMATION

			Swing frame 120°		Swing frame 160°		Slide rail for swing frame	Swing frame trim		Safety lock
			Swing frame 120°	Stop 120°	Swing frame 160°	Stop 160°		Asymmetrical assembly	Symmetrical assembly	
			 01005070 St, 2 mm, RAL 7021, load-carrying capacity150 kg, 120° hinge, square locks incl. 2 keys (Dimension	 01005061 St; for safety reasons a swing frame stop is recommended	 01005070 St, 2 mm, RAL 7021, load-carrying capacity 150 kg, 160° hinge, square locks incl. 2 keys	 01005061 St, swing frame stop is recommended for safety reasons	 01015060	 01005058 St, 1.5 mm, RAL 7021, trim (item 1, width 200 mm) incl. handle (item 2) and cut-out for cable eyes	 01005057 St, 1.5 mm, RAL 7021, trim (item 1, 2 x width 100 mm) incl. handle (item 2) and cut-out for cable eyes	 01015060 for swing frame, instead of square lock, incl. 2 keys
Height U	Usable height U	Width mm	1 piece assembled	PU 1 kit assembled	1 piece assembled	PU 1 kit assembled	PU 2 pieces assembled	1 piece assembled	PU 2 pieces assembled	1 piece assembled
Partial height	12	800	21130-747	23130-158	21130-761	23130-159	23130-184	–	–	**60113-267**
	21	800	21130-748	23130-158	21130-762	23130-159	23130-184	21130-432	21130-442	**60113-267**
29	25	800	21130-749	23130-158	21130-763	23130-159	23130-184	21130-433	21130-443	**60113-267**
33	30	800	21130-750	23130-158	21130-764	23130-159	23130-184	21130-434	21130-444	**60113-267**
38	34	800	21130-751	23130-158	21130-765	23130-159	23130-184	21130-435	21130-445	**60113-267**
42	39	800	21130-752	23130-158	21130-766	23130-159	23130-184	21130-436	21130-446	**60113-267**
47	43	800	21130-753	23130-158	21130-767	23130-159	23130-184	21130-437	21130-447	**60113-267**

Cabinets – Varistar Electronics








INTERIOR MOUNTING MOUNTING PLATE, STATIONARY SHELVES, 75 KG

ORDER INFORMATION

					Mounting plate			Stationary shelf	Stationary shelf	
					Full height	Height 1200 mm	Strengthening brackets	Full depth	Shortened by 100 mm	Depth member, 3 rows
					 01008052	 01008053	 01008080	 01004142	 01004142	 01004126
	Completely in RAL 7021 (black grey)				St, zinc-plated, 3 mm, static load-carrying capacity up to 450 kg (rear mounted); strengthening bracket increases static load-carrying capacity; please order separately		St profile, increases static load-carrying capacity of mounting plate to 150 kg	St, 1.5 mm, static load-carrying capacity 75 kg, 1 U, incl. GND/earthing	St, 1.5 mm, static load-carrying cap. 75 kg, 1 U, depth 479 mm, incl. GND/ earthing, for recessed installation order depth members separately	length 460 mm, St, 1.5 mm, finish AlZn; required for recessed shelf
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)									
	Cabinet dimensions									
No.	Height U	Height mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	PU 2 pieces assembled	1 piece assembled	1 piece assembled	PU 1 pair assembled
	Completely in RAL 7021				**zinc-plated**	**zinc-plated**	**RAL 7021**	**RAL 7021**	**RAL 7021**	**AlZn**
1	29	1400	600	600	–	23130-413	**23130-418**	**21130-323**	21130-322	**23130-081**
2	29	1400	600	800				21130-325	**21130-324**	**23130-082**
3	33	1600	600	600	–	23130-413	**23130-418**	**21130-323**	21130-322	**23130-081**
4	33	1600	600	800				21130-325	**21130-324**	**23130-082**
5	38	1800	600	600	23130-405	23130-413	**23130-418**	**21130-323**	21130-322	**23130-081**
6	38	1800	600	800				21130-325	**21130-324**	**23130-082**
7	38	1800	800	600	23130-406	23130-414	**23130-418**	21130-333	21130-332	**23130-081**
8	42	2000	600	300	23130-407	23130-413	**23130-418**	–	–	–
9	42	2000	600	600	23130-407	23130-413	**23130-418**	**21130-323**	21130-322	**23130-081**
10	42	2000	600	800				21130-325	**21130-324**	**23130-082**
11	42	2000	800	600	23130-408	23130-414	**23130-418**	21130-333	21130-332	**23130-081**
12	42	2000	800	800				21130-335	21130-334	**23130-082**
13	47	2200	600	300	–	23130-413	**23130-418**	–	–	–
14	47	2200	600	600	–	23130-413	**23130-418**	**21130-323**	21130-322	**23130-081**
15	47	2200	600	800				21130-325	**21130-324**	**23130-082**
16	47	2200	800	800	–	23130-414	**23130-418**	21130-335	21130-334	**23130-082**
	Colour combinations				**zinc-plated**	**zinc-plated**	**RAL 7021**	**RAL 7035**	**RAL 7035**	**AlZn**
17	29	1400	600	600	–	23130-413	**23130-418**	22130-323	22130-322	**23130-081**
18	29	1400	600	800				22130-325	22130-324	**23130-082**
19	33	1600	600	600	–	23130-413	**23130-418**	22130-323	22130-322	**23130-081**
20	33	1600	600	800				22130-325	22130-324	**23130-082**
21	38	1800	600	600	23130-405	23130-413	**23130-418**	22130-323	22130-322	**23130-081**
22	38	1800	600	800				22130-325	22130-324	**23130-082**
23	38	1800	800	600	23130-406	23130-414	**23130-418**	22130-333	22130-332	**23130-081**
24	42	2000	600	300	23130-407	23130-413	**23130-418**	–	–	–
25	42	2000	600	600	23130-407	23130-413	**23130-418**	22130-323	22130-322	**23130-081**
26	42	2000	600	800				22130-325	22130-324	**23130-082**
27	42	2000	800	600	23130-408	23130-414	**23130-418**	22130-333	22130-332	**23130-081**
28	42	2000	800	800				22130-335	22130-324	**23130-082**
29	47	2200	600	300	–	23130-413	**23130-418**	–	–	–
30	47	2200	600	600	–	23130-413	**23130-418**	22130-323	22130-322	**23130-081**
31	47	2200	600	800				22130-325	22130-324	**23130-082**
32	47	2200	800	800	–	23130-414	**23130-418**	22130-335	22130-334	**23130-082**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

ORDER INFORMATION









		Telescopic shelf, 2 U				
		Full depth	Shortened by 100 mm	Mounting bracket	T-bar lock	GND/earthing
	Completely in RAL 7021 (black grey)	 01004144	 01004145	 01005054	 01004125	 05904052
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	St, 1.5 mm, static load-carrying capacity 70/50 kg (width 600/ 800 mm), incl. telescopic slide, please order mounting bracket separately	St, 1.5 mm, static load-carrying capacity 70/50 kg (width 600/ 800 mm), incl. telescopic slide, please order mounting bracket separately	St, finish AlZn	to lock the telescopic shelf	for telescopic shelf

No.	Cabinet dimensions Height U	mm	Width mm	Depth mm	1 piece assembled	1 piece assembled	PU 4 pieces assembled	1 piece assembled	PU 1 kit assembled
Completely in RAL 7021					**RAL 7021**	**RAL 7021**	**AlZn**		
1	29	1400	600	600	**21130-353**	**21130-352**	**23130-274**	**23130-092**	**23130-140**
2	29	1400	600	800	**21130-355**	**21130-354**			
3	33	1600	600	600	**21130-353**	**21130-352**	**23130-274**	**23130-092**	**23130-140**
4	33	1600	600	800	**21130-355**	**21130-354**			
5	38	1800	600	600	**21130-353**	**21130-352**	**23130-274**	**23130-092**	**23130-140**
6	38	1800	600	800	**21130-355**	**21130-354**			
7	38	1800	800	600	21130-373	21130-372	**23130-274**	**23130-092**	**23130-140**
8	42	2000	600	300	–	–	–	–	–
9	42	2000	600	600	**21130-353**	**21130-352**	**23130-274**	**23130-092**	**23130-140**
10	42	2000	600	800	**21130-355**	**21130-354**			
11	42	2000	800	600	21130-373	21130-372	**23130-274**	**23130-092**	**23130-140**
12	42	2000	800	800	21130-375	21130-374			
13	47	2200	600	300	–	–	–	–	–
14	47	2200	600	600	**21130-353**	**21130-352**	**23130-274**	**23130-092**	**23130-140**
15	47	2200	600	800	**21130-355**	**21130-354**			
16	47	2200	800	800	21130-375	21130-374	**23130-274**	**23130-092**	**23130-140**
Colour combinations					**RAL 7035**	**RAL 7035**	**AlZn**		**RAL 7021**
17	29	1400	600	600	**22130-353**	22130-352	**23130-274**	**23130-092**	**23130-140**
18	29	1400	600	800	**22130-355**	22130-354			
19	33	1600	600	600	**22130-353**	22130-352	**23130-274**	**23130-092**	**23130-140**
20	33	1600	600	800	**22130-355**	22130-354			
21	38	1800	600	600	**22130-353**	22130-352	**23130-274**	**23130-092**	**23130-140**
22	38	1800	600	800	**22130-355**	22130-354			
23	38	1800	800	600	22130-373	22130-372	**23130-274**	**23130-092**	**23130-140**
24	42	2000	600	300	–	–	–	–	–
25	42	2000	600	600	**22130-353**	22130-352	**23130-274**	**23130-092**	**23130-140**
26	42	2000	600	800	**22130-355**	22130-354			
27	42	2000	800	600	22130-373	22130-372	**23130-274**	**23130-092**	**23130-140**
28	42	2000	800	800	22130-375	22130-374			
29	47	2200	600	300	–	–	–	–	–
30	47	2200	600	600	**22130-353**	22130-352	**23130-274**	**23130-092**	**23130-140**
31	47	2200	600	800	**22130-355**	22130-354			
32	47	2200	800	800	22130-375	22130-374	**23130-274**	**23130-092**	**23130-140**

Cabinets – Varistar Electronics

INTERIOR MOUNTING 19" SHELVES 1 U, STATIONARY 75 KG, TELESCOPIC 30 KG

ORDER INFORMATION








		Dimension Standard fitting	19" stationary shelf, 1 U, 75 kg		19" telescopic shelf, 1 U, 30 kg		
			Full depth	Shortened by 100 mm	Full depth	Shortened by 100 mm	GND/earthing
	Completely in RAL 7021 (black grey)	 01004146	 01004118	 01004119	 01004123	 01004122	 05904052
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	x_f = distance from front c = pitch of 19" panel/slide mounts D = cabinet depth W = cabinet width	St, 1.5 mm, static load-carrying capacity 75 kg, depth 600 mm, incl. GND/earthing	St, 1.5 mm, static load-carrying capacity 75 kg, depth 500 mm, incl. GND/earthing	St, 1.5 mm, static load-carrying capacity 30 kg, incl. telescopic slide; please order GND/ earthing kit separately	St, 1.5 mm, static load-carrying capacity 30 kg, incl. telescopic slide; please order GND/ earthing kit separately	for telescopic shelf

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	x_f mm	c mm	1 piece assembled	1 piece assembled	1 piece assembled	1 piece assembled	PU 1 kit assembled
Completely in RAL 7021							**RAL 7021**	**RAL 7021**	**RAL 7021**	**RAL 7021**	
1	29	1400	600	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
2	29	1400	600	800	50	700	**21130-305**	**21130-304**	**21130-345**	**21130-344**	
3	33	1600	600	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
4	33	1600	600	800	50	700	**21130-305**	**21130-304**	**21130-345**	**21130-344**	
5	38	1800	600	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
6	38	1800	600	800	50	700	**21130-305**	**21130-304**	**21130-345**	**21130-344**	
7	38	1800	800	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
8	42	2000	600	300	50	200	–	–	–	–	–
9	42	2000	600	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
10	42	2000	600	800	50	700	**21130-305**	**21130-304**	**21130-345**	**21130-344**	
11	42	2000	800	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
12	42	2000	800	800	150	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	
13	47	2200	600	300	50	200	–	–	–	–	–
14	47	2200	600	600	50	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
15	47	2200	600	800	50	700	**21130-305**	**21130-304**	**21130-345**	**21130-344**	
16	47	2200	800	800	150	500	**21130-303**	**21130-302**	**21130-343**	**21130-342**	**23130-140**
Colour combinations							**RAL 7035**	**RAL 7035**	**RAL 7035**	**RAL 7035**	
17	29	1400	600	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
18	29	1400	600	800	50	700	**22130-305**	**22130-304**	**22130-345**	**22130-344**	
19	33	1600	600	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
20	33	1600	600	800	50	700	**22130-305**	**22130-304**	**22130-345**	**22130-344**	
21	38	1800	600	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
22	38	1800	600	800	50	700	**22130-305**	**22130-304**	**22130-345**	**22130-344**	
23	38	1800	800	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
24	42	2000	600	300	50	200	–	–	–	–	–
25	42	2000	600	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
26	42	2000	600	800	50	700	**22130-305**	**22130-304**	**22130-345**	**22130-344**	
27	42	2000	800	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
28	42	2000	800	800	150	500	**22130-303**	22130-302	**22130-343**	**22130-342**	
29	47	2200	600	300	50	200	–	–	–	–	–
30	47	2200	600	600	50	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**
31	47	2200	600	800	50	700	**22130-305**	**22130-304**	**22130-345**	**22130-344**	
32	47	2200	800	800	150	500	**22130-303**	22130-302	**22130-343**	**22130-342**	**23130-140**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days







INTERIOR MOUNTING 19" TELESCOPIC SHELF, 2 U, 70 KG

ORDER INFORMATION

		Dimension Standard fitting	Telescopic shelf, 2 U, 70 kg			
			Full depth	Shortened by 100 mm	T-bar lock	GND/earthing
	Completely in RAL 7021 (black grey)	 01004146	 01004123	 01004122	 01004125	 05904052
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	x_f = distance from front c = pitch of 19" panel/slide mounts D = cabinet depth W = cabinet width	St, 1.5 mm, RAL 7021, static load-carrying capacity 70 kg, width 417 mm, depth 482 mm, incl. telescopic slide, please order, T-bar lock and earthing kit separately	St, 1.5 mm, RAL 7021, static load-carrying capacity 70 kg, width 400 mm, depth 682 mm, incl. telescopic slide, please order, T-bar lock and earthing kit separately	to lock the telescopic shelf	for telescopic shelf

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	x_f mm	c mm	1 piece assembled	1 piece assembled	1 piece assembled	PU 1 kit assembled
Completely in RAL 7021							**RAL 7021**	**RAL 7021**		
1	29	1400	600	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
2	29	1400	600	800	50	700	**21130-355**	**21130-354**		
3	33	1600	600	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
4	33	1600	600	800	50	700	**21130-355**	**21130-354**		
5	38	1800	600	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
6	38	1800	600	800	50	700	**21130-355**	**21130-354**		
7	38	1800	800	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
8	42	2000	600	300	50	200	–	–	–	–
9	42	2000	600	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
10	42	2000	600	800	50	700	**21130-355**	**21130-354**		
11	42	2000	800	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
12	42	2000	800	800	150	500	**21130-353**	**21130-352**		
13	47	2200	600	300	50	200	–	–	–	–
14	47	2200	600	600	50	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
15	47	2200	600	800	50	700	**21130-355**	**21130-354**		
16	47	2200	800	800	150	500	**21130-353**	**21130-352**	**23130-092**	**23130-140**
Colour combinations							**RAL 7035**	**RAL 7035**		
17	29	1400	600	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
18	29	1400	600	800	50	700	**22130-355**	22130-354		
19	33	1600	600	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
20	33	1600	600	800	50	700	**22130-355**	22130-354		
21	38	1800	600	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
22	38	1800	600	800	50	700	**22130-355**	22130-354		
23	38	1800	800	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
24	42	2000	600	300	50	200	–	–	–	–
25	42	2000	600	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
26	42	2000	600	800	50	700	**22130-355**	22130-354		
27	42	2000	800	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
28	42	2000	800	800	150	500	**22130-353**	22130-352		
29	47	2200	600	300	50	200	–	–	–	–
30	47	2200	600	600	50	500	**22130-353**	22130-352	**23130-092**	**23130-140**
31	47	2200	600	800	50	700	**22130-355**	22130-354		
32	47	2200	800	800	150	500	**22130-353**	22130-352	**23130-092**	**23130-140**








ORDER INFORMATION

		Dimension Standard fitting	Slide rail 25 kg	Slide rail 100 kg	Short slide rail	Depth member, 3 rows
 Completely in RAL 7021 (black grey)		 01004146	 01004115		 01004154	 01004126
 Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)		x_f = distance from front c = pitch of 19" panel/slide mounts D = cabinet depth W = cabinet width	St, 1.5 mm, finish AlZn, static load-carrying capacity 25 kg/pair	St, 2.5 mm, zinc-plated, static load-carrying capacity 100 kg/pair	St, 1.5 mm, finish AlZn, static load-carrying capacity 15 kg/pair	length 460 mm, St, 1.5 mm, finish AlZn; required for recessed shelf

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	x_f mm	c mm	PU 2 pieces supplied loose	PU 2 pieces supplied loose	PU 1 kit supplied loose	PU 1 pair assembled
Completely in RAL 7021							**AlZn**	**zinc-plated**	**AlZn**	**AlZn**
1	29	1400	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
2	29	1400	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
3	33	1600	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
4	33	1600	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
5	38	1800	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
6	38	1800	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
7	38	1800	800	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
8	42	2000	600	300	50	200	**23130-099**	**23130-116**	**23130-094**	–
9	42	2000	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
10	42	2000	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
11	42	2000	800	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
12	42	2000	800	800	150	500	**23130-096**	**23130-118**		**23130-082**
13	47	2200	600	300	50	200	**23130-099**	**23130-116**	**23130-094**	–
14	47	2200	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
15	47	2200	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
16	47	2200	800	800	150	500	**23130-096**	**23130-118**	**23130-094**	**23130-082**
Colour combinations							**AlZn**	**zinc-plated**	**AlZn**	**AlZn**
17	29	1400	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
18	29	1400	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
19	33	1600	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
20	33	1600	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
21	38	1800	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
22	38	1800	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
23	38	1800	800	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
24	42	2000	600	300	50	200	**23130-099**	**23130-116**	**23130-094**	–
25	42	2000	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	
26	42	2000	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
27	42	2000	800	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
28	42	2000	800	800	150	500	**23130-096**	**23130-118**		**23130-082**
29	47	2200	600	300	50	200	**23130-099**	**23130-116**	**23130-094**	–
30	47	2200	600	600	50	500	**23130-096**	**23130-118**	**23130-094**	**23130-081**
31	47	2200	600	800	50	700	**23130-097**	**23130-119**		**23130-082**
32	47	2200	800	800	150	500	**23130-096**	**23130-118**	**23130-094**	**23130-082**

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

ORDER INFORMATION


		Cable ducting with C-profile				
		C-rail for cabinet depth	C-rail for cabinet width	Slide nut	Cable shell	Cable support for C-rail
	Completely in RAL 7021 (black grey)	 01006109	 01006107	 01504054	 vnt009	 01006110
	Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)	St, 1.5 mm, finish AlZn	St, 1.5 mm, finish AlZn	for C-rail	for C-rail or for cable support rail, for cable bundles of 42 ... 46 mm, further dimensions see page 1.24	PA, UL 94 V-0, black, assembly by clipping onto the C-rail

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	PU 2 pieces supplied loose	PU 2 pieces supplied loose	PU 10 pieces supplied loose	PU 10 pieces supplied loose	PU 5 pieces supplied loose
Completely in RAL 7021					**AlZn**	**AlZn**			
1	29	1400	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
2	29	1400	600	800	**23130-087**				
3	33	1600	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
4	33	1600	600	800	**23130-087**				
5	38	1800	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
6	38	1800	600	800	**23130-087**				
7	38	1800	800	600	**23130-086**	**23130-334**	**21120-140**	**20114-731**	**60118-472**
8	42	2000	600	300	–	–	–	–	–
9	42	2000	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
10	42	2000	600	800	**23130-087**				
11	42	2000	800	600	**23130-086**	**23130-334**	**21120-140**	**20114-731**	**60118-472**
12	42	2000	800	800	**23130-087**				
13	47	2200	600	300	–	–	–	–	–
14	47	2200	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
15	47	2200	600	800	**23130-087**				
16	47	2200	800	800	**23130-087**	**23130-334**	**21120-140**	**20114-731**	**60118-472**
Colour combinations					**AlZn**	**AlZn**			
17	29	1400	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
18	29	1400	600	800	**23130-087**				
19	33	1600	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
20	33	1600	600	800	**23130-087**				
21	38	1800	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
22	38	1800	600	800	**23130-087**				
23	38	1800	800	600	**23130-086**	**23130-334**	**21120-140**	**20114-731**	**60118-472**
24	42	2000	600	300	–	–	–	–	–
25	42	2000	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
26	42	2000	600	800	**23130-087**				
27	42	2000	800	600	**23130-086**	**23130-334**	**21120-140**	**20114-731**	**60118-472**
28	42	2000	800	800	**23130-087**				
29	47	2200	600	300	–	–	–	–	–
30	47	2200	600	600	**23130-086**	**23130-333**	**21120-140**	**20114-731**	**60118-472**
31	47	2200	600	800					
32	47	2200	800	800	**23130-087**	**23130-334**	**21120-140**	**20114-731**	**60118-472**


Cabinets – Varistar Electronics

INTERIOR MOUNTING CABLE TIES, VELCRO


ORDER INFORMATION



Completely in RAL 7021 (black grey)




Colour combination RAL 7035 (light grey)/ RAL 7021 (black grey)



01005078

plastic, 92 mm x 2.5 mm, further dimensions see page 1.26



01005079

black, length 300 mm, further dimensions see page 1.26

No.	Cabinet dimensions Height U	Height mm	Width mm	Depth mm	Cable tie PU 25 pieces supplied loose	Velcro PU 10 pieces supplied loose
Completely in RAL 7021						
1	29	1400	600	600	**20118-351**	**20118-624**
2	29	1400	600	800		
3	33	1600	600	600	**20118-351**	**20118-624**
4	33	1600	600	800		
5	38	1800	600	600	**20118-351**	**20118-624**
6	38	1800	600	800		
7	38	1800	800	600	**20118-351**	**20118-624**
8	42	2000	600	300	–	–
9	42	2000	600	600	**20118-351**	**20118-624**
10	42	2000	600	800		
11	42	2000	800	600	**20118-351**	**20118-624**
12	42	2000	800	800		
13	47	2200	600	300	–	–
14	47	2200	600	600	**20118-351**	**20118-624**
15	47	2200	600	800		
16	47	2200	800	800	**20118-351**	**20118-624**
Colour combinations						
17	29	1400	600	600	**20118-351**	**20118-624**
18	29	1400	600	800		
19	33	1600	600	600	**20118-351**	**20118-624**
20	33	1600	600	800		
21	38	1800	600	600	**20118-351**	**20118-624**
22	38	1800	600	800		
23	38	1800	800	600	**20118-351**	**20118-624**
24	42	2000	600	300	–	–
25	42	2000	600	600	**20118-351**	**20118-624**
26	42	2000	600	800		
27	42	2000	800	600	**20118-351**	**20118-624**
28	42	2000	800	800		
29	47	2200	600	300	–	–
30	47	2200	600	600	**20118-351**	**20118-624**
31	47	2200	600	800		
32	47	2200	800	800	**20118-351**	**20118-624**

General components

Mechanics



from page 3.2

Electrics




from page 3.29

Power distribution



from page 3.50

Climate control



from page 4.0

Part number in bold face type: ready for despatch within 2 working days
Part number in normal type: ready for despatch within 10 working days

Cabinets – Varistar Platform

TWO LOAD-CARRYING CLASSES, ONE ACCESSORY RANGE: THE VARISTAR FRAMES



Varistar is the only cabinet platform that allows identical accessories to be combined with two basic frames.
The cabinet is available in Slim-Line (narrow) or Heavy-Duty (robust) profiles.

SLIM-LINE PROFILE

The Slim-Line version is based on very thin steel profiles in order to obtain the greatest opening width between the uprights. This frame can accommodate either 19" equipment or metric components to ETS 3000-119-3. With a maximum load of 400 kg* on the 19" plane the frame is still highly robust and suitable for demanding applications in electronics or data and network technology.

HEAVY-DUTY PROFILE

The Heavy-Duty frame, on the other hand, is designed for use with heavy loads or in regions susceptible to earthquakes. It offers on the one hand maximum stability for a load of up to 800 kg* on the 19" plane and, thanks to its high bending stiffness, can meet the shock and vibration requirements such as occur in railway and traffic signal installations, in the control of rotating machines, on commercial ships or in low-level military installations. In the IEC 61587-2 earthquake test the Heavy-Duty frame qualified for use in Bellcore Zone 3. Equipped with very simple, low-cost strengthening brackets, the Varistar Seismic version meets the demands of Bellcore Zone 4.




01006035

Slim-Line profile



01006034

Heavy-Duty profile



01008062


Heavy-duty profile with strengthening bracket

	Standard	Slim-Line	Heavy-Duty
Static load-carrying capacity	IEC 61587-1	400 kg *	800 kg *
Type of protection	IEC 60529	IP 20, IP 55	IP 20, IP 55
Shock test	IEC 61587-1	Maximum acceleration: 5 g Duration: 11 ms	Maximum acceleration: 5 g Duration: 11 ms
Vibration test	IEC 61587-1	Frequency: 5 Hz -100 Hz Acceleration: 1 g	Frequency: 5 Hz -100 Hz Acceleration: 1 g
Earthquake test	IEC 61587-2		Standard: up to Bellcore Zone 3, acceleration: 3 g, Frequency: 1 Hz ... 5 Hz With strengthening: up to Bellcore Zone 4, acceleration: 5 g, Frequency: 2 Hz ... 5 Hz
EMC shielding	IEC 61587-3	60 dB at 1 GHz, 40 dB at 3 GHz	60 dB at 1 GHz, 40 dB at 3 GHz
Installing options		19" or ETS	19"

* The figures for static load-carrying capacity are based on the test procedure of IEC 61587-1. In this procedure the cabinet must withstand being moved about on the floor and dropped from a height of 1000 mm onto a hard surface while carrying the maximum load, without sustaining substantial deformations to the frame or to the 19" panel/ slide mounts. The possible loading for the Varistar frame is therefore, under normal operating conditions, considerably higher than the test value given under IEC 61587-1.


DECIDEDLY DIFFERENT: THE VARISTAR SEALING AND SHIELDING CONCEPT

Item	Description
1	Frame
2	Conductive textile EMC gasket with CuNi coating
3	Contact/shielding
4	Rear panel
5	Side panel



In most shielding designs currently available, conductive seals or springs connect the cover parts to the cabinet frame. The points of contact have thus to be kept conductive and corrosion-free.
With VARISTAR, however, the conductive textile gaskets connect the cladding parts together directly, with two results:
A considerably better shielding performance of 60 dB at 1 GHz (and 40 dB at 3 GHz) is obtained than with conventional designs. There is no longer any need for expensive treatment of the frame surface.
The textile EMC gasket is at the same time also a shield against dust and water to IP 55. Where no shielding is required, a rubber gasket offering the same IP 55 protection is used. Both gaskets are fitted to the 45°-angled surface of the exterior of the frame.


Shielding up to 3 GHz



1: Cabinet with solid door 2: Cabinet with perforated door



SMOOTH-RUNNING AND ABSOLUTELY TIGHT: THE VARISTAR LOCKING SYSTEM



The latching system also contributes to protection class and shielding.
The innovative locking bar accepts a variable number of deadbolts, depending on the cabinet height, to ensure the most even compression of the gaskets.
And best of all: Activating the locking bar causes the latches to move in the opposite direction. Thus the frictional forces of the bolts are balanced out and a resulting lopsided vertical force on the door is avoided. The doors close easily and with an absolute seal.
EMC doors are fitted with 4-point locking, IP and server doors with 3-point locking.


Part number in bold face type: ready for shipping within 2 working days
Part number in normal type: ready for shipping within 10 working days

Cabinets – Varistar Platform

PEERLESS AND EFFICIENT: THE VARISTAR PROFILE (SLIM-LINE AND HEAVY-DUTY)

19" brackets are fixed without depth members





0100403401006105

Self-fixing cable eyes


The VARISTAR profile has fixing holes in all three axes (height, width, depth), following a 25 mm grid. This allows for the greatest variability in the fitting of components and accessories. Thus for example 19" panel/slide mounts may be installed in a 600 mm wide cabinet without additional depth members. This saves costs and provides stability on the 19" plane.
The intricately shaped form of the profile offers further new assembly possibilities. Cable eyes, for instance, can be plugged directly into the frame whilst fixing themselves.

NEW AND WELL THOUGHT OUT: VARISTAR CABLE MANAGEMENT

Schroff has divided the available space in the VARISTAR into zones and given a simple description of the position and use of these zones. The coloured arrows show the direction of the cable ducting.

For each zone a range of accessories has been developed to suit the conditions in the cabinet, which simplifies cabling and thus helps to include as many connections as possible in a distribution cabinet. The VARISTAR profile with its many fixing options has thus proved a real boon.


Zone 1



01006087

- In front of the 19" plane
- In this zone the patch cables are ducted horizontally between the distribution fields


Zone 2



01006088

- On the right and left hand side, next to the 19" plane
- In this zone patch cables are ducted vertically in a kind of channel to the individual components


Zone 3



01006085

- Zone 3 is located laterally behind the 19" plane across the cabinet depth; mainly for 800 mm wide cabinets
- In this zone entering cable bundles are fixed in the cabinet, parted and ducted to the rear of the distribution fields

Zone 4




01006086

- Zone 4 is located in the rear across the cabinet width
- Alternative to zone 3 for only 600 mm wide cabinets or when cable entry is at the rear of the cabinet

HEAT DISSIPATION TO EXACT REQUIREMENTS: COOLING CONCEPTS FOR VARISTAR

Depending on installed heat dissipation and the surroundings, VARISTAR offers various cooling options and also good conditions for problem-free operation of the installed equipment.
Either top cover fans are used to assist the heat dissipation or perforated doors with 78 % air throughput are fitted.
Additionally, VARISTAR LHX 20/40 with assembled air/water heat exchanger allows to cool especially strained appliances with water.
And that for up to 40 kW per cabinet.




01106027

Fan unit, positioned inside


41003017

78 % air throughput


01005020

Air/water heat exchanger

CLASSIC AND CONSISTENT: VARISTAR COLOUR AND DESIGN

As well as its functional aspects, in the development of VARISTAR the design of the individual components and their combined effect on the appearance of the cabinet was always a priority. The cabinet gains its characteristic, unmistakable look from the high narrow door with the memorable hinges and the very thin, almost inconspicuous top cover edge. While rack, base and cover are offered in black grey (RAL 7021) for all standard cabinets, a choice of two colour options are available - even in our standard programme - for side panels, doors and rear panels:

Either entirely black grey (RAL 7021), as is the contemporary look in data centres and recording studios. Or in light grey (RAL 7035), whereby an attractive combination of mainly light surfaces with a few dark accents is obtained.
Alternatively, VARISTAR can be supplied in many RAL colours within 15 working days, or even as a combination of two special colours. The current range of colours can be seen online at **www.schroff.de/modification**.


01006037


Colour RAL 7021 (black grey)


01006036

Colour combination RAL 7035/RAL 7021 (light grey/black grey)

Part number in bold face type: ready for shipping within 2 working days
Part number in normal type: ready for shipping within 10 working days

FRAME DIMENSIONS



01005087

Height

Cabinet height		Frame	
		H	h
mm	U	mm	mm
1200	24	1192	1102
1400	29	1392	1302
1600	33	1592	1502
1800	38	1792	1702
2000	42	1992	1902
2200	47	2192	2102


Width

Cabinet width	Frame	Slim-Line	Heavy-Duty
	W	w	w
mm	mm	mm	mm
600	592	535	502
800	792	735	702

Depth


Cabinet depth		Frame		
	D	d	d_1	d_2
mm	mm	mm	mm	mm
300	292	128.8	150	175
600	592	428.8	450	475
800	792	628.8	650	675
900	892	728.8	750	775
1000	992	828.8	850	875
1100	1092	928.8	950	975
1200	1192	1028.8	1050	1075

Adjustable feet




01004081

Castors with adjustable feet




Locking castors




0100408201004156

Base/plinth



Mobile base/plinth




0100411001004111

Height of adjustable feet, castors, base/plinth


Adjustable feet	20 ... 40 mm
Locking castors	85 mm
Castors with adjustable feet	85 ... 95 mm
Base/plinth (feet)	112 ... 132 mm
Base/plinth, mobile	126.5 ... 134.5 mm

TOP COVER WITH CUT-OUT ZONES



	W = 600 mm					W = 800 mm				
D	a	b	c	d	e	a	b	c	d	e
600	-	✓	✓	-	-	-	✓	✓	-	-
800	-	✓	✓	✓	-	✓	✓	✓	✓	-
900	-	✓	✓	✓	-	✓	✓	✓	✓	-
1000	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
1100	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
1200	-	✓	✓	✓	✓	✓	✓	✓	✓	✓

BASE PLATE, MULTI-PIECE



	Depth in mm		
D	a	b	c
600	300	-	-
800	300	200	-
900	300	300	-
1000	300	200	200
1100	300	300	200
1200	300	300	300

Cabinet width W mm	Opening width w mm
600	426
800	626

Part number in bold face type: ready for shipping within 2 working days
Part number in normal type: ready for shipping within 10 working days

North America

Warwick, RI, USA
Tel +1.800.525.4682
San Diego, CA, USA
Tel +1.800.854.7086

Europe, Middle East & India

Straubenhardt, Germany
Tel +49 7082 794 0
Betschdorf, France
Tel +33 3 88 90 64 90
Warsaw, Poland
Tel +48 22 209 98 35
Hemel Hempstead,
Great Britain
Tel +44 1442 24 04 71
Lainate, Italy
Tel +39 02 932 714 1
Dubai, United Arab Emirates
Tel +971 4 37 81 700
Bangalore, India
Tel +91 80 67152000
Istanbul, Turkey
Tel +90 216 250 7374

Asia Pacific

Shanghai, China
Tel +86 21 2412 6943
Singapore
Tel +65 6768 5800
Shin-Yokohama, Japan
Tel +81 45 476 0271

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

nVent

nVent.com/SCHROFF

©2018 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.