DATASHEET - M22-SOL-PVLPL11-230Q

Fireman's switch, PV, 1N/O+1N/C, FW switch, red, IP65_x

Part no.	**M22-SOL-PVLPL11-230Q**
	152627
EL Number (Norway)	**4300329**

General specifications			
Product name			Eaton Moeller® series M22 Fireman's switch
Part no.			M22-SOL-PVLPL11-230Q
EAN			4015081493654
Product Length/Depth			110 millimetre
Product height			80 millimetre
Product width			72 millimetre
Product weight			0.273 kilogram
Compliances			CE
Product Tradename			M22
Product Type			Fireman's switch
Product Sub Type			None
Features & Functions			
Bezel color			Other
Bezel material			Plastic
Electric connection type			Screw connection
Fitted with:			Light source
General information			
Degree of protection			NEMA 4X IP65
Opening diameter			22.5 mm
Suitable for			Illumination
Electrical rating			
Supply voltage - max			230 V
Actuator			
Actuator color			Red
Actuator type			Turn button
Number of switch positions			2
Contacts			
Number of contacts (change-over contacts)			0
Number of contacts (normally closed contacts)			1
Number of contacts (normally open contacts)			1

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Selector switch, complete (EC001029)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Selector switch, complete unit (ecl@ss13-27-37-12-43 [ACN984016])

Number of switch positions			2
Type of control element			Turn button
Suitable for illumination			Yes
With light source			Yes
Colour button			Red
Hole diameter		mm	22.5
Width opening		mm	0
Height opening		mm	0
Switching function latching			No
Spring-return			No
Degree of protection (IP)			IP65

Degree of protection (NEMA)			4X
Supply voltage		V	230 - 230
Power loss		W	
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Type of electric connection			Screw connection
With front ring			No
Material front ring			Plastic
Colour front ring			Other

© 04/2023 by Eaton Industries GmbH