# SKINDICHT® O-Ring NBR metric

SKINDICHT® O-Ring NBR metric,incised seal for sealing the housing reliably, to protect against oils, dust and water, ozone&amp
UV-resistant



UV-resistant

## Application range

For sealing the housing reliably to protect against oils, dust, and water at the connection thread of a gland or other similar parts

## Note

O-rings with thickness of 1.5 mm are recommended for optimum sealing of the converter SKINDICHT® ZSE-M12/16/20 x 1.5
Delivery will be made in the largest possible packing unit (bulk goods), minimum order quantity is one packing unit

## Technical Data

| | |
|---|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC001181<br>ETIM 5.0 Class-Description: Sealing ring |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC001181<br>ETIM 6.0 Class-Description: Sealing ring |
| Colour delivered: | Black |
| Material: | NBR |
| Temperature range: | -30°C to +100°C |

## Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.


©2018 Lapp Group - Technical changes reserved

LAPP

# SKINDICHT® O-Ring NBR metric

PRODUCT INFORMATION

| Article number | Article designation / size | Inner Ø (mm) | Cable thickness (mm) |
|---|---|---|---|
| SKINDICHT® O-Ring NBR | | | |
| 53102001 | M 12 x 1,5 | 9.0 | 1.5 |
| 53102000 | M 12 x 2,0 | 9.0 | 2 |
| 53102010 | M 16 x 2,0 | 13.0 | 2 |
| 53102021 | M 20 x 1,5 | 17.0 | 1.5 |
| 53102020 | M 20 x 2,0 | 17.0 | 2 |
| 53102030 | M 25 x 2,0 | 22.0 | 2 |
| 53102040 | M 32 x 2,0 | 28.0 | 2 |
| 53102050 | M 40 x 2,0 | 36.0 | 2 |
| 53102060 | M 50 x 2,0 | 46.0 | 2 |
| 53102070 | M 63 x 2,0 | 57.0 | 2 |

Last Update (26.11.2018)
©2018 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16