EXR.1 - Standard bits series 1 for Resistorx® screws



Standards:

NF ISO 1173, ISO 1173

Description:

- Compliant with Resistorx® specifications.
- For manual screwing.
- Drive 1/4" - 6.35 mm.
- Long bits 70 mm are low cut for access to screws inserted in the wells.

© FACOM 2020

	A [mm]	Length L [mm]	Weight [g]	Resistorx Number [']	Diameter [mm]
EXR.110	2.72	25.0	5.0	TT10	
EXR.110L	2.72	70.0	8.0	TT10	5.2
EXR.115	3.26	25.0	6.0	TT15	
EXR.115L	3.26	70.0	8.0	TT15	5.2
EXR.120	3.84	25.0	6.0	TT20	
EXR.120L	3.84	70.0	9.0	TT20	5.6
EXR.125	4.4	25.0	6.0	TT25	
EXR.125L	4.4	70.0	11.0	TT25	5.6
EXR.127	4.96	25.0	6.0	TT27	
EXR.130	5.59	25.0	6.0	TT30	
EXR.130L	5.59	70.0	14.0	TT30	6.0
EXR.140	6.6	25.0	6.0	TT40	
EXR.140L	6.6	70.0	17.0	TT40	7.1

© FACOM 2020