Spec Sheet

TILSATEC®

53 7121

Lightweight cut level **F** sandy foam nitrile palm coated glove with reinforcement



Code	53-7121
Description	Lightweight cut level F sandy foam nitrile coated glove with reinforcement
Gauge	13gg
Colour	Grey liner / Black coating
Cuff Style	Knit wrist
Length	220-270mm
Sizes	6/XS - 11/2XL
Packaging	12 pairs/polybag 120 pairs/carton

Features & Benefits

- EN388: 2016 level F cut resistance
- New Rhino Yarn™ composition using lighter, finer steel
- Additional black nitrile reinforcement to thumb crotch for high action area increasing lifespan of glove
- EN407:2020 contact heat level 1
- 360 breathability reduces perspiration
- Sandy foam nitrile palm coating provides good wet and dry grip
- New back of hand markings

Applications / Industries

- Assembly
- Automotive industry
- Light metal fabrication / stamping
- Glass Manufacturing
- White goods manufacturing

Performance

EN388: 2016 — 4 X 4 2 F

EN407:2020 — X 1 X X X X

ANSI 105: 2016 — A6 — CUT

CE UKCA

Sizing Cuff Colours

Size	6 X-Small	7 Small	8 Medium	9 Large	10 X-Large	11 2X-Large
Colour coded cuff						

RHINOYARN®

Made with Tilsatec Rhino Yarn™ technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

tilsatec.com/products/lightweight-cut-level-f-foam-nitrile-coated-glove-thumb-reinforcement-53-7121

Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | **www.tilsatec.com**

For businesses who want expertise they can rely on to keep their people safe, Tilsatec offer high performance hand and arm protection. We manufacture our own proprietary cut resistant yarn - the primary source of mechanical protection, on site in the UK. This means we can deliver maximum performance in every fibre of what we do. Because when our gloves perform at their best, your people can perform at their best.