Date: 13/04/2023

RLS-2000; Guide tube length: 1500.0; 3 switching outputs

RLS-2000; Guide tube length: 1500.0; 3 switching outputs

Item number: 48791129

Quantity: 1 pcs.

Order code: RLS-20005M2015002080000214500ZZZZZZ1GZ18S150006Z8
Z2W101ARS2ZL5

Overview:
RLS-2000; Guide tube length: 1500.0; 3 switching outputs
Magnetic float switch, Plastic version Model RLS-2000
Output Signal: 3 switching outputs
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : Normally open / n.o.
Switch position - Switch output 1 : 150 mm
Switching function - Switch output 2 : Normally open / n.o.
Switch position - Switch output 2: 800.0
Switching function - Switch output 3: Normally open / n.o.
Switch position - Switch output 3: 1450.0
Switch position - Switch output 4: without
Electrical connection: Circular connector M12x1, IP65
pin assignment el. connection: see product label
Process connection: G 1/2, installation from inside
Guide tube length: 1500.0 mm
Material: Polypropylene
medium temperature: -10 °C ... 80 °C
Float: Polypropylene float, Ø55 mm, PN3
Specifications according to data sheet: LM 50.04

Details:
RLS-2000; Guide tube length: 1500.0; 3 switching outputs
Magnetic float switch, Plastic version Model RLS-2000
Output Signal: 3 switching outputs
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : Normally open / n.o.
Switch position - Switch output 1 : 150 mm
Switching function - Switch output 2 : Normally open / n.o.
Switch position - Switch output 2: 800.0
Switching function - Switch output 3: Normally open / n.o.
Switch position - Switch output 3: 1450.0
Switch position - Switch output 4: without
Electrical connection: Circular connector M12x1, IP65

© 2023 - WIKA Instruments s.a.r.l.

pin assignment el. connection: see product label
Process connection: G 1/2, installation from inside
Guide tube length: 1500.0 mm
Material: Polypropylene
medium temperature: -10 °C ... 80 °C
Float: Polypropylene float, Ø55 mm, PN3
Specifications according to data sheet: LM 50.04

© 2023 - WIKA Instruments s.a.r.l.