Date: 12/04/2023

BADN 0 … 6 bar 1/4 NPT-F 1/2 -14 NPT-F

Bourdon tube pressure switch, Flameproof enclosure Ex d

Item number: 48800611

Quantity: 1 pcs.

Order code: BA-DNBBEB1AAAMZZZ1ZZ ZKC
F4-C5- - - - -

Overview:
BADN 0 … 6 bar 1/4 NPT-F 1/2 -14 NPT-F
Bourdon tube pressure switch, Flameproof enclosure Ex d
Model BA, Ex d IIC Gb, Ex tb IIIC Db and Ex d II 2 GD, only for non-flammable process fluids
Contact version: 2 x SPDT or 1 x DPDT silver contact
Setting range, working range, proof pressure: 0 … 6 bar, working range 0 … 6 bar, proof pressure 12 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
measuring elements and wetted materials: Bourdon Tube and Process Connection AISI 316L
Enclosure with plate for wall or direct mounting
Brand: WIKA Instruments Italia
Ingress Protection: IP66
Specifications according to data sheet: PV 32.21
Repeatability of set point: ≤ 0,5% of span

Set point definition: Set Point not defined
Approvals / Certificates
IECEx-ATEX Ex d

Details:
Bourdon tube pressure switch, Flameproof enclosure Ex d
Specifications according to data sheet: PV 32.21
Repeatability of set point: ≤ 0,5% of span
Model BA, Ex d IIC Gb, Ex tb IIIC Db and Ex d II 2 GD, only for non-flammable process fluids
2 x SPDT or 1 x DPDT silver contact
0 … 6 bar, working range 0 … 6 bar, proof pressure 12 bar
Set Point not defined
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
Bourdon Tube and Process Connection AISI 316L
Enclosure with plate for wall or direct mounting
Approvals / Certificates: with
Switch standard: without
Ingress Protection: IP66
Brand: WIKA Instruments Italia

© 2023 - WIKA Instruments s.a.r.l.

Unit: bar
BADN 0 … 6 bar
Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.