Chemical protection

ULTRANEO 341

Frequent contact | continous wear

Comfort with standard chemical protection



CHEMICAL PROTECTION
TYPE A

EN388	EN ISO 374-1	EN ISO 374-5
2121X	TYPE A ACLMNS	

EN407	CATEGORY 3	DEXTERITY
X1XXXX	0334	EN ISO 21420: 5/5

SPECIFIC ADVANTAGES

Comfort

- Suitable for long-term wear; added comfort of textile support

Durability

- Longer service life for heavy-duty work: good mechanical resistance

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Additional benefits

- Longer length provides forearm protection

Care for the environment

- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive/mechanical industry
- Chemical industry
- Other industries

APPLICATIONS

- Chemical treatment of metals
- Handling and transporting chemicals
- Industrial cleaning, maintenance
- Timber treatment
- Battery, pump, and compressor manufacturing

Edit 01/12/2024

Chemical protection

ULTRANEO 341

Frequent contact | continous wear

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

2	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 — THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread

EN ISO 374-1 — CHEMICAL RISKS



TYPE A

A: Methanol
C: Acetonitrile
L: Sulphuric acid 96%
M: Nitric acid 65%
N: Acetic acid 99%
S: Hydrofluoric acid 40%

EN ISO 374-5 — MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Smooth
Material	Polychloroprene and natural latex
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	38
Thickness (mm)	1.45
European sizes	8 9 10 11

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/box 50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2994
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 01/12/2024