# DATASHEET - PKZ0-XHT-MCC

## Door coupling handle, for MCC-V. 90 degree, twisted

**Part no.** **PKZ0-XHT-MCC**
**164297**

| | |
|---|---|
| Product name | Eaton Moeller® series PKZ0 Accessory Door coupling handle |
| Part no. | PKZ0-XHT-MCC |
| EAN | 4015081608256 |
| Product Length/Depth | 235 millimetre |
| Product height | 66 millimetre |
| Product width | 64 millimetre |
| Product weight | 0.16 kilogram |
| Certifications | EN 60204 |
| Product Tradename | PKZ0 |
| Product Type | Accessory |
| Product Sub Type | Door coupling handle |
| Catalog Notes | Cannot be used in combination with VHI20-PKZ0. |
| | |
| Color | Black |
| Features | Lockable |
| Fitted with: | Axis extension<br>Door interlock<br>ON/OFF switch position and “+” (tripped), lockable<br>3 padlocks, 4 - 8 mm hasp thickness |
| | |
| Degree of protection | NEMA Other |
| Suitable as | Main switch to EN 60204 in MCC power distribution systems and with PKZM0 installed when rotated by 90° |
| | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 55 °C |
| | |
| Equipment heat dissipation, current-dependent Pvid | 0 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0 W |
| Rated operational current for specified heat dissipation (In) | 0 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Please enquire |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | Not applicable. |

| | | | |
|---|---|---|---|
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

| | | | |
|---|---|---|---|
| Low-voltage industrial components (EG000017) / Door coupling handle for switchgear (EC000230) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Hand drive for switch devices (ecl@ss10.0.1-27-37-04-15 [AKF013014]) | | | |
| With axis extension | | | Yes |
| With door interlock | | | Yes |
| Lockable | | | Yes |
| With handle red/yellow | | | No |
| Degree of protection (NEMA) | | | Other |


© 04/2023 by Eaton Industries GmbH