Specifications

Eaton 199438

Catalog Number: 199438

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 9.5 A, 4 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS2



General specifications

Product Name
Eaton DC1 Variable frequency drive

Catalog Number
199438

EAN
4015081978274

Product Length/Depth
182 mm

Product Height
257 mm

Product Width
188 mm

Product Weight
3.5 kg

Certifications
CE
UL Listed
RCM
Certified by UL for use in Canada
CUL
CSA-C22.2 No. 14
IEC/EN 61800-2
IEC/EN 61800-3
UL report applies to both US and Canada
UkrSEPRO
UL File No.: E172143
UL Category Control No.: NMMS, NMMS7
IEC/EN61800-5
IEC/EN 61800-5-1
UL 508C

Powering Business Worldwide

RoHS, ISO 9001
CE marking
U
EAC

Features & Functions

Features

Parameterization: Fieldbus
Parameterization: drivesConnect mobile (App)
Parameterization: drivesConnect
Parameterization: Keypad

Fitted with:

Radio interference suppression filter
Internal DC link
UV resistance
Additional PCB protection
Breaking resistance
7-digital display assembly
IGBT inverter
Control unit
Local controls
PC connection
Brake chopper

Functions

4-quadrant operation possible

Catalog Notes

Environmental class: 3C3, 3S3
Overload cycle for 60 s every 600 s
For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz

General

Cable length

C3 ≤ 25 m, maximum motor cable length
150 m, unscreened, maximum permissible cable length
300 m, unscreened, with motor choke, maximum permissible, Motor feeder
100 m, screened, maximum permissible cable length
200 m, screened, with motor choke, maximum permissible cable length
C2 ≤ 5 m, maximum motor cable length

Communication interface

SmartWire-DT, optional
OP-Bus (RS485), built in
CANopen®, built in
Modbus RTU, built in

Connection to SmartWire-DT

No

Degree of protection

IP66
NEMA 4X

Climatic environmental conditions

Altitude

Above 1000 m with 1 % derating per 100 m
Max. 4000 m

Ambient operating temperature - min

-20 °C

Ambient operating temperature - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

60 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Frame size

FS2

Mounting position

Vertical

Product category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Protocol

EtherNet/IP
Other bus systems
CAN
MODBUS

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments

Suitable for

Branch circuits, (UL/CSA)

Efficiency

97 % (η)

Heat dissipation capacity Pdiss

0 W

Input current ILN at 150% overload

11.5 A

Leakage current at ground IPE - max

12.6 mA

Mains switch-on frequency

Maximum of one time every 30 seconds

Mains voltage - min

380 V

Mains voltage - max

480 V

Operating mode

Synchronous reluctance motors
Speed control with slip compensation
U/f control
Sensorless vector control (SLV)
BLDC motors
PM motors

Output frequency - min

0 Hz

Output frequency - max

500 Hz

Output voltage (U2)

480 V AC, 3-phase
400 V AC, 3-phase

Overload current IL at 150% overload

14.25 A

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

48 Hz

Rated frequency - max

62 Hz

Rated operational current (Ie)

9.5 A at 150% overload (at an operating frequency of 6 kHz and an ambient air temperature of +40 °C)

Rated operational power at 380/400 V, 50 Hz, 3-phase

4 kW

Rated operational voltage

400 V AC, 3-phase

480 V AC, 3-phase

Resolution

0.1 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

15 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

175 % IH

Supply frequency

50/60 Hz

Switching frequency

8 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit

System configuration type

AC supply systems with earthed center point

Voltage rating - max

480 V

Motor rating

Assigned motor current IM at 110/120 V, 60 Hz, 150% overload

7.6 A

Assigned motor current IM at 115 V, 50 Hz, 150% overload

8.5 A

Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload

7.6 A

Assigned motor current IM at 230 V, 50 Hz, 150% overload

8.5 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

8.5 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

7.6 A

Assigned motor power at 115/120 V, 60 Hz, 1-phase

5 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

5 HP

Assigned motor power at 460/480 V, 60 Hz

5 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

5 HP

Apparent power

Apparent power at 400 V

6.58 kVA

Apparent power at 480 V

7.9 kVA

Braking function

Braking resistance

120 Ω

Braking torque

Max. 30 % MN, Standard - Main circuit

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit

Max. 100 % of rated operational current Ie, variable, DC - Main circuit

Switch-on threshold for the braking transistor

780 VDC

Control circuit

Number of inputs (analog)

Design verification

Heat dissipation capacity Pdiss

2 (parameterizable, 0 - 10 V DC, 0/4 - 20 mA)

Number of inputs (digital)

4 (parameterizable, 10 - 30 V DC)

Number of outputs (analog)

1

Number of outputs (digital)

1

Number of relay outputs

1 (parameterizable, N/O, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Electromagnetic compatibility (EMC)

How does the internal motor protection work?

Access to Parameter Levels 2 + 3 Parameter Lock - Load Default

Starting, Stopping and Operation

I/O Configuration

Operating Permanent Magnet and Brushless DC Motors

Low Temperature Applications

PI controller

Fire Mode

Connecting drives to generator supplies

Update DX-COM-STICK3

Set Point Setting

Operating Single Phase Motors

The OP System Bus - Parameterizing - Control

DX-COM-STICK3_Connection

Conformal Coating

Dependency of the output current on switching frequency and ambient temperature

Motor data - Motor Protection - V/f curves Slip Compensation

Brochures

eaton-powerxl-variable-frequency-drives-dc1-da1-brochure-br040001en-en-us.pdf

DA-SW-drivesConnect

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004555.pdf

DA-DC-00003964.pdf

DA-DC-00004184.pdf

DA-DC-00004552.pdf

Drawings

eaton-frequency-inverter-dc1-dimensions-003.eps

Installation instructions

eaton-powerxl-dc1-ip66-instruction-leaflet-il040059zu.pdf

Installation videos

Video PowerXL DA1

PowerXL Variable Frequency Drives DC1 and DA1 - EN

Manuals and user guides

MN040018_EN

MN040022_EN

MN040003_EN

MN040059_EN

eaton-canopen-communication-manual-for-variable-frequency-drives-variable-speed-starters-da1-db1-dc1-de11-mn040019-en-us.pdf

mCAD model

e3_s2_ip66_mit_bedienelementen.dwg

e3_s2_ip66_mit_bedienelementen.stp

Multimedia

Looking for variable frequency drives DC1 and DA1 which can be used in harsh environments?

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia