Technical Specifications

Webbing anchorage sling

References:

0.6 m 1002916
0.8 m 1002917
1 m 1003245
1.2 m 1002918
1.5 m 1002919



Features:

Yellow webbing:
Material: Polyester 23 mm
Breaking strength: > 1000 daN

Tubular webbing :
24mm
Breaking strength: > 1150 daN

Sling in m	0.6	0.8	1	1.2	1.5
Colours	Blue	purple	green	black	red
Material	PES	PES	PES	PES	PES
Weight in Kg	0.104	0.119	0.138	0.178	0.214

PA : Polyamide
PES : Polyester

Tests:
Static test: > 1500 daN
Temperature : +50°C

EN 795 B : Anchorage devices – class B

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com