CAT. N° 4 173 45



MPCB MPX³ 32 MA - MAGNETIC - MOTOR PROTECTION - 3P - 1.6 A - 100 KA

Pack (number of units)	1
Volume (dm³)	0,545
Weight (g)	359,00

Product characteristics

Magnetic only MPCBs
- Without thermal release
- Magnetic release 13 x Ie max.

MPX³ 32MA
- High breaking capacity
- With rotary handle
- Fixing on rail
- 3P
- 3-phase motor 400/415 V : 0.37/0.55 kW
- Magnetic release operating current : 20.8 A
- 415 V breaking capacity Icu : 100 kA

General characteristics

MPCBs MPX³ - motor protection circuit breakers from 0.16 A to 100 A
- Conform to IEC 60947-1, IEC 60947-2, IEC 60947-4 ; class 10

Documentation

Catalogue pages & additional information
- Technical page (p.182-183)
- Description page (p.184)
- MPCBs MPX3

Installation & technical data
- F01988EN-05

Installation instructions & related documents
- LE07207AB

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.