DAYTONA S3

SRC

0% METAL

Standard EN ISO 20345 : 2011

LEMAITRE
Safety since 1974



THE PLUS PRODUCT

0% metal model. Suitable for areas equipped with metal detectors (warehouses,...).

Size 35 to 50 Réf. **DAYTS30BN**

Product Highlights

- **2,0 mm thick high strengh leather**: against abrasion, tearing and puncture.
- **Anti-abrasion upper,** additional resistance of the stem on the forefoot that ensures a long life to the product.
- **Comfort sole with shock absorbing heel pad:** reduction of impact and fatigue, prevention of MSD.
- **Tongue with gusset** to prevent the intrusion of dust inside the shoe.
- **Extreme size coverage:** model available up to size 50.
- **Protective toe-cap**: polycarbonate.
- **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



C07 PU2D antistatic sole

- **Wide and comfortable shoe**
- **Versatility:** effective spikes on industrial floors and outdoor surfaces
- **Extended contact area and 10 mm offset heel:** self-cleaning and multi-functional sole with excellent stability
- **Rounded heel attack** for a natural rolling of the foot

USAGE

- Indoor and outdoor use: excellent versatility.

FRENCH TRADEMARK

DEVELOPED RESPECTING THE FOOT ANATOMY

lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority

DAYTONA S3

SRC 0% METAL

Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** water-repellent leather with abrasion-resistant uppers
- **Tongue with gusset:** abrasion resistant textile
- **Lining:** 3D microporus fabric

Characteristics of the sole

- **Designation:** C07
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
  forward flat slip: 0,32 (standard ≥ 0,32)
  forward heel slip: 0,29 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
  forward flat slip: 0,18 (standard ≥ 0,18)
  forward heel slip: 0,15 (standard ≥ 0,13)

VARIANT



Darwin S3 SRC
DARWS30BN

Practical information

Weight of one shoe size 42: 586 g

CERTIFICATION N°OZO299-CPT005/21

Packaging

size 35 to 42	size 43 to 50
shoebox 315 x 220 x 125 mm	**shoebox** 355 x 220 x 130 mm
carton 635 x 445 x 325 mm	**carton** 660 x 450 x 360 mm
10 shoeboxes per carton	10 shoeboxes per carton

Gencods

35	3237154439357	**43**	3237154439432
36	3237154439364	**44**	3237154439449
37	3237154439371	**45**	3237154439456
38	3237154439388	**46**	3237154439463
39	3237154439395	**47**	3237154439470
40	3237154439401	**48**	3237154439487
41	3237154439418	**49**	3237154439494
42	3237154439425	**50**	3237154439500

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear						
SBP	●	●				
S1	●		A	E	Fo	
S1P	●	●	A	E	Fo	
S2	●		A	E	Fo	Wru
S3	●	●	A	E	Fo	Wru

● 200 J toe-cap: protection of the forefoot against impact and crushing.

● Anti-perforation insert 1100 N: foot protection against perforation.

- **A** Anti-static footwear
- **E** Shock absorption at the heel
- **Fo** Fuel oil-resistant outsole
- **Wru** Water penetration and water absorption resistant upper
- ESD Electrostatic discharge
- **Ci** Insulation against cold
- **Hi** Insulation against heat
- **Hro** Outsole resistance to hot contact
- **Wr** Water resistant
- **An** Ankle protection

- **SRA** Slip-resistance on ceramic floors with detergent
- **SRB** Slip-resistance on steel floors with glycerol
- **SRC** = **SRA** + **SRB**

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com

LEMAITRE
Safety since 1974

DON_LS 04 TDS 0057
update: 04/06/21

Member of SYNAMAP

afaq ISO 9001 Qualité AFNOR CERTIFICATION

afaq ISO 14001 Environnement AFNOR CERTIFICATION