Specifications

Eaton 271122

Catalog Number: 271122

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 1200A, N4-AE1200-NA



General specifications

Product Name
Eaton Moeller series NZM molded case circuit breaker electronic

Catalog Number
271122

Model Code
NZMN4-AE1200-NA

EAN
4015082711221

Product Length/Depth
401 mm

Product Height
207 mm

Product Width
210 mm

Product Weight
21 kg

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
RoHS conform

Certifications
IEC 60947-2
UL listed
CSA-C22.2 No. 5-09
UL (File No. E31593)
IEC/EN 60947
CE marking
UL/CSA
UL (Category Control Number DIVQ)
CSA (File No. 22086)
IEC
CSA certified
UL 489
Specially designed for North America

Powering Business Worldwide

Product specifications

Type

Circuit breaker

Special features

For AC-3 rated operational current with NZM4 the following applies: 400 V: max. 650 kW; 690 V: max. 600 kW (switching capacity, rated making and breaking capacity)
Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity Icn)
Rated current = rated uninterrupted current: 1200 A
Switches conform to UL/CSA as well as the IEC regulations. IEC switching performance values are contained on the rating plate.
Adjustable overload releases Ir
R.m.s. value measurement and “thermal memory”

Application

Branch circuits, feeder circuits
Use in unearthed supply systems at 525 V

Amperage Rating

1200 A

Voltage rating

690 V - 690 V

Circuit breaker frame type

NZM4

Resources

Brochures

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

eaton-digital-nzm-brochure-br013003en-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Characteristic curve

eaton-circuit-breaker-nzm-mccb-characteristic-curve-047.eps

Declarations of conformity

DA-DC-03_N4

Drawings

eaton-circuit-breaker-nzm-mccb-dimensions-022.eps

eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-003.eps

eCAD model

ETN.271122.edz

Installation instructions

eaton-circuit-breaker-basic-unit-nzmn4-il01210010z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CS-nzm4_3p

DA-CD-nzm4_3p

Technical data sheets

eaton-nzm-technical-information-sheet

Features

Motor drive optional

Protection unit

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM4

Pollution degree

3

Class

Distribution circuit protection

Mounting Method

Built-in device fixed built-in technique

Fixed

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Equipment heat dissipation, current-dependent

160 W

Utilization category

A (IEC/EN 60947-2)

Interrupt rating

50 kAIC at 400 Vac

Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

-40 °C

Low-voltage HBC fuse - max

2 x 630 A gG/gL

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110

Connection

Front screw

Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

Direction of incoming supply

As required

Electrical connection type of main circuit

Screw connection

Lifespan, mechanical

10000 operations

Overvoltage category

III

Rated operational current

1600 A (415 V AC-1, making and breaking capacity)

1200 A (690 V AC -1, making and breaking capacity)

1200 A (660-690 V AC-3, making and breaking capacity)

2000 A (380/400 V AC-1, making and breaking capacity)

Degree of protection (IP), front side

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate

Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

10 segments of 80 mm x 1 mm (2x) at rear-side width extension

NA: same as for IEC

Lifespan, electrical

1000 operations at 690 V AC-3

2000 operations at 400 V AC-3

2000 operations at 415 V AC-3

2000 operations at 690 V AC-1

3000 operations at 400 V AC-1

Functions

System and cable protection

Shock resistance

20 g (half-sinusoidal shock 20 ms)

Position of connection for main current circuit

Front side

Rated operational current for specified heat dissipation (In)

1200 A

Release system

Electronic release

Short-circuit total breaktime

< 25 ms (415 V); < 35 ms (> 415 V)

Rated short-time withstand current (t = 0.3 s)

19.2 kA

Rated short-time withstand current (t = 1 s)

19.2 kA

Short-circuit release non-delayed setting - max

14400 A

Short-circuit release non-delayed setting - min

2400 A

Terminal capacity (control cable)

14 mm² - 18 mm² (1x)
16 mm² - 18 mm² (2x)

Terminal capacity (copper busbar)

M10 at rear-side screw connection
Min. 25 mm x 5 mm direct at switch rear-side connection
Max. 50 mm x 10 mm (2x) direct at switch rear-side connection
Min. 25 mm x 5 mm at rear-side 1-hole module plate
Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate
50 mm x 10 mm (2x) at rear-side 2-hole module plate
Min. 60 mm x 10 mm at rear-side width extension
Max. 80 mm x 10 mm (2x) at rear-side width extension
NA: same as for IEC

Terminal capacity (copper stranded conductor/cable)

50 mm² - 240 mm² (4x) at 4-hole tunnel terminal
120 mm² - 185 mm² (1x) direct at switch rear-side connection
50 mm² - 185 mm² (4x) direct at switch rear-side connection
Min. 120 mm² - 300 mm² (1x) at rear-side 1-hole module plate
Max. 95 mm² - 300 mm² (2x) at rear-side 1-hole module plate
Min. 95 mm² - 185 mm² (2x) at rear-side 2-hole module plate
Max. 35 mm² - 185 mm² (4x) at rear-side 2-hole module plate
300 mm² (4x) at rear-side width extension
95 mm² - 240 mm² (6x) at rear-side width extension
NA: AWG 0- kcmil 500 (4x) at 4-hole tunnel terminal
NA: kcmil 250 - kcmil 350 (1x) direct at switch rear-side connection
NA: AWG 0 - kcmil 350 (4x) direct at switch rear-side connection
NA: min. kcmil 250 - kcmil 600 (1x) at rear-side 1-hole module plate
NA: max. AWG 3/0 - kcmil 600 (2x) at rear-side 1-hole module plate
NA: min. AWG 3/0 - kcmil 350 (2x) at rear-side 2-hole module plate
NA: max. AWG 2 - kcmil 350 (4x) at rear-side 2-hole module plate
NA: kcmil 600 (4x) at rear-side width extension
NA: AWG 3/0 - kcmil 500 (6x) at rear-side width extension

Terminal capacity (aluminum stranded conductor/cable)

Min. 185 mm² - 240 mm² (1x) at rear-side 1-hole module plate
Max. 70 mm² - 185 mm² (2x) at rear-side 1-hole module plate
50 mm² (4x) at rear-side 2-hole module plate

240 mm² (2x) at rear-side width extension

70 mm² - 240 mm² (6x) at rear-side width extension

NA: aluminum conductor not applicable

Handle type

Rocker lever

Short delay current setting (Isd) - max

0 A

Short delay current setting (Isd) - min

0 A

Instantaneous current setting (Ii) - max

14400 A

Instantaneous current setting (Ii) - min

2400 A

Number of operations per hour - max

60

Overload current setting (Ir) - max

1200 A

Overload current setting (Ir) - min

600 A

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 230 V, 50/60 Hz

37 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz

37 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz

26 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz

19 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

15 kA

Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz

105 kA

Rated short-circuit making capacity Icm at 440 V, 50/60 Hz

74 kA

Rated short-circuit making capacity Icm at 525 V, 50/60 Hz

53 kA

Rated short-circuit making capacity Icm at 690 V, 50/60 Hz

40 kA

Standard terminals

Screw connection,Optional:Tunnel terminal,Rear-side connection,Strip connection

Rated operating voltage Ue (UL) - max

600 V

Rated short-circuit making capacity Icm at 240 V, 50/60 Hz

105 kA

Rated impulse withstand voltage (Uimp) at auxiliary contacts

6000 V

Rated impulse withstand voltage (Uimp) at main contacts

8000 V

Rated insulation voltage (Ui)

1000 V AC

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia