Date: 25/04/2023

DPGS43.100...LM-F51 1 bar 2 x G 1/2 B

switchGAUGE DPGS43.100/160

Item number:	48658958
Quantity:	1 pcs.
Order code:	DPGS43.100.211ZZPZ-BG310Z-IFAB-LM-F51-ZZZIZ-ZZZZ 5UZZZ 33DDHZZISGZZ-ZZZZZZ11Z
Overview:	DPGS43.100...LM-F51 1 bar 2 x G 1/2 B magnetic snap action switch, model 821.11 plug sidewise Case: with pressure blowout disk Connection location: lower mount class 1.6 Ingress protection: IP 65 Case filling fluid: Silicon oil M50 max. static pressure: 25 bar Overpressure safety: 10 bar laminated safety glass Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F) Permissible ambient temperature: -20 … +60 °C Pressure Gauge Standard: International (standard Europe) *WIKA* Serial number *...*
Details:	switchGAUGE DPGS43.100/160 differential pressure gauge with switches, all welded construction Specifications according to data sheet: PV 27.05 and AC 08.01 switch: magnetic snap action switch, model 821 first switch operation: makes (1) second switch operation: makes (1) Electrical connection: plug sidewise Nominal size: 100 Scale range: 0...1 bar max. static pressure: 25 bar Overpressure safety: 10 bar Process connection: 2 x G 1/2 B Connection location: lower mount Liquid Damping (case filling): with Case: pressure blowout disk Pressure Gauge Standard: International (standard Europe) Accuracy class: class 1.6 Case material: Stainless steel 1.4301 Case surface: bare Case filling fluid: Silicon oil M50 Window: laminated safety glass

© 2023 - WIKA Instruments s.a.r.l.

Ingress protection: IP 65
Permissible medium temperature: -20 ... +100 °C (-4 ... +212 °F)
Permissible ambient temperature: -20 … +60 °C
Manufacturer logo: *WIKA*
serial number on dial: Serial number *...*

© 2023 - WIKA Instruments s.a.r.l.