Specifications

Eaton 266626

Catalog Number: 266626

Eaton Moeller series NZM - Molded Case Circuit Breaker. Main switch assembly kit, handle black, size 1



General specifications

Product Name
Eaton Moeller series NZM operating element

Catalog Number
266626

EAN
4015082666262

Product Length/Depth
190 mm

Product Height
90 mm

Product Width
90 mm

Product Weight
0.742 kg

Compliances
IEC
UL/CSA
RoHS conform

Certifications
IEC60947
UL listed
CSA-C22.2 No. 5-09
CSA (File No. 22086)
UL (Category Control Number DIHS)
CSA (Class No. 1437-01)
CE marking
UL489
UL (File No. E140305)
CSA certified

Powering Business Worldwide

Product specifications

Used with

N(S)1(-4)

PN1(-4)

NZM1(-4)

Type

Accessory Main switch assembly kit

Special features

External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch

Features

Lockable

With black door coupling rotary handle

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-nzm-mccb-dimensions-014.eps

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-010.eps

eaton-circuit-breaker-switch-nzm-mccb-3d-drawing-005.eps

Installation instructions

eaton-door-coupling-rotary-handle-nzm1-2-xt-il01203005z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

nzm1_xhb.dwg

nzm1_xhb.stp

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

External warning plate/marking plate in German/English
Black and yellow lightning symbol
Door coupling rotary handle with rotary drive
Extension shaft
NZM...-XV4 extension shaft
Padlock

Frame

NZM1

Suitable for

Switch disconnector

Power circuit breaker

Cover/door type

Door interlock can be modified such that it can be defeated from the outside using a screwdriver

After the door interlock is activated, must not be opened while on ON or TRIP. Must only be opened on OFF

Door interlock not defeated in the locked OFF position.

Door interlock can also be modified in I position

Door interlock can only be switched ON when the door is closed

Door interlock on OFF with max. 3 padlocks

Locking facility

Lockable on the 0 position on the handle using up to 3 padlocks

With door interlock

Can also be modified in I position

Degree of protection / NEMA enclosure type

IP66

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia