DATASHEET - IZMX-UVR230AD-1

Undervoltage release 220-240 VAC/DC

Part no.	**IZMX-UVR230AD-1**
	184162
EL Number (Norway)	**4398507**

General specifications

Product name	Eaton Moeller series IZMX/INX undervoltage release
Part no.	IZMX-UVR230AD-1
EAN	4015081783403
Product Length/Depth	150 millimetre
Product height	100 millimetre
Product width	100 millimetre
Product weight	0.091 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Undervoltage release

Delivery program

Type	Accessory
Special features	Cannot be combined with a second shunt release. Retrofitting kit Limited to 3/min due to the high pick-up current for 35 ms. Please note - the circuit-breaker's switching frequency = 60/h The retrofit kit includes the required SEC control cable terminals.
Suitable for	Power circuit breaker Off-load switch Overload relay Motor safety switch
Used with	INX16..., INX40... IZMX16..., IZMX40...

Technical Data - Electrical

Voltage type	AC/DC
Control voltage operating range	0.85 - 1.1 x Us 208 - 240 V AC (50/60 Hz) 208 - 250 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min	208 V
Rated control supply voltage (Us) at AC, 50 Hz - max	240 V
Rated control supply voltage (Us) at AC, 60 Hz - min	208 V
Rated control supply voltage (Us) at AC, 60 Hz - max	240 V
Rated control supply voltage (Us) at DC - min	220 V
Rated control supply voltage (Us) at DC - max	250 V
Current rating - max	0.028 A (maximum holding current)
Rated operational current	0.028 A (maximum holding current)
Power consumption	5 VA/W AC/DC
Pick-up power consumption at 35 ms - max	910 VA/W
Circuit breaker total switching time	50 ms (Us = 100%) (IZMX16…, INX16…) 40 ms (Us = 100%) (IZMX40…, INX40…)
Electric connection type	Flat plug-in connection

Technical Data - Mechanical

Number of actuation per minute - max	3
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0

Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C

Additional information

Accessory/spare part type			Remote switching

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip (ecl@ss13-27-37-04-17 [AKF015018])			
Rated control supply voltage AC 50 Hz		V	208 - 240
Rated control supply voltage AC 60 Hz		V	208 - 240
Rated control supply voltage DC		V	220 - 250
Voltage type for actuating			AC/DC
Type of electric connection			Flat plug-in connection
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Delayed			No
Suitable for power circuit breaker			Yes
Suitable for off-load switch			Yes
Suitable for motor safety switch			Yes
Suitable for overload relay			Yes

© 04/2023 by Eaton Industries GmbH