Specifications

Eaton 3-5016-003A

Catalog Number: 3-5016-003A

Eaton DM1 Variable frequency drive, 400 V AC, 3-phase, 31 A, 15 kW, IP20/NEMA0, 7-digital display assembly, Setpoint potentiometer, Brake chopper, FS4



General specifications

Product Name
Eaton DM1 Variable frequency drive

Catalog Number
3-5016-003A

EAN
4015081980963

Product Length/Depth
195 mm

Product Height
300 mm

Product Width
184 mm

Product Weight
6.3 kg

Certifications
CE
CSA-C22.2 No. 274-17
UkrSEPRO
IEC/EN 61800-3
IEC/EN 61800-5-1
IEC/EN61800-5
IEC/EN 61800-2
CE marking
UL File No.: E134360
Certified by UL for use in Canada
UL report applies to both US and Canada
C-Tick
EAC
UL 508C
UL Listed
CUL
UL
UL Category Control No.: NMMS, NMMS7
RoHS, ISO 9001

Powering Business Worldwide

General

Air volume capacity

98 m³/h

Communication interface

Ethernet IP, built in
Modbus TCP, built in
BACnet TCP
Modbus RTU, built in
CANopen®, optional
DeviceNet, optional
PROFIBUS, optional
BACnet MS/TP, built in
SmartWire-DT, optional

Connection to SmartWire-DT

Yes
In conjunction with DXG-NET-SWD SmartWire DT module

Degree of protection

IP20
NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Features

Temperature-controlled fan
Parameterization: Keypad
Parameterization: Power Xpert inControl
Parameterization: Fieldbus

Fitted with:

Setpoint potentiometer
7-digital display assembly
Internal DC link
IGBT inverter
Brake chopper
Breaking resistance
Control unit
PC connection

Frame size

FS4

Mounting position

Vertical

Climatic environmental conditions

Altitude

Max. 1000 m
Max. 3000 m
Max. 2000 m for Corner Grounded TN Systems
Above 1000 m with 1 % derating per 100 m

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Heat dissipation at current/speed

169 W at 25% current and 0% speed
213.8 W at 25% current and 50% speed
231.4 W at 100% current and 50% speed
236.5 W at 50% current and 90% speed
248.5 W at 50% current and 50% speed
335.8 W at 100% current and 0% speed
485.5 W at 100% current and 90% speed
497 W at 50% current and 0% speed

Input current ILN at 110% overload

43.7 A

Input current ILN at 150% overload

35.7 A

Mains current distortion

40 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Number of slots

1 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only

Safety function/level

STO (Safe Torque Off, SIL2, PLc Cat 2)

Shock resistance

0.75 mm (peak) at 10 - 57 Hz, max. 1 g at 57 - 150 Hz, according to EN 61800-5-1, EN 60068-2-6: 10 - 150 Hz

Suitable for

Branch circuits, (UL/CSA)

Mains voltage - min

380 V

Mains voltage - max

480 V

Operating mode

Sensorless vector control (SLV)
Speed control with slip compensation
U/f control
Torque regulation
PM motors

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

500 V AC, 3-phase
400 V AC, 3-phase
480 V AC, 3-phase

Overload current IL at 110% overload

41.8 A

Overload current IL at 150% overload

46.5 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

38 A

Rated operational current (Ie) at 150% overload

31 A

Rated operational power at 380/400 V, 50 Hz, 110% overload

18.5 kW

Rated operational power at 380/400 V, 50 Hz, 3-phase

15 kW

Rated operational power at 500 V, 50 Hz, 3-phase

18.5 kW

Rated operational power at 500 V, 50 Hz, 3-phase, 110% overload

22 kW

Rated operational voltage

500 V AC, 3-phase
480 V AC, 3-phase
400 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

50 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

3.6 kHz, 1 - 16 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

500 V

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

36 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

29.3 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

34 A

Assigned motor current IM at 500 V, 50 Hz, 110% overload

33 A

Assigned motor current IM at 500 V, 50 Hz, 150% overload

28.9 A

Assigned motor power at 460/480 V, 60 Hz

20 HP

Assigned motor power at 460/480 V, 60 Hz, 110% overload

25 HP

Braking function

Braking resistance

17 Ω

Braking torque

Max. 100 % of rated operational current Ie with external braking resistor - Main circuit
Max. 30 % MN, Standard - Main circuit
Adjustable to 150 %, DC - Main circuit

Switch-on threshold for the braking transistor

800 VDC

Control circuit

Number of inputs (analog)

1

Number of inputs (digital)

4

Number of outputs (analog)

1

Number of relay outputs

2 (parameterizable, 1 changeover contact and 1 N/O, 3 A (240 V

Design verification

Equipment heat dissipation, current-dependent Pvid

393.8 W

Rated operational current for specified heat dissipation (In)

38 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

AC) / 3 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 100 mA options incl.)

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise

calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Application notes

Electromagnetic compatibility (EMC)

Dual Rating What exactly does that mean?

Connecting drives to generator supplies

Brochures

eaton-powerxl-dm1-variable-frequency-drives-brochure-br040016en-en-us.pdf

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004864.pdf

DA-DC-00004643.pdf

Installation instructions

DM1 IL PUB 53-675 TBG Change Request 12-24-21 Final (300 DPI).pdf

Installation videos

PowerXL Variable Frequency Drive DM1

Manuals and user guides

MN040060EN

MN040049EN

mCAD model

fs4_89_1315.dwg

fs4-89-1315.stp

Multimedia

PowerXL DM1 Variable Frequency Drive - Setup via WebUI

PowerXL DM1 Variable Frequency Drive - Setup via Software

PowerXL DM1 Variable Frequency Drive - PowerXpert inControl with Bluetooth

PowerXL DM1 Variable Frequency Drive - Configuration with keypad

PowerXL DM1 Variable Frequency Drive - Establishing a Modbus TCP connection with software Power Xper

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Sales notes

eaton-powerxl-dm1-variable-frequency-drives-flyer-fl040006en-en-us.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia