DATASHEET - BBA0L-32

Busbar adapter, 45 mm, 32 A, DIN rail: 2

Part no. **BBA0L-32**
142527

Powering Business Worldwide

General specifications	
Product name	Eaton Moeller® series BBA Accessory Busbar adapter
Part no.	BBA0L-32
EAN	4015081392568
Product Length/Depth	260 millimetre
Product height	73 millimetre
Product width	45 millimetre
Product weight	0.3 kilogram
Compliances	Contact Manufacturer
Certifications	CE
Product Tradename	BBA
Product Type	Accessory
Product Sub Type	Busbar adapter
Delivery program	
Type	Busbar adapter SASY Busbar system 60 mm
Nominal current	32 A
Technical Data - Electrical	
Voltage rating at AC	690 V
Rated operation current (Ie)	32 A
Electric connection type	3 conductors AWG 10
Technical Data - Mechanical	
Rail width	20 mm
Number of DIN rails	2
Busbar distance	60 mm
Busbar thickness - min	5 mm
Busbar thickness - max	10 mm
Adapter width	45 mm
Design verification as per IEC/EN 61439 - technical data	
Equipment heat dissipation, current-dependent Pvid	2.4 W
Static heat dissipation, non-current-dependent Pvs	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.

10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information			
Special features			Terminal capacity: 6 mm^2 (AWG 10)

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss13-27-37-03-04 [ACN951016])

Mounting rail armament			2 mounting rails
Type of electric connection			3 conductors AWG 10
Rated current In		A	32
Min. busbar thickness		mm	5
Max. busbar thickness		mm	10
Width of the adapter		mm	45
Rail width		mm	20
Busbar distance		mm	60

© 04/2023 by Eaton Industries GmbH