JALARTIC SAS
00J0257

Softane™ Tradition

S3 CI SRC
EN ISO 20345:2011
36 to 48

AP23
PLEINE FLEUR



- **Full grain AP 23 leather**
- **Softane™ dual-density sole**
- **Steel toe cap / Steel midsole**
- **Antistatic**

- Natural-coloured, fur-lined boot with 2 leather side tabs for rapid pull-on.
- Isothermal lining for better protection against cold.
- Boot in full grain leather **AP 23**, water and oil resistant : a Jallatte exclusive
  - **10 to 15% thicker** (2.4mm) than most leathers usually used in safety shoe manufacture.
  - **Upper resistance to water penetration:** to European standard level or more.
- Flat binding at top of quarters.
- Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
- Perforated steel toe-cap (patented) – 200 J.
- Puncture-resistant stainless steel midsole.
- Heel stiffener to reinforce the heel seat.

- Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic/lubricant : water and detergent
On flat 0,58 (>0,32) – On the heel 0,54 (>0,28)

SRB Test ground steel/lubricant : glycerine
On flat 0,37 (>0,18) – On the heel: 0,14 (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm^3
- ✓ Heel schock absorption 29 Joules.

Weight	Gross weight (42): 1760 g / Net weight (42): 1440 g
Size	36 to 48
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345



Jallatte®
www.jallatte.com

Non contractual
Copyright JALLATTE
Limited distribution