Spec Sheet

TILSATEC®

53 7191

Lightweight cut level **F** sandy foam nitrile palm coated glove with leather palm and thumb reinforcement



Code	53-7191
Description	Lightweight cut level F sandy foam nitrile palm coated glove with leather palm and thumb reinforcement
Gauge	13gg
Colour	Grey liner / Grey leather
Cuff Style	Knit wrist
Length	220-270mm
Sizes	7/S - 11/2XL
Packaging	12 pairs/polybag 72 pairs/carton

Features & Benefits

- EN388: 2016+A1:2018 level F cut resistance
- New Rhino Yarn® composition using lighter, finer steel
- EN407:2020 contact heat level 1
- Leather palm combined with foam nitrile coating delivers incredible robustness and handling comfort
- Foam nitrile palm coating allows breathability and prevents oil ingress to hand
- Leather reinforcement to thumb crotch

Applications / Industries

- Assembly
- Automotive industry
- Metal fabrication / stamping
- Glass Manufacturing
- White goods manufacturing

Performance

EN388: 2016 — 4 X 4 3 F

EN407: 2020 — X 1 X X X X

CE UKCA

Sizing Cuff Colours

Size	6 X-Small	7 Small	8 Medium	9 Large	10 X-Large	11 2X-Large
Colour coded cuff						

RHINOYARN®

Made with Tilsatec Rhino Yarn® technology. Produced in the UK and developed by Tilsatec's specialist team of yarn technologists to deliver the optimum in performance and comfort.

tilsatec.com/products/lightweight-cut-level-f-foam-nitrile-coated-glove-thumb-reinforcement-53-7191

Tilsatec | +44 (0)1924 375742 | info@tilsatec.com | **www.tilsatec.com**

For businesses who want expertise they can rely on to keep their people safe, Tilsatec offer high performance hand and arm protection. We manufacture our own proprietary cut resistant yarn - the primary source of mechanical protection, on site in the UK. This means we can deliver maximum performance in every fibre of what we do. Because when our gloves perform at their best, your people can perform at their best.