Handling protection

ULTRANE 541

Comfort, suppleness and high dexterity without any compromise on breathability and durability



RESICOMFORT TECHNOLOGY

EN388
4121A

EN407
X1XXXX

CATEGORY 2
CE

DEXTERITY
EN ISO 21420:
5/5

OEKO TEX®
STANDARD 100
CQ 979/2
IFTH

SPECIFIC ADVANTAGES

Comfort
- Comfort: high suppleness and flexibility, dexterity at fingertips, proven breathability

Durability
- Resistance: Extended use guaranteed by our exclusive process ResiComfort, coating provides resistance to friction

Skin protection
- Free of harmful substances: OEKO-TEX® STANDARD 100, DMF Free
- Dermatologically approved

Guaranteed quality
- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability
- Washable 1 time at 40°C

INDUSTRIES
- Automotive/mechanical industry
- Food industry
- Other industries
- Transport, logistics
- Manufacturing
- Industrial maintenance
- Installation of industrial equipments
- White appliance

APPLICATIONS
- Food handling
- Mechanical maintenance
- Assembly of small parts
- Automotive assembly
- Fitting small screws and fasteners
- Precision assembly
- Precision mechanical work
- Packaging
- Warehousing and receipt of goods

Edit 18/03/2024

Handling protection

ULTRANE 541

LEGENDS

EN388 MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

4	1	2	1	A	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN407 THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)

X	1	X	X	X	X
0-4	0-4	0-4	0-4	0-4	0-4

- 0-4: Resistance to large quantities of molten metal
- 0-4: Small splashes of molten metal
- 0-4: Radiant heat resistant
- 0-4: Convective heat resistance
- 0-4: Contact heat resistance
- 1: Limited flame spread



FOOD CONTACT
French decree of 05/08/2020

PRODUCT DETAILS

Interior finish	Seamless textile support
Gauge	15
Exterior finish	Reinforced grip
Material	Nitrile foam sandy
Cuff characteristic	Knitted Cuff
Colour.s	Black
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.0E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.1E+12 Ω

LOGISTIC DETAILS

Packaging	12 pairs/bag 96 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/19/1047 update 02-16/02/2022
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

Edit 18/03/2024