




jalas® EXALTER 9968 GTX

EN ISO 20345:2011 S3, SRC, WR, HRO ASTM F2413-18 M/I/C SD 35 PR

Learn more

A LOW-CUT SAFETY SHOE, NOW WITH GORE-TEX

A light, comfortable, safety shoe with side-mounted BOA®. Waterproof due to GORE-TEX. Its Microfiber upper and sock-like construction provides great comfort and fit and has anti-static properties. The nitrile outer sole is heat and oil resistant for outstanding grip. It features also our JALAS® aluminium toe cap, plasma-treated textile puncture protection and double impact protection zones in PORON® XRD®.

CHARACTERISTICS

- Highest level of protection
- Excellent grip
- Perfect fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Waterproof
- Specially designed details
- Double shock absorption zones
- Polstered shaft edge
- Ventilating insole
- BOA® Fit System
- Conforms with IEC 61340-5-1 (ESD)
- Ergonomically shaped
- Quick-tie
- Stabilizator
- Soft
- Free from animal-derived materials
- GORE-TEX Extended Comfort Footwear technology

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, nail penetration, sprain injuries, antistatic, wet feet

PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, wet environments, moist environments

SPECIFICATION

TYPE Safety footwear, Low shoes
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Regular
COLLECTION Exalter
UPPER MATERIAL Microfiber, Textile
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyamide
INSOLE FX3 Supreme
INNERSOLE MATERIAL Textile, Soft EVA, Rigid EVA, Polyester-based conductive thread, Neo foam, Poron® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING BOA® Fit System
COLOUR Black
NET WEIGHT, (SIZE 42) 1.41 kg

COMPLIANCE

CE Cat. II

EN ISO 20345:2011
S3, SRC, WR, HRO

EAC TP TC 019:2011

ASTM F2413-18
M/I/C
SD 35 PR

ÖNORM Z 1259

DGUV 112-191

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- ESD
- Aluminium toecap
- Oil-resistant outsole
- Heat-resistant outsole
- Waterproof
- Nail protection in plasma-treated composite (PTC) textile
- Stabilizator

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1½	2½	3½	9968-34	6408487533662
35	2	3½	4	9968-35	6408487533709
36	3	4	5	9968-36	6408487533747
37	4	5	6	9968-37	6408487533785
38	5	5½	6½	9968-38	6408487533822
39	6	6½	7½	9968-39	6408487533860
40	6½	7½	8½	9968-40	6408487533907
41	7	8	9	9968-41	6408487533945
42	8	9	10	9968-42	6408487533983
43	9	9½	11	9968-43	6408487534027
44	10	10½	11½	9968-44	6408487534065
45	10½	11	12½	9968-45	6408487534102
46	11	12	13	9968-46	6408487534140
47	12	13	14	9968-47	6408487534188

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.