BJ ROUND BRAID WITH CRIMPED LUGS



CERTIFICATIONS

RoHS

FEATURES

- Ready to use out of the box, saving installation time and labor
- Allows for bending very close to the contact area
- RoHS compliant

SPECIFICATIONS

Material: Copper

Finish: Tinned

Working Temperature: 221 °F Max

Table 1/2


Catalog Number	Article Number	Ampacity	Cross Section	Length (L)	Wire Diameter	Hole Size (HS)
BJ10-300S	556920	75A	19.74	11.81"	0.01"	0.26"
BJ6-150S	556900	45A	11.84	5.91"	0.01"	0.26"
BJ6-200S	556910	45A	11.84	7.87"	0.01"	0.26"

Table 2/2

Catalog Number	Article Number	Unit Weight

BJ10-300S	556920	0.07 lb
BJ6-150S	556900	0.02 lb
BJ6-200S	556910	0.03 lb

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.