




# TEGERA® 465A

Learn more

## FOR GREAT DEXTERITY IN PRECISION WORK

Thin 18 gg knitted cut protection glove (D) with great dexterity for precision work. Touch screen function so you can use your smartphone with the gloves on. Breathable back for extra comfort and high cut protection thanks to the CRF® Technology in combination with stainless steel fibre yarn. Reinforced thumb crotch for improved longevity. PU palm dipped with smooth finish provides a good grip on dry to slight moist surfaces.

### CHARACTERISTICS

- High level of protection
- Extra comfortable
- Good grip
- Extremely good fingertip sensitivity
- Extra flexible

### FUNCTIONS

- For touchscreen
- Thin
- Reinforcement between index finger and thumb

CRF®



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*

## PREVENTS RISK OF
Cut injuries, blisters, grazes, scratches, lacerations, contact with dirt

## PRIMARY ENVIRONMENTS OF USE
Cut risk environments, dry environments, moist environments, dirty environments

## PRIMARY AREAS OF USE
Assembly, sheet-metal work, engineering, transport work, warehouse work, metalwork

## PRIMARY INDUSTRIES OF USE
Rubber and plastic, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, logistics

## TYPE OF WORK
Light weight

## SPECIFICATION
**TYPE** Cut resistant gloves
**CATEGORY** Cat. II
**LINING MATERIAL** 18 gg, CRF® Technology, HPPE, Nylon, Spandex, Stainless steel fibre yarn
**LENGTH** 215-280 mm
**DEXTERITY** 5
**GRIP DESIGN** Smooth finish
**COLOUR** Grey
**PAIRS PER: BUNDLE/CARTON** 6/60
**DISPLAY TYPE** Bulk pack
**DIPPING** Palm-dipped
**DIPPING MATERIAL** PU
**CUFF STYLE** Knitwrist cuff
**CUFF MATERIAL** Textile
**CUT RESISTANCE (EN ISO 13997)** Cut resistance level D
**CUT RESISTANCE (EN ISO 13997) TDM:** 18 N
**INNER MATERIAL SPECIFICATION** HPPE (High performance polyethylene), Stainless steel fibre yarn, Nylon, Polyester, Elastane
**OUTER MATERIAL SPECIFICATION** Polyurethane

## COMPLIANCE
CE Cat. II
TP TC 019:2011

UKCA Cat. II
EN 388:2016+A1:2018
3X42D

EAC
EN ISO 21420:2020

ANSI A4 CUT

ANSI 3 ABR

OEKO-TEX® STANDARD 100 SE 14-214 RISE www.oeko-tex.com

## FEATURES
For touchscreen

Cut protection

| SIZE | | ARTICLE NUMBER | EAN |
|---|---|---|---|
| 5 | XXS | 465A-5 | 7340118427737 |
| 6 | XS | 465A-6 | 7340118428130 |
| 7 | S | 465A-7 | 7340118428536 |
| 8 | M | 465A-8 | 7340118428932 |
| 9 | L | 465A-9 | 7340118429335 |
| 10 | XL | 465A-10 | 7340118429731 |
| 11 | XXL | 465A-11 | 7340118430133 |
| 12 | 3XL | 465A-12 | 7340118430539 |

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com



*All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.*