BS Street Lighting Fuses gG 415VAC

LOW VOLTAGE IEC FUSES

BS FUSE-LINKS



FEATURES & BENEFITS

- Reliability
- Immediate isolation
- Ensures fire safety

APPLICATIONS

- Street lighting

STANDARDS

- IEC 60269-1 & -2
- BS 88-1 & 2

Mersen's range of street lighting fuses is carefully designed to respond effectively and reliably to the diverse needs encountered in street lighting. This diverse range aims to provide optimum protection and secure management of the power supply, guaranteeing users peace of mind in the face of everyday electrical challenges.

TECHNICAL DATA OVERVIEW

Current Range In	2 to 32 A
Rated voltage AC (IEC)	415 V
Breaking capacity AC	16,5 to 33 kA
Speed/Characteristic	gG
Body Material	Ceramic
BS type	BMD

©2024 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

PRODUCT RANGE



BMD42V6

BS Street Lighting Fuses gG 415VAC - BMD

Catalog number	Item number	Rated voltage AC (IEC)	Rated current I_n	Pre-arcing I^2t	Clearing I^2t at Rated Voltage	Rated breaking capacity AC	Power dissipation at I_n	Package
BMD42V2	V1036973	415 V	2 A	1 A^2s	3.5 A^2s	80 kA	1.17 W	10
BMD42V4	W1036974	415 V	4 A	8 A^2s	27 A^2s	80 kA	1.48 W	10
BMD42V6	X1036975	415 V	6 A	22 A^2s	77 A^2s	80 kA	1.54 W	10
BMD42V8	P1065074	415 V	8 A	13 A^2s	55 A^2s	80 kA	1.01 W	10
BMD42V10	Y1036976	415 V	10 A	27 A^2s	113 A^2s	80 kA	1.42 W	10
BMD42V16	Z1036977	415 V	16 A	107 A^2s	451 A^2s	80 kA	1.43 W	10
BMD42V20	A1036978	415 V	20 A	241 A^2s	1015 A^2s	80 kA	1.52 W	10
BMD42V25	B1036979	415 V	25 A	428 A^2s	1805 A^2s	80 kA	2.28 W	10
BMD42V32	C1036980	415 V	32 A	668 A^2s	2821 A^2s	80 kA	2.64 W	10

©2024 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

TIME CURRENT CHARACTERISTIC CURVES

gG curve - 2 to 32 A - 415VAC BMD



©2024 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

CUT-OFF CURRENT CHARACTERISTIC

gG curve - 2 to 32 A - 415VAC BMD



©2024 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.

DIMENSIONS

BMD - 2 to 32 A - 415VAC



Dimensions in mm

Fuse Type	Current rating (A)	A MAX	B MAX	C MAX	A	B	C
BMD	2, 4, 6, 8, 10, 16, 20, 25, 32	24.4	12.8	8.5	29	8	12,7

©2024 Mersen. All rights reserved. Mersen reserves the right to change, adapt, limit or discontinue its products. Therefore the data provided herein are for information only and are not contractually binding. To ensure that Mersen provides the best solution to your needs, please contact and provide Mersen with all relevant technical specifications and conditions.