Garant CEE IP 44 industrial/construction site cable reel 30 m H07RN-F 5G2.5

For use on construction sites in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.









MADE IN GERMANY

cable pilot

3 YEARS MANUFACTURER GUARANTEE

DGUV-I 203-006 K2

VDE 0100 Teil 704

EN 61316

SPECIAL ROBUST

IP 44

Product number	1238010
EAN	4007123687497

DESCRIPTION

- In accordance with EN 61316.
- Reel body made of special plastic on galvanised support frame.
- Innovative „cablepilot“ carrying handle for perfect cable routing. Swings on both sides for easy carrying and hanging.
- With twist handle for convenient retraction.
- RN cable is approved for difficult building conditions in accordance with VDE 0100 Part 704.
- CEE plug 400 V/16 A,
  – 2 CEE socket 400 V/16 A,
  – 1 splash-proof 230 V socket outlet with earthing contact.
- With 3-pole safety cut-out and overheating protection.
- With reel brake.
- Category 2 equipment (K2 DGUV 203-005): For use in harsh operating conditions with high mechanical, physical and chemical influences.

Garant CEE IP 44 industrial/construction site cable reel 30 m H07RN-F 5G2.5

For use on construction sites in accordance with DGUV 203-006 (formerly BGI 608) and permanent outdoor use IP 44.



Product number	1238010
EAN	4007123687497

TECHNICAL DATA

Cable quality	Rubber-Neoprene	**Plug system socket**	Type F (Protective contact)
Cable length	30 m	**Plug system plug**	CEE 16 A 3P+N+E (5p) 400 V
Cable designation	H07RN-F 5G2,5	**Max. current carrying capacity**	16 A
Cable colour	black	**Nominal input voltage**	230 V/400 V
Reel diameter	320 mm	**Degree of protection (IP)**	IP44
Plug system CEE socket	CEE 2x 16 A 3P+N+E (5p) 400 V		

PACKAGING, DIMENSIONS AND WEIGHTS

UP	1	**Weight of product (including packaging)**	12.23 kg
Weight of product (without packaging)	12.23 kg	**Dimension LxWxH (incl. packing)**	25 cm x 33.5 cm x 43 cm
Dimension LxWxH (without packing)	24 cm x 32 cm x 42 cm		

SCOPE OF DELIVERY

Garant CEE IP44 industrial/construction site cable reel