J-ENERGY

# JY204
# JALTONIC SAS ESD

**S3 CI SRC**
**EN ISO 20345:2011**
**38 to 48**




- **Water-repellent full-grain leather** / textile
- **J-ENERGY sole Infinergy ® de BASF**
- **Aluminum safety toe cap and midsole no metallic**
- **Antistatic**

- Low safety shoe of urban sport type designed with **anti-fatigue technology**.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather and déperlant textiles upper. **TPU insert** built-in to the laces, ensuring an effective heel grip, enhanced alignment of the foot in the shoe and protection against any sprains.
- Micro-aerated mesh lining, smooth appearance, 3 layer structure combining a textile mesh, a foam and a reinforcing grid. High mechanical strength (abrasion and tearing) and fast drying.
- Vamp lining in non-woven fabric, resists scuffing and acid perspiration.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on five pairs of eyelets. Leather lace-loop keeps tongue in place as you walk. Black laces : 110 cm.
- POLYJAL footbed single-block structure made of soft polyurethane and textile, anatomical, perforated in the font part and with heel schock absorbers.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- PREM-Alu tip in aluminium resisting an impact of an energy of 200 joules.
- New manufacturing process : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
  **100% composite** materials : lighter than steel, non-magnetic, non-conductive of heat or cold.
- Heel stiffener to reinforce the heel seat.
- Innovative **J-energy** sole in bi-ingredient PU / and **BASF Infinergy® E-TPU** (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 55**% of the energy accumulated** while walking in order to reduce fatigue and to prevent RSIs to the legs.

**Slip resistance tests results**
EN Standard : EN ISO 20345 : 2011
**Requirement SRC** (SRA+SRB)

**SRA** Test ground : ceramic / lubricant : water and detergent
On flat **0,62** (>0,32) – On the heel **0,48** (>0,28)

**SRB** Test ground steel/lubricant : glycerine
On flat **0,23** (>0,18) – On the heel **0,19** (>0,13)

- Outsole in Polyuréthane.
- E-TPU insert at low density of 0.25.
  - As elastic as rubber but lighter.
  - High resistance to abrasion and stretching.
  - Good chemical resistance.
  - Long-term durability in a wide temperature range.
  - **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return**

| | | | | |
|---|---|---|---|---|
| Weight | Gross weight (42) : 1390 g / Net weight (42) : 1182 g | | | |
| Size | 38 to 39 | 40 | 41 to 45 | 46 to 48 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box shoes (mm) | 306 x 192 x 114 | | 340 x 210 x 133 | |
| Cartons (mm) | 585 x 199 x 315 | 585 x 395 x 315 | 680 x 425 x 350 | 680 x 215 x 350 |



Jallatte®
www.jallatte.com

Non contractual document
Copyright JALLATTE
Limited distribution

10/04/2017