Balance reels with steel cables

F Series: 25-105 kg load capacity



Technical characteristics

Temperature: +5°C to +60°C

Construction: Body : Aluminium
Cable : Stainless steel

Applications: Mounting Decks, Assembling, Packaging

- Gnooved knob adjusts spring tension
- Brake stops loads from falling if spring suddenly breaks
- Swivel safety hook for ceiling mounting
- Safety cable for ceiling mounting
- Cable wound in tapered drum rotating on ball bearings



A (mm)	B (mm)	Length (cable (m)	Min.Load (kg)	Max.load (kg)	Weight (kg)	Parts Numbers
636	220	2	25	30	11.3	**BAL 250300F**
636	220	2	30	35	11.3	**BAL 300350F**
636	220	2	35	45	12.21	**BAL 350450F**
636	220	2	45	55	12.21	**BAL 450550F**
636	220	2	55	65	13.06	**BAL 550650F**
636	220	2	65	75	13.86	**BAL 650750F**
636	220	2	75	90	16.84	**BAL 750900F**
636	220	2	90	105	17.77	**BAL 9001050F**

PREVOST UK - G, Tower Business Park, Commercial Rd, Darwen BB3 0FJ - United Kingdom
Tel. : (+44) 0844 800 2788 - Fax : (+44) 0844 800 2789 - E-mail : sales@prevost-ltd.co.uk - www.prevost.eu International = PREVOST SAS - - C.S. 90208 - 74942 ANNECY-LE-VIEUX CEDEX - France Tel. : +33 (4)50 64 04 45 - Fax : +33 (0)4 50 64 00 10 - E-mail : sales@prevost.eu- www.prevost.eu

This document is non-contractual. PREVOST reserves the right to modify the features of its range without prior notice.