Specifications

Eaton 265244



Catalog Number: 265244

Eaton Distribution parts. Restarting device, 24-48VDC, 4HP

General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	265244
EAN	**Product Length/Depth**
4015082652449	80 mm
Product Height	**Product Width**
77.3 mm	88.4 mm
Product Weight	**Compliances**
0.247 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Restarting device
Accessory for residual current circuit breaker
Accessory
Accessory for miniature circuit breaker

Type

Accessory
Accessory for miniature
circuit breaker
Accessory for residual
current circuit breaker

Special features

Z-FW… (Test module (0.5 space unit) for remote testing of residual current devices)

Application

Switchgear for industrial and advanced commercial applications

Accessory/spare part type

Restarting device

Degree of protection

IP40

Frame

Standard front dimension: 45 mm

Equipment heat dissipation, current-dependent

0 W

Mounting method

For fitting on right to: CLS6, PFIM, PFHM-4p, dRCM, Z-A40, PFR, Z-MS
Quick attachment with 2 latch positions on top-hat rail IEC/EN 60715

Additional equipment required

Monitoring unit with automatic reclosing

Terminal protection

Protection against electric shock to BGV A3, ÖVE-EN 6

Terminal type

Lift terminals

Ambient operating temperature - max

40 °C

Resources

Declarations of conformity

DA-DC-03_Z-FW-LP

Drawings

eaton-dimensions-mas-fw-lp.jpg

Installation instructions

IL019014ZU

mCAD model

z_fw_lp.dwg

z_fw_lp.stp

Wiring diagrams

FW_LPD

Ambient operating temperature - min

-25 °C

Assembly width

4 TE

Enclosure width

80 mm

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

0 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

0

Number of poles at main contact unit - max

0

Number of switches (fault signal)

0

Rated operational current for specified heat dissipation (In)

0 A

Voltage type

DC

Functions

Automatic restart

With auto test for earth leakage function

Remote drive

Device fitting

Universal

Mounting width

70 mm

Function selector

Automatic 5 x, OFF/RESET

Rated operational voltage (Ue) - max

48 V

Rated switch current

0 A

Relay output for alarm

5 A

Static heat dissipation, non-current-dependent

0.8 W

Suitable for current of main contact unit - max

0 A

Voltage rating at DC

24 V DC - 48 V DC

Terminal capacity (cable)

2.5 mm² (1x)

1.5 mm² (2x)

Terminal capacity (solid wire)

1 mm² - 2.5 mm²

1.5 mm² (2x)

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia