Date: 11/04/2023

PSD-4-ECO ; 0...250 bar gauge; one switching output (PNP) + 4...20 mA

PSD-4-ECO ; 0...250 bar gauge; one switching output (PNP) + 4...20 mA

Item number:	48784486
Quantity:	1 pcs.
Order code:	PSD-4-ECO-D-BG525-013Z-2O1CZZS-ULZZ- W1011P4E-ZZOSW-GSFJ
Overview:	PSD-4-ECO ; 0...250 bar gauge; one switching output (PNP) + 4...20 mA OEM Pressure Switch with Display Output signal: one switching output (PNP) + 4...20 mA IO-Link: without Power supply: 15 ... 32 V DC Measuring range: 0...250 bar gauge Process connection: G1/4 B EN 837 Sealing: without Permissible medium temperature: -25...+85°C Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1,S+=2, U-=3, SP1 =4 Overload Safety: 2 x Accuracy: 1.0% of span Approvals: cULus Type of packaging: single packaging Specifications according to data sheet: PE 81.69
Details:	PSD-4-ECO ; 0...250 bar gauge; one switching output (PNP) + 4...20 mA OEM Pressure Switch with Display Output signal: one switching output (PNP) + 4...20 mA IO-Link: without Power supply: 15 ... 32 V DC Measuring range: 0...250 bar gauge Process connection: G1/4 B EN 837 Sealing: without Permissible medium temperature: -25...+85°C Electrical connection: circular connector M12x1, 4-pin pin assignment: U+=1,S+=2, U-=3, SP1 =4 Overload Safety: 2 x Accuracy: 1.0% of span Approvals: cULus Type of packaging: single packaging Specifications according to data sheet: PE 81.69

© 2023 - WIKA Instruments s.a.r.l.