KLEENGUARD®

Technical Data Sheet

Product Data Sheet for KleenGuard® G60 Endurapro™ Level 3 Cut Resistant Gloves - Ambidextrous / Grey & Purple

Product Information

Customer Facing Code	97430 - 97434
Description	KleenGuard® G60 Endurapro™ Level 3 Cut Resistant Gloves - Ambidextrous / Grey & Purple
PDS Reference	13/04/2022
Status	On Sale

Packaging Configuration

Case Contents	97430: 1 Bag x 12 Pairs = 24 Gloves 97431: 1 Bag x 12 Pairs = 24 Gloves 97432: 1 Bag x 12 Pairs = 24 Gloves 97433: 1 Bag x 12 Pairs = 24 Gloves 97434: 1 Bag x 12 Pairs = 24 Gloves
Outer Pack Material	Corrugated

Packaging and Palletisation

Code/Size	ITF Barcode	EAN Barcode	Case LWH (cm)	Net/Gross Weight (kg)	Pallet Type	Pallet LWH (m)	Cases per Pallet	Inner Gross Weight (Kg)
97430-7	10036000974307		28.3 x 14.2 x 14.5	0.624/0.81	E5	1.20 x 0.80 x 1.31	20 x 8 =160	0.76
97431-8	10036000974314		29.5 x 15.2 x 16.2	0.684/0.88	E5	1.20 x 0.80 x 1.45	20 x 8 =160	0.70
97432-9	10036000974321		29.5 x 15.2 x 16.2	0.744/0.94	E5	1.20 x 0.80 x 1.45	20 x 8 =160	0.80
97433-10	10036000974338		29.5 x 15.2 x 16.2	0.804/1	E5	1.20 x 0.80 x 1.45	20 x 8 =160	0.90
97434-11	10036000974345		29.4 x 15.2 x 16.2	0.864/1.06	E5	1.20 x 0.80 x 1.45	20 x 8 =160	0.90

Product Description

KleenGuard® G60 Endurapro™ Dual Grip Purple Nitrile™ Gloves are part of a range of cost effective, durable gloves and sleeves for processes where there is a cutting or laceration risk to workers' hands and arms. These gloves provide PPE category 2 classification, high level 3 cut resistance and level 4 abrasion resistance, offering superior protection against cuts and gashes. Using HPPE fibers, this product also conforms to EN420 Minimum Cuff Length providing protection to wrist areas yet still offering user breathability as the yarn is designed to transmit heat away. The unique design with nitrile dots on the palm of the gloves and nitrile coated finger tips offers excellent grip where needed, without compromising dexterity. Perfect for use in metal fabrication, glass handing and automotive assembly. Latex-free and ambidextrous, these gloves come in five sizes with colour-coded cuffs. For other sizes see products: 97430, 97431, 97432, 97433 and 97434. 1 bag x 24 ambidextrous, grey & purple gloves, 10, (24 total)Kimberly-Clark Professional™ personal protective equipment is only intended for occupational workplace use and must be used in compliance with all applicable health and safety laws and standards in addition to all user instructions, warnings and limitations accompanying each product. It is essential all product user instructions and laws and regulations on the use of each product be followed in order for the product to help protect the wearer. Misuse of personal protective equipment may result in injury, sickness, or death. For correct product selection and use, individuals should seek occupational health and safety advice from a suitably competent person. This product is suitable for sale in the EU.Individual units should not be sold separately.

Product Data Sheet for KleenGuard® G60 Endurapro™ Level 3 Cut Resistant Gloves - Ambidextrous / Grey & Purple

Features and Benefits

Features	Benefits
Ambidextrous	Unique cost in use for increased efficiency and productivity
Conforms to EN420 - minimum cuff length	Enhanced protection to wrist area
Highest abrasion resistance	Enhanced efficiency and productivity
Nitrile coated fingertips	Grip and breathability at the same time
Nitrile dots on palm	Excellent grip
Suitable for washing	Efficient use

Product Configuration

Sterile	No	**Latex Free**	Yes
Main Protection Type	Cut	**Application**	Industrial
Ambidextrous	Yes	**Powdered**	No
Material	Other	**Coated**	No
Liner	No	**Coating**	Nitrile
Colour	Grey & Purple	**Chlorinated**	No
Gauge	13	**Length**	160 - 240 mm

International Standards and Symbols

Solution

Safer Workplace

We know staff safety is your top priority. You can rely on our solutions to protect them, their environment and your important work.



Productive Workplace

The success of your business hinges on your work efficiency. That's why our solutions are designed to help improve your productivity.



Standard R+E

CE Mark

Simple - CAT I, Intermediate - CAT II or Complex - CAT III

CE
CAT II

Trade

ISO 9001

This gives the requirements for quality management systems, is now firmly established as the globally implemented standard for providing assurance about the ability to satisfy quality requirements and to enhance customer satisfaction in supplier-customer relationships.

CERTIFIED ISO 9001:2015 COMPANY

Packaging

Unit Of Sale	Case	**Max Weight(kg)**	1.17
Case Dimension(LXWXH)(cm)	29.4 x 15.2 x 16.2	**Inner Pack Material**	LDPE

Product Data Sheet for KleenGuard® G60 Endurapro™ Level 3 Cut Resistant Gloves - Ambidextrous / Grey & Purple

Instructions

The open book pictogram - indicates that the user should read and understand the USER INSTRUCTIONS before using the garment.

Protect from heat and radioactive sources.

Keep Dry. Store in a cool, dry place.

Information

It is the employer's responsibility to assess the risk of the task to be undertaken and determine the correct choice of personal protective equipment for the task. The manufacturer, Kimberly-Clark, does not accept any responsibility for the incorrect choice or misuse of the personal protective equipment shown in this brochure. All care has been taken to ensure that the information contained herein is as accurate as possible at the time of publication, however errors may occur and legislation concerning personal protective equipment is under constant review and may change in the lifetime of this brochure. Accordingly, the specification for the products may be subject to change. We would advise you to contact INFOFAX if you have any queries concerning the products shown or the suitability of such products for a particular task. Always dispose of used protective equipment in a safe and appropriate manner in accordance with European, National and Local environmental regulations.

Websites	www.kcprofessional.co.uk	**Storage conditions**	Keep dry. Store in a cool dry place and shield from exposure to direct sunlight, intense artificial light or exposure to sources of radiation or ozone.
Durability	This product has a five years shelf life from the date of manufacture.		
Customer Service Number	For more information please contact Customer Service during regular office hours-0870 551 044		
Country of Origin	PAKISTAN		

(Code=09743999/LN=01/Country=GB/Type=C)