by Honeywell

Technical specifications

Webbing temporary horizontal lifeline 20 M

Reference : 1011160

Features



- Webbing tempory horizontal lifeline adjustable from 5 to 20 m
- Supplied in a bag
- Breaking strength : > 20 KN
- Maximum deflexion : 2m
- EN 795 classe b
- Weight : approx. 4,54 Kgs
- Temperature : -30°C to +50°C

• Webbing :
Polyester 35mm webbing
Breaking strength : > 4500 daN

• Webbing Adjuster :
bichromate steel adjuster
Breaking strength : > 1500 daN

DEFLEXION IN CASE OF FALL			
Length of the line	Number of users	Deflexion	Strength at the extremity
5 meters	2	0,50m	1450 daN
10 meters	2	1m	1300 daN
20 meters	2	2m	1200 daN

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS
35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97
Web site : www.honeywellsafety.com